

Safety Data Sheet

Printing date 01/03/2023

Revised On 01/03/2023

1 Identification of the substance and manufacturer

Trade name: GLOSS BLACK LACQUER
Product code: 0000160815
Recommended use: Paint and coatings application.
Uses advised against: Any that differs from the recommended use.
Manufacturer/Supplier: Seymour of Sycamore
 917 Crosby Avenue
 Sycamore, IL 60178 USA
 phone: 815-895-9101
 www.seymourpaint.com

Emergency telephone number: 1-800-255-3924

Seymour of Sycamore
 3041 Dougall Avenue, Suite 503
 Windsor, ONT N9E 1S3 CANADA
 phone: 800-435-4482
 www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.
 Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.
 Skin Irritation 2 H315 Causes skin irritation.
 Eye Irritation 2A H319 Causes serious eye irritation.
 Toxic to Reproduction 1B H360 May damage fertility or the unborn child.
 Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.
 Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information:
GHS Hazard pictograms

GHS02 GHS04 GHS07 GHS08

Signal word
Hazard statements

Danger
 Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 Causes skin irritation.

Precautionary statements

Causes serious eye irritation.
 May damage fertility or the unborn child.
 May cause drowsiness or dizziness.
 May cause damage to organs through prolonged or repeated exposure.
 Obtain special instructions before use.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.
 Do not breathe the dust/fume/gas/mist/vapors/spray.
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Call a poison center/doctor if you feel unwell.
 Specific treatment (see on this label).
 Take off contaminated clothing and wash it before reuse.
 If eye irritation persists: Get medical advice/attention.
 Store in a well-ventilated place.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone	25-50%
74-98-6	propane	10-15%
110-19-0	Isobutyl Acetate	10-15%
106-97-8	n-butane	5-10%
123-86-4	butyl acetate	5-10%
111-76-2	Glycol Ether EB	≥5-<10%
108-88-3	Toluene	1-5%
108-65-6	PM acetate	1-5%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

(Contd. on page 2)

Safety Data Sheet

Printing date 01/03/2023

Revised On 01/03/2023

Trade name: GLOSS BLACK LACQUER

(Contd. of page 1)

After eye contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing:	Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects:	Dizziness
Indication of any immediate medical attention needed:	No further relevant information available.

5 Fire-fighting measures

Extinguishing agents:	CO2, extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards:	Can form explosive gas-air mixtures.
Protective equipment for firefighters:	A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol.
Methods and material for containment and cleaning up:	Ensure adequate ventilation. Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling	Use only in well ventilated areas.
Storage requirements:	Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection**Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**

PEL (USA)	Long-term value: 2400 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 590 mg/m ³ , 250 ppm
TLV (USA)	Short-term value: 500 ppm Long-term value: 250 ppm A4, BEI

74-98-6 propane

PEL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV (USA)	see Appendix F Minimal oxygen content (D, EX)

110-19-0 Isobutyl Acetate

PEL (USA)	Long-term value: 700 mg/m ³ , 150 ppm
REL (USA)	Long-term value: 700 mg/m ³ , 150 ppm
TLV (USA)	Short-term value: 150 ppm Long-term value: 50 ppm

106-97-8 n-butane

REL (USA)	Long-term value: 1900 mg/m ³ , 800 ppm
TLV (USA)	Short-term value: 1000 ppm (EX)

123-86-4 butyl acetate

PEL (USA)	Long-term value: 710 mg/m ³ , 150 ppm
REL (USA)	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV (USA)	Short-term value: 150 ppm Long-term value: 50 ppm

111-76-2 Glycol Ether EB

PEL (USA)	Long-term value: 240 mg/m ³ , 50 ppm Skin
REL (USA)	Long-term value: 24 mg/m ³ , 5 ppm Skin
TLV (USA)	Long-term value: 20 ppm BEI, A3

(Contd. on page 3)

Safety Data Sheet

Printing date 01/03/2023

Revised On 01/03/2023

Trade name: GLOSS BLACK LACQUER

(Contd. of page 2)

108-88-3 Toluene

PEL (USA)	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV (USA)	Long-term value: 20 ppm BEI, OTO, A4

108-65-6 PM acetate

WEEL (USA)	Long-term value: 50 ppm
------------	-------------------------

Ingredients with biological limit values:**67-64-1 Acetone**

BEI (USA)	25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----------	--

111-76-2 Glycol Ether EB

BEI (USA)	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis)
-----------	--

108-88-3 Toluene

BEI (USA)	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

Hygienic protection:

Keep away from foodstuffs and animal feed. Wash hands after use.
Immediately remove all soiled and contaminated clothing.
Wash hands after use.
Store protective clothing separately.
Avoid contact with the eyes and skin.
Do not eat or drink while working.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection:

Nitrile gloves.
The glove material must be impermeable and resistant to the substance.

Eye protection:

Tightly sealed goggles

9 Physical and chemical properties

Appearance:	Aerosol.
Odor:	Aromatic
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range	Undetermined.
Boiling point:	-44 °C (-47.2 °F)
Flash point:	-19 °C (-2.2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.7 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapor density	Not determined.
Evaporation rate	Not applicable.

(Contd. on page 4)

Safety Data Sheet

Printing date 01/03/2023

Revised On 01/03/2023

Trade name: GLOSS BLACK LACQUER

(Contd. of page 3)

Partition coefficient: n-octonal/water: Not determined.

Solubility: Not determined.

Viscosity: Not determined.

Water: 0.0 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available.

Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

110-19-0 Isobutyl Acetate

Oral LD50 4,763 mg/kg (rbt)

123-86-4 butyl acetate

Oral LD50 14,000 mg/kg (rat)

Inhalative LC50/4 h >21 mg/l (rat)

111-76-2 Glycol Ether EB

Oral LD50 1,200 mg/kg (ATE)

Dermal LD50 1,480 mg/kg (rat)

Dermal LD50 400 mg/kg (rab)

108-65-6 PM acetate

Oral LD50 8,500 mg/kg (rat)

Inhalative LC50/4 h 35.7 mg/l (rat)

Information on toxicological effects: No data available.

Skin effects: No irritant effect.

Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number UN1950

DOT UN1950

DOT Aerosols, flammable

ADR 1950 Aerosols

Transport hazard class(es):

Class 2.1 Gases

Marine pollutant: No

Special precautions for user: Warning: Gases

EMS Number: F-D,S-U

Packaging Group: --

UN "Model Regulation": UN1950, Aerosols, 2.1

(Contd. on page 5)

Safety Data Sheet

Printing date 01/03/2023

Revised On 01/03/2023

Trade name: GLOSS BLACK LACQUER

(Contd. of page 4)

15 Regulatory information**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

111-76-2 Glycol Ether EB

108-88-3 Toluene

Toxic Substances Control Act**(TSCA):**

All hazardous ingredients are found on the inventory list of substances.

Canadian Domestic Substances List**(DSL):**

All ingredients are listed or exempted.

Consumer Product Safety**Comission (CPSC):**

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

1333-86-4 Carbon black

100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-88-3 Toluene

EPA:

67-64-1 Acetone

I

110-19-0 Isobutyl Acetate

D

111-76-2 Glycol Ether EB

NL

16 Other information**Contact:**

Regulatory Affairs