

3.5"

45382 TRIPLE REGRESSED GIMBAL

PROJECT: _____

TYPE: _____

DATE: _____

NOTES: _____



2700K . 3000K . 3500K . 4000K . 5000K



The Midway collection is a family of integrated led recessed lights available in sizes ranging from 2"-6". With their durable die cast aluminum bodies and built on CCT color selecting switch Midway family fixtures are aesthetically appealing, functional and extremely versatile. Their IC rated shallow bodies allow them to be used in most residential and commercial installations with or without insulation in the ceiling. Midway fixtures are available in white or black finish and come standard with a reliable phase dimming power supply.

SPECIFICATIONS

LIGHT HOUSING

- IC Airtight Cast aluminum body.
- Remodel application. C/W spring loaded clips.
- Mates to driver box with quick connector.
- Max Ceiling thickness 5/8".
- Approved for damp location.

DIMENSIONS

- Cut hole: $\phi 10 \frac{7}{8}" \times 3 \frac{3}{4}"$.
- Fixture: $\phi 11 \frac{5}{8}" \times 3 \frac{3}{16}"$ H.

ELECTRICAL

- 120 V Input class 2 constant current dimmable driver enclosed in junction box.
- TRIAC and ELV dimming.
- Min operating temperature (-4°F~104°F) (-20°C~40°C).

LIGHT MODULE

- 1 x 36W Integrated LED COB.
- Lumen maintenance 70% 50,000 hrs.
- CRI: 90+
- Beam angle: 38 degree.
- Kelvin (CCT): 27K | 30K | 35K | 40K | 50K
- Delivered Lumen: 1914 lm | 2025 lm | 2202 lm | 2300 lm | 2280 lm

CERTIFICATIONS



ORDERING GUIDE

MODEL	FINISH
45382-024	Black
45382-017	White

ACCESSORIES

45611-018
60"
2 pin Connector



45383-014
2LT/3LT
NEW CONSTRUCTION
PLATE
16 1/4" x 11 7/8"


$\phi 7 \frac{3}{8}" \times 3 \frac{3}{4}"$
 $\phi 10 \frac{13}{16}" \times 3 \frac{3}{4}"$



47205-017
15W REMOTE
EMERGENCY
BACKUP BATTERY



**NO IC BOX
REQUIRED**

	WATTS	LUMENS	KELVIN	DIMMABLE	CRI	BEAM ANGLE	ADJUSTABLE
 10 7/8" x 3 3/4"	36W	Up to 2300	CCT Selectable	TRIAC/ELV	90+	38°	15°

Driver
Box
included



FINISHES



024- Black



017- White

PRODUCT DIMENSIONS

