



IPL250-3 SHOWN

PART NUMBER	NO. OF PORTS	LENGTH
IPL250-3	3	2.93
IPL250-4	4	3.80
IPL250-5	5	4.66
IPL250-6	6	5.22
IPL250-8	8	7.24
IPL250-10	10	8.97

CONTACT NSi FOR SALES @ 800.321.5847

NOTES:

- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
- UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
- DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.
- COLD TEMPERATURE RATED TO -45°C.
- HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION, CHEMICAL AND UV RESISTANT.

		POLARIS SALES CO. INC
<small>PROPRIETARY AND CONFIDENTIAL</small>		<small>11625 PROSPEROUS DRIVE ODESSA, FL 33556</small>
<small>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.</small>		TITLE: INSULATED 250 CONNECTOR
<small>NAME</small> S.PARRY	<small>DATE</small> 06/2012	DWG. NO. IPL250-
MATERIAL: N/A		SCALE: N/A
		SHEET: 1 OF 1