



## HEAVY DUTY CRACK SEALER #20-702

This is a HEAVY DUTY non-rubberized aerosol driveway sealer that fills cracks to help prevent water intrusion, a leading cause of driveway deterioration. Ideal for use before a driveway is re-sealed. A convenient option for small jobs when hot applied asphalt equipment is not available. Unlike squeeze bottles, the pressurized can will deeply inject the sealer to fill cracks up to 3/8" wide and 1/2" deep.

Resists water and will not crack in cold temperatures. Can be top-coated with both oil or latex driveway seal coats.

### Suggested Uses:

Driveway and sidewalk cracks

### Packaging:

UPC Code	043281009751
Cans per case	12
Shipping weight per case	19 lbs.
Container	20 fluid ounce can
Label weight	18 ounces (484 grams)
Shipping Classification	limited quantity, UN 1950
Hazard Class	2.1

### Properties:

Cleanup	Paint/lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.80
Solids Content	~65%
MIR value	does not exceed 0.50
HAPs content	~10%
Storage Temperature	40-100F
Application Temperature	40-90F
Heat Resistance	300F
Resin System	Proprietary
Shelf life	Guaranteed for 2 years

### Dry Time\*:

To touch	30 minutes
Full cure	12 hours (depending on width of crack)

\*At 72F, 50% humidity

\*\*Curing time is extended with multiple coats and cooler temperatures\*\*

**Gloss\*:** Flat, <15

\*as measured on a 60 degree gloss meter

### Additional Information:

Cracks must be cleaned of all dirt, debris, and vegetation prior to application of crack sealant. An additional application may be needed after the initial coat has dried to fill deeper cracks. If necessary, use putty knife to level the product with the existing asphalt. When sealing cracks in concrete, use Seymour's 20-600 Concrete Re-New to conceal the color difference between the sealer and the concrete. Allow material to dry before opening to traffic.

12-3-2021