



### PROTECTION ON THE JOB SITE AND BEYOND

Safety is more than a word or an idea.

Safety is not only a feeling; it's a state of being.

We all want to live in a place of safety. We strive to safeguard our homes, our families and ourselves — so we can return home at the end of each day and continue to protect everyone and everything we love.

Enter RHINO Safety® Personal Protective Equipment.

Our full product line is rugged and tough enough to stand up to any job, all day and every day, giving you everything you need to protect what's most important, both on and off the job site.





#### **FEATURES**

- Full Brim and Cap Brim styles available
- Fully adjustable ratchet assembly

- Impact and penetration resistant
- Washable brow pad





#### CAP BRIM // SH-330 SERIES



- Fully adjustable 6-point ratchet assembly with snap lock
- HDPE construction
- Meets CE0086 EN397 : 2012
  - + A1: 2012
- Meets ANSI Z89.1 2014,
   Type 1 Class C

SPECIFICATIONS					
PART #	SIZE RANGE	HAT SIZE	HEAD CIRCUMFERENCE		
SH-330W	52 - 62 cm	6.5" - 7.75"	20.5" - 24.25"		
SH-330Y	52 - 62 cm	6.5" - 7.75"	20.5" - 24.25"		

SPECIFICA			
PART #	SIZE RANGE	HAT SIZE	HEAD CIRCUMFERENCE
SH-200W	52 - 62 cm	6.5" - 7.75"	20.5" - 24.25"
SH-200Y	52 - 62 cm	6.5" - 7.75"	20.5" - 24.25"

#### FULL BRIM // SH-200 SERIES



- Fully adjustable 4-point ratchet assembly with snap lock
- Polypropylene (PP) construction
- Meets CE0086 EN397 : 2012 + A1 : 2012
- Meets ANSI Z89.1 –
   2014, Type 1 Class E



#### **FEATURES**

- Impact Resistant
- Available in your choice of clear or grey lenses
- All models: ANSI Z87.1 2015, CE EN166
- Some models feature bi-focal magnification
- Durable construction for reliable eye protection





#### SG-100C

- Polycarbonate impact resistant lens
- Wrap around design increases protection and peripheral vision coverage
- · Polycarbonate temples



#### SG-101G

- Polycarbonate impact resistant lens
- Durable nylon frame with 99.9% UV protection for indoor/outdoor use
- Length adjustable temples



#### **SG-200C SERIES**

- Polycarbonate bi-focal impact resistant lens
- · Durable nylon frame
- Adjustable rubber nosepiece and temple tip



#### SG-300C

- Polycarbonate impact resistant lens
- Streamline design
- Adjustable rubber nosepiece and temple tip



#### SG-100G

- Polycarbonate impact resistant lens
- Wrap around design increases protection and peripheral vision coverage
- · Polycarbonate temples



#### SG-103C

- Polycarbonate impact resistant lens
- Bi-injected PC and rubber temple
- Hytrel inner frame with EVA foam



#### **SG-200G SERIES**

- Polycarbonate bi-focal impact resistant lens
- Durable nylon frame with 99.9% UV protection for indoor/outdoor use
- Adjustable rubber nosepiece and temple tip



#### SG-300G

- Polycarbonate impact resistant lens
- Streamline design with 99.9% UV protection for indoor/outdoor use
- Adjustable rubber nosepiece and temple tip



#### SG-101C

- Polycarbonate impact resistant lens
- Durable nylon frame
- Length adjustable temples



#### SG-103G

- Polycarbonate impact resistant lens
- Bi-injected PC and rubber temple
- · Hytrel inner frame with EVA foam

#### **SPECIFICATIONS BI-FOCAL** PART# LENS COLOR MAGNIFICATION **SG-100C** clear **SG100G** grey SG-101C clear SG-101G grey SG-103C clear SG-103G grey SG-200C15 clear +1.5 SG-200C20 clear +2.0 SG-200C25 +2.5 clear SG-200G15 grey +1.5SG-200G20 +2.0 grey SG-200G25 +2.5 grey SG-300C clear SG-300G grey



#### **FEATURES**

- Available in a range of sizes
- Lightweight, breathable and durable

- · Superior grip
- Styles and colors to suit every need





#### **GLV-100**

- · Comfort Grip
- · Smooth grey nitrile coated palm for excellent grip and dexterity
- 13 ga. white nylon, lightweight and breathable



#### **GLV-400**

- ANSI Cut Level A2
- · ISO Cut Level B
- · Polyurethane coated palm for better grip
- 13 ga. HPPE, lightweight and breathable



- ANSI Cut Level A7
- for better grip
- lightweight and breathable



#### **GLV-800**

- ANSI Cut Level A4
- ISO Cut Level D
- · Black sandy nitrile coated palm for better grip
- 13 ga. HPPE, lightweight and breathable



#### **GLV-200**

- · Comfort Grip
- · Black polyurethane coated palm for better grip
- 13 ga. black nylon, lightweight and breathable



#### **GLV-500**

- ANSI Cut Level A2
- ISO Cut Level B
- · Sandy nitrile coated palm for better grip
- 13 ga. HPPE, lightweight and breathable



#### **GLV-300**

- ANSI Cut Level A4
- · ISO Cut Level D
- Polyurethane coated palm for better grip
- 13 ga. HPPE, lightweight and breathable



- ANSI Cut Level A4
- · ISO Cut Level D
- · Foam nitrile coated palm for better grip
- 13 ga. HPPE, lightweight and breathable



#### **GLV-700**

- ISO Cut Level F
- · Polyurethane coated palm
- 13 ga. HPPE,



#### **GLV-900**

- ANSI Cut Level A4
- ISO Cut Level D
- · Foam nitrile coated palm for better grip
- 13 ga. aramid fiber steel, lightweight and breathable

SPECIFICATIONS				
PART #	COLOR	PALM COATING	SIZES AVAILABLE	CERTIFICATION
GLV-100	white	grey	M, L, XL	CE EN388 - 4121X
GLV-200	black	black	M, L, XL	CE EN388 - 4131X
GLV-300	grey	black	M, L, XL	CE EN388 - 4X43D
GLV-400	grey	black	M, L, XL	CE EN388 - 4X42B
GLV-500	black/ white	grey	M, L, XL	CE EN388 - 4X43B
GLV-600	black/ white	black	M, L, XL	CE EN388 - 4X44D
GLV-700	red	black	M, L, XL	CE EN388 - 4X43F
GLV-800	black/ white	black	M, L, XL	CE EN388 - 4X43D
GLV-900	green	black	M, L, XL	CE EN388 - 4X42D
]				



Model Number Shown// EM-138









#### STANDARD // EM-107



- Comfort cushioned adjustable vented headband
- All-day comfort cushioned ear cups
- Adjustable pivoting ear cups





SPECIFICATIONS				
	PART #	NOISE REDUCTION RATING	CE CERTIFICATION	ANSI CERTIFICATION
	EM-107	24dB	EN352	S3.19 - 1974

Noise Reduction Rating 24 DECIBELS
(WHEN USED AS DIRECTED)

THE RANGE OF NOISE REDUCTION RATINGS FOR EXISTING HEARING PROTECTORS IS APPROXIMATELY 0 TO 30 (HIGHER NUMBERS DENOTE GREATER EFFECTIVENESS)

NSI INDUSTRIES LLC. HUNTERSVILLE, NC

Part # EM-107

Federal law prohibits removal of this label prior to purchase.



LABEL REQUIRED BY U.S. E.P.A. REGULATION 40 CFR PART 211

## SPECIFICATIONS PART # NOISE REDUCTION RATING CE CERTIFICATION ANSI CERTIFICATION EM-138 21dB EN352 S3.19 - 1974

#### Noise Reduction Rating

21 DECIBELS
(WHEN USED AS DIRECTED)

THE RANGE OF NOISE REDUCTION RATINGS FOR EXISTING HEARING PROTECTORS IS APPROXIMATELY 0 TO 30 (HIGHER NUMBERS DENOTE GREATER EFFECTIVENESS)

NSI INDUSTRIES LLC. HUNTERSVILLE, NC

Part # EM-138

Federal law prohibits removal of this label prior to purchase.



LABEL REQUIRED BY U.S. E.P.A. REGULATION 40 CFR PART 211 SUBPART B

#### LOW PROFILE // EM-138



- Comfort cushioned adjustable vented headband
- All-day comfort cushioned ear cups
- Low profile, adjustable pivoting ear cups













#### FOAM EAR PLUGS // FEP SERIES



- Foam construction for a comfortable fit
- · Hearing protection helps reduce exposure to hazardous noise and other loud sounds

<b>€</b> P*	
A (L)	NRR 32 dB
4NSI	32 dB
S3.19-1974	

SPECIFICATIONS					
PART #	QUANTITY	PACKAGING TYPE	NOISE REDUCTION RATING		
FEP-80-O-CB	80 PAIRS	CLEAR BOX	32dB		
FEP-200-O-DB	200 PAIRS	DISPENSER BOX	32dB		
FEP-200-O-J	200 PAIRS	JAR	32dB		

Noise Reduction Rating

32 DECIBELS (WHEN USED AS DIRECTED)

THE RANGE OF NOISE REDUCTION RATINGS FOR EXISTING HEARING PROTECTORS IS APPROXIMATELY 0 TO 30 (HIGHER NUMBERS DENOTE GREATER EFFECTIVENESS)

NSI INDUSTRIES LLC. HUNTERSVILLE, NC

Part # FEP series



SPECIFICATIONS				
PART #	QUANTITY	PACKAGING TYPE	NOISE REDUCTION RATING	
TEP-100-OB- DB	100 PAIRS	DISPENSER BOX	25dB	

#### Noise Reduction Rating

DECIBELS

(WHEN USED AS DIRECTED)

THE RANGE OF NOISE REDUCTION RATINGS FOR EXISTING HEARING PROTECTORS IS APPROXIMATELY 0 TO 30 (HIGHER NUMBERS DENOTE GREATER EFFECTIVENESS)

NSI INDUSTRIES LLC. HUNTERSVILLE, NC

Part # TEP-100-OB-DB

**\$EPA** 

#### TETHERED EAR PLUGS // TEP SERIES



- Tethered design keeps ear plugs handy
- Hearing protection helps reduce exposure to hazardous noise and other loud sounds







#### PARTICULATE RESPIRATOR // DM-400

- NIOSH approved
- Adjustable nosepiece
- Comfortable, secure straps



SPECIFIC	SPECIFICATIONS				
PART #	NIOSH RATING	CARTON CONTAINS			
DM-400	N95	20			





#### SAFETY VEST // SV-600-UCX



- 5 Point Break-Away Safety Vest
- 100% polyester, silver reflective material
- · High visibility, fluorescent yellow with "X back"
- 100% polyester fluorescent mesh
- Withstands 30 wash cycles per washing instructions
- Type R Class 2

SPECIFICATIONS				
PART #	ТҮРЕ	CLASS	SIZE	
SV-600-UCX	R	2	ONE SIZE	





- ▲ WARNING: Cancer and reproductive harm. www.P65Warnings.ca.gov.
- ▲ AVERTISSEMENT: Cancer et effets nocifs sur la reproduction.www.P65Warnings.ca.gov.

  ADVERTENCIA: Cáncer y daños al sistema reproductivo. www.P65Warnings.ca.gov.



# IN SAFETY®