



WIRE ENTRY PORT
 WIRE RANGE: #4 - #14 AWG
 PRE-FILLED W/ OXIDE INHIBITOR

IPL4-3 SHOWN

PART NUMBER	NO. OF PORTS	LENGTH
IPL4-3	3	1.55
IPL4-4	4	1.97
IPL4-5	5	2.39
IPL4-6	6	2.81
IPL4-8	8	3.66
IPL4-10	10	4.51
IPL4-12	12	5.35
IPL4-14	14	6.20

CONTACT NSi FOR SALES @ 800.321.5847

- NOTES:
- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
 - UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
 - DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.
 - COLD TEMPERATURE RATED TO -45°C.
 - HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION, CHEMICAL AND UV RESISTANT.

		POLARIS SALES . CO . INC	
PROPRIETARY AND CONFIDENTIAL		11625 PROSPEROUS DRIVE ODESSA, FL 33556	
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.		TITLE: INSULATED #4 CONNECTOR	
		DWG. NO. IPL4-	
DRAWN BY	NAME	DATE	
	L. HILL	07/14/10	
MATERIAL: N/A		SCALE: N/A	SHEET: 1 OF 1