

## TOOL CRIB OPEN GEAR LUBE #620-1501



A heavy duty black lubricant that offers superior lubricity and adhesion to gears. Improves the gear efficiency and will not dry out or leave harmful deposits. Open Gear Lube is unaffected by salt water, detergents, and most chemicals. Performs well under extreme pressures and temperatures. An extension tube is furnished for pinpoint application.

### Suggested Uses:

- Open gears
- Cams
- Slides
- Roller chains
- Slow moving bearings
- Latches
- Construction equipment

### Packaging:

|                          |                           |
|--------------------------|---------------------------|
| UPC Code                 | 043281006972              |
| Cans per case            | 6                         |
| Shipping weight per case | 9 lbs.                    |
| Container                | 20 fluid ounce can        |
| Label weight             | 15 ounces (426 grams)     |
| Shipping Classification  | Limited quantity, UN 1950 |
| Hazard Class             | 2.1                       |

### Properties:

|                             |                          |
|-----------------------------|--------------------------|
| Cleanup                     | Paint or lacquer thinner |
| Flammability                | Extremely Flammable      |
| Flash point                 | -4F                      |
| Specific Gravity            | 0.75                     |
| Solids Content              | 49%                      |
| VOC content                 | 40%                      |
| HAPs content                | 0                        |
| Storage Temperature         | 40-90F                   |
| Application Temperature     | 40-100F                  |
| Lubricity Rating            | Excellent                |
| Active Ingredient           | Asphalt and Pine Tar     |
| Appearance                  | Black, tacky             |
| Operating Speed             | 500+ RPM                 |
| High Temperature Resistance | 250F                     |
| Low Temperature Resistance  | -10F                     |
| Heavy Load Capability       | Extremely Heavy Loads    |
| Shelf life                  | Guaranteed for 2 years   |
| Food contact rating         | No                       |

### Dry Time\*:

Not applicable

### Gloss:

Not applicable

12-11-2021