





SECTION A-A

NOTES:

- 1. FLASH TO BE HELD TO A MINIMUM AND MAY NOT WEB ACROSS HOLES.
- 2. I.D. AND O.D. CONCENTRICITY .020.
- 3. ALL OTHER DIMENSIONS ±.015.
- 4. MATERIAL: BLACK NEOPRENE 50-60 DUROMETER
- 5. REPLACES SRB-35833

J. K.	FLACES S	KD-33033									
REV.	DATE	CHANGE		UNLESS OTHERWISE SPECIFIED:		NAME	DATE		8		
Α	11/30/00	DRAWING RELEASEI	D	DIMENSIONS ARE IN INCHES TOLERANCES:	DRAWN	JCN	7/15] (E	BRIDGEF	ORT	
D	7/1//15	DEDDAMNI		FRACTIONAL ± 1/64 ANGULAR: MACH ± 1° BEND ± 1°	CHECKED						
В	7/16/15	REDRAWN		ONE PLACE DECIMAL ±.015 TWO PLACE DECIMAL ±.010 THREE PLACE DECIMAL ±.005	ENG APPR.			TITLE:	BUSHING		
					MFG APPR.						
					Q.A.						
				MATERIAL SEE NOTE	THE INFORMATION DRAWING IS THE S REMKE INDUSTRIES IN PART OR AS A V	ANY REPRODUCTION /HOLE WITHOUT THE	SIZE DWG.	NG. NO. SBF-5001			
				DO NOT SCALE DRAWING	WRITTEN PERMISSION OF REMKE INDUSTIRES IS PROHIBITED.		SCALE: 1:1		SHEET 1 OF 1		
		5 4		3	2			1		1	

