



POLARIS®

DATA CENTER LUG MATRIX

LONG BARREL COMPRESSION CONNECTORS FOR DATA CENTERS

CONNECTOR SIZE	L SERIES COPPER	L-N SERIES COPPER	AL SERIES ALUMINUM	AL-N SERIES ALUMINUM	DETAILS
#6		X			TYPICAL GROUNDING SIZE
#4		X			
#1	X	X	X		
1/0	X	X	X	X	MAX GROUNDING SIZE
2/0	X	X	X	X	
4/0	X	X	X	X	
250		X		X	
350		X		X	NARROW TANG NEEDED FOR SOME APPLICATIONS
400		X		X	
500		X		X	
600		X		X	
750		X		X	

Inspection window is mandatory on certain specs when copper conductor is used.

POLARIS COMPRESSION CONNECTOR SERIES

L (P) Series - Copper Long Barrel 1 Hole

L-B Series - Copper Long Barrel 1 Hole Flared End

L-N (P) Series - Copper Long Barrel 2 Hole

L-NB Series - Copper Long Barrel 2 Hole Flared End

AL Series - Aluminum Long Barrel 1 Hole


AL-N Series - Aluminum Long Barrel 2 Hole

AL-N-NT Series - Aluminum Long Barrel 2 Hole Narrow Tang

Flared End - For fine stranded cables

(P) - Indicates inspection window or "peep hole"

Narrow Tang - For space constrained installations



Scan for more information

