

# Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/13/2026

Revised On 01/13/2026

## 1 Identification

**Trade name:** COLD GALV  
**Other means of identification**

**Product code:** 0000201645  
**Recommended use:** Paint and coatings application.  
**Uses advised against:** Any that differs from the recommended use.  
**Manufacturer/Supplier:** Seymour of Sycamore  
 917 Crosby Avenue  
 Sycamore, IL 60178 USA  
 phone: 815-895-9101  
 www.seymourpaint.com

**Emergency telephone number:** 1-800-255-3924

Seymour of Sycamore  
 3041 Dougall Avenue, Suite 503  
 Windsor, ONT N9E 1S3 CANADA  
 phone: 800-435-4482  
 www.seymourpaint.com

## 2 Hazard(s) identification

### Classification of the substance or mixture

Aerosols 1	H222-H229	Extremely flammable aerosol. Pressurized container: may burst if heated.
Skin irritation 2	H315	Causes skin irritation.
Reproductive toxicity 2	H361	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure) 3	H336	May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure) 2	H373	May cause damage to organs through prolonged or repeated exposure.

### Additional information:

### GHS Hazard pictograms



GHS02 GHS07 GHS08

### Signal word

Danger

### Hazard-determining components of labeling:

Toluene

Isopropyl Alcohol

### Hazard statements

Extremely flammable aerosol. Pressurized container: may burst if heated.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

### Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Avoid breathing fume/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Wear protective gloves.

If on skin: Wash with plenty of water.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).

Dispose of contents/container in accordance with local/regional/national/international regulations.

### Effects of chronic overexposure:

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

### Classification according to (d)(1)(ii) of § 1910.1200

The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.

### Hazards not otherwise classified

There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

## 3 Composition/information on ingredients

### Chemical characterization: Mixtures

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

### Dangerous components:

108-88-3	Toluene	≥20-≤25%
74-98-6	propane	10-15%

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/13/2026

Revised On 01/13/2026

Trade name: COLD GALV

(Contd. of page 1)

106-97-8	n-butane	5-10%
64742-47-8	Mineral Spirits	1-5%
67-63-0	Isopropyl Alcohol	1-5%

## 4 First-aid measures

### Description of first aid measures

#### After inhalation:

Supply fresh air; consult doctor in case of complaints.

#### After skin contact:

Remove contaminated clothing. Wash exposed area with soap and water.

#### After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

#### After swallowing:

Rinse out mouth and then drink plenty of water.

Rinse mouth with water. Do not induce vomiting.

### Most important symptoms and effects:

Dizziness

### Indication of any immediate medical attention needed:

No further relevant information available.

## 5 Fire-fighting measures

### Extinguishing media

### Extinguishing agents:

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray.

### Special hazards:

Can form explosive gas-air mixtures.

### Protective equipment for firefighters:

A respiratory protective device may be necessary.

### Additional information

Cool endangered receptacles with water spray.

## 6 Accidental release measures

### Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Do not allow product to reach sewage systems or ground water.

### Environmental precautions:

### Methods and material for containment and cleaning up:

Ensure adequate ventilation.

## 7 Handling and storage

### Precautions for safe handling

Use only in well ventilated areas.

### Fire/explosion protection:

Keep respiratory protective device available.

Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.

### Conditions for safe storage:

### Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

## 8 Exposure controls/personal protection

### Components with limit values that

### require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

### 108-88-3 Toluene

PEL Long-term value: 200 ppm  
Ceiling limit value: 300; 500\* ppm  
\*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 375 mg/m<sup>3</sup>, 100 ppm

TLV Long-term value: 20 ppm  
BEI, OTO, A4

### 74-98-6 propane

PEL Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm

REL Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm

TLV see Appendix F Minimal oxygen content ( D, EX)

### 106-97-8 n-butane

REL Long-term value: 1900 mg/m<sup>3</sup>, 800 ppm

TLV Short-term value: 2370 mg/m<sup>3</sup>, 1000 ppm  
(EX)

### 67-63-0 Isopropyl Alcohol

PEL Long-term value: 980 mg/m<sup>3</sup>, 400 ppm

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/13/2026

Revised On 01/13/2026

**Trade name: COLD GALV**

(Contd. of page 2)

REL	Short-term value: 1225 mg/m <sup>3</sup> , 500 ppm Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
TLV	Short-term value: 984 mg/m <sup>3</sup> , 400 ppm Long-term value: 491 mg/m <sup>3</sup> , 200 ppm BEI, A4

**Ingredients with biological limit values:****108-88-3 Toluene**

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

**67-63-0 Isopropyl Alcohol**

BEI	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----	---

**Exposure controls****Hygienic protection:**

Keep away from foodstuffs and animal feed. Wash hands after use.  
Immediately remove all soiled and contaminated clothing.  
Wash hands after use.  
Store protective clothing separately.  
Do not eat or drink while working.

**Breathing equipment:**

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:**

Nitrile gloves.  
The glove material must be impermeable and resistant to the substance.

**Eye protection:**

Tightly sealed goggles

**9 Physical and chemical properties****General Information:**

<b>Physical state</b>	Aerosol
<b>Odor:</b>	Aromatic
<b>Odor threshold:</b>	Not determined.
<b>Melting point/Melting range</b>	Undetermined.
<b>Boiling point:</b>	-44 °C (-47.2 °F)
<b>Flammability:</b>	Extremely flammable.
<b>Lower Explosion Limit:</b>	1.7 Vol %
<b>Upper Explosion Limit:</b>	10.9 Vol %
<b>Flash point:</b>	-19 °C (-2.2 °F)
<b>Decomposition temperature:</b>	Not determined.
<b>pH-value:</b>	Not determined.
<b>Viscosity:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
<b>Dynamic:</b>	Not determined.
<b>Solubility:</b>	Not determined.
<b>Vapor pressure:</b>	40 PSI 2750 hPa
<b>Vapor Pressure:</b>	40 PSI, 2750 hPa
<b>Relative Density:</b>	Between 0.77 and 0.85 (Water equals 1.00)
<b>Vapor density</b>	Not determined.
<b>Particle characteristics</b>	Not applicable.
<b>Appearance:</b>	Aerosol.
<b>Ignition temperature:</b>	Product is not self-igniting.
<b>Danger of explosion:</b>	Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.
<b>Evaporation rate</b>	Not applicable.
<b>Partition coefficient: n-octonal/water:</b>	Not determined.

**10 Stability and reactivity**

<b>Conditions to avoid:</b>	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
-----------------------------	--

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/13/2026

Revised On 01/13/2026

Trade name: COLD GALV

(Contd. of page 3)

**Possibility of hazardous reactions:** No dangerous reactions known.  
**Conditions to avoid** No further relevant information available.  
**Incompatible materials:** No further relevant information available.  
**Hazardous decomposition:** No dangerous decomposition products known.

## 11 Toxicological information

### LD/LC50 values that are relevant for classification:

#### 67-63-0 Isopropyl Alcohol

Oral	LD50	4,570 mg/kg (rat)
Dermal	LD50	13,400 mg/kg (rab)
Inhalative	LC50/4 h	30 mg/l (rat)

**Skin effects:** Irritant to skin and mucous membranes.  
**Eye effects:** Irritating effect.  
**Sensitization:** No sensitizing effects known.  
**Aspiration hazard**  
**Interactive effects** No interactive effects between components are known.

### IARC (International Agency for Research on Cancer)

67-63-0 | Isopropyl Alcohol

3

### NTP (National Toxicology Program)

None of the ingredients is listed.

### Alternative sources for toxicological information

No non-standard sources for toxicological information where used.

## 12 Ecological information

**Toxicity**  
**Aquatic toxicity:** Hazardous for water, do not empty into drains.  
**Persistence and degradability:** The product is degradable after prolonged exposure to natural weathering processes.  
**Other information:** This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents.  
**Bioaccumulative potential:** No further relevant information available.  
**Mobility in soil:** No further relevant information available.  
**Results of PBT and vPvB assessment**  
**PBT:** Not applicable.  
**vPvB:** Not applicable.  
**Other adverse effects:** No further relevant information available.

## 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

### Waste treatment methods

**Recommendation:** Completely empty cans should be recycled.

## 14 Transport information

**UN-Number** UN1950  
**DOT** UN1950  
 UN1950  
**UN proper shipping name:**  
**DOT** AEROSOLS, flammable  
**Transport hazard class(es):**  
**Class** 2.1 Gases  
**Marine pollutant:** Yes  
 Symbol (fish and tree)  
**DOT**  
**Packaging Group:** --  
**Special precautions for user:** Warning: Gases  
**EMS Number:** F-D,S-U

## 15 Regulatory information

### Reglamentación y legislación en materia de seguridad, salud y medio ambiente específicas para la sustancia o la mezcla

#### Toxic Substances Control Act

**(TSCA):** All ingredients are found on the inventory list of substances.

#### Consumer Product Safety

**Comission (CPSC):** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

### Hazardous Air Pollutants

108-88-3 | Toluene

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/13/2026

Revised On 01/13/2026

**Trade name: COLD GALV**

(Contd. of page 4)

**California Proposition 65 chemicals known to cause cancer:**

None of the ingredients in this product are listed.

**Prop 65 chemicals known to cause birth defects or reproductive harm:**

108-88-3 Toluene

**CANADIAN ENVIRONMENTAL PROTECTION ACT:**

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

**EPA:**

7440-66-6 zinc powder

D, I, II

1314-13-2 zinc oxide

D, I, II

**GHS label elements****Precautionary statements**

The product is classified and labeled according to the Globally Harmonized System (GHS).  
 Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 Do not spray on an open flame or other ignition source.  
 Do not pierce or burn, even after use.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Avoid breathing fume/mist/vapors/spray.  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
 Wear protective gloves.  
 If on skin: Wash with plenty of water.  
 If inhaled: Remove person to fresh air and keep comfortable for breathing.  
 If exposed or concerned: Get medical advice/attention.  
 Call a poison center/doctor if you feel unwell.  
 Specific treatment (see on this label).  
 Get medical advice/attention if you feel unwell.  
 Take off contaminated clothing and wash it before reuse.  
 If skin irritation occurs: Get medical advice/attention.  
 Store in a well-ventilated place.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).  
 Dispose of contents/container in accordance with local/regional/national/international regulations.  
 A Chemical Safety Assessment has not been carried out.

**Chemical safety assessment:****16 Other information**

This product was manufactured in the U.S.A.

The information on this sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Contact:**

Regulatory Affairs

**Date of preparation**

01/13/2026

**Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 PNEC: Predicted No-Effect Concentration (REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 EPA: Environmental Protection Agency  
 IARC: International Agency for the Research of Cancer  
 NIOSH: National Institute for Occupational Safety and Health  
 TSCA: Toxic Substances Control Act  
 CPSC: Consumer Product Safety Commission  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 BEI: Biological Exposure Limit  
 Aerosols 1: Aerosols – Category 1  
 Skin irritation 2: Skin corrosion/irritation – Category 2  
 Reproductive toxicity 2: Reproductive toxicity – Category 2  
 Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3  
 Specific target organ toxicity (repeated exposure) 2: Specific target organ toxicity (repeated exposure) – Category 2