



REMOVABLE CAP
TO TIGHTEN SCREW
(REPLACE WHEN COMPLETE)

REMOVABLE CAP
FOR DUAL ENTRY
(INSERT IN OTHER SIDE)

5/16 INTERNAL
HEX PRESSURE SCREW



WIRE ENTRY PORT
WIRE RANGE: 350KCMIL - #6 AWG
PRE-FILLED W/ OXIDE INHIBITOR



IPLDS350-10 SHOWN

NSI PART NUMBER	UL PART NUMBER	NO. OF PORTS	LENGTH
IPLDS350-4	IS4E	4	2.55
IPLDS350-6	IS6E	6	3.60
IPLDS350-8	IS8E	8	4.65
IPLDS350-10	IS10E	10	5.70
IPLDS350-12	IS12E	12	6.75
IPLDS350-14	IS14E	14	7.80

CONTACT NSI FOR SALES @ 800.321.5847

		POLARIS SALES . CO . INC	
<small>PROPRIETARY AND CONFIDENTIAL</small>		<small>11625 PROSPEROUS DRIVE ODESSA, FL 33556</small>	
<small>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.</small>		TITLE: INSULATED STACKED DUAL ENTRY (BOTTOM ROW) 350 CONNECTOR	
<small>NAME</small>		<small>DATE</small>	
<small>DRAWN BY</small> S.PARRY		<small>DATE</small> 06/2012	
<small>MATERIAL:</small> N/A		<small>SCALE:</small> N/A	
<small>DWG. NO.</small>		<small>SHEET:</small> 1 OF 1	
IPLDS350-			

NOTES:

- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
- UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
- DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.
- COLD TEMPERATURE RATED TO -45°C.
- HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION, CHEMICAL AND UV RESISTANT.