


- FEATURES:**
- 1. Material: Tin Plated CU
 - 2. UL listed for U.S. & Canada.
 - 3. Wire connector rated for 35Kv max.
 - 4. Class B/C compressed, concentric, and compact copper conductor only.
 - 5. Expanded wire range when installed with dieless NSi compression tool (N12ID).
 - 6. Dimensions are for reference only, tolerance is +/- .06".


L Series: L75048



PROGRAM:	SOLIDWORKS
UPDATED:	4/2022
SALES REV:	A
SIZE:	B (11x17)



SCALE 1:1



7

			COPPER COMPRESSION CONNECTOR TOOL AND DIE CHART (# OF CRIMPS)									
			NSI				GREENLEE		ILSCO	BURNDY	T&B	HUSKIE
WIRE SIZE	STRIP LENGTH	DIE COLOR	EXPANDED WIRE RANGE W/N12ID	N1240 SERIES	NSI-12	NSI-12	1240 SERIES		ILC-12/ILC-15 SERIES	Y-35. Y750, PAT 750	TBM-15, TBM-14M	EP510C
750kcmil	2-13/16"	BLACK	750kcmil-500kcmil	KC12-750 (2)	CD21 (4)	HT41BP (4)	KC12-750 (2)	ILD-17 (4)	KC12-750 (2)	U39RT (4)	15515-CK (4)	HT41BP (4) CD21 (4)