

GET A LINEBACKER® ON YOUR TEAM.



LINEBACKER® OEM-GRADE MOTOR RUN CAPACITORS

A Supco® BRAND

Sure to catch an eye on the shelf, the Linebacker® is designed to reduce inventory, perform like its OEM counterparts and save you money.

NEVER SETTLE FOR JUST GOOD ENOUGH

Linebacker® Motor Run Capacitors are built for longevity and performance. Engineered by an ISO certified manufacturer with over twenty years' experience in OEM capacitor fabrication, Linebacker® capacitors come off the same production line as the OEM, and are 100% in-line production tested to the same rigorous international standards.

Built Tough | Meets EIA-456A accelerated life test at 70° C for 60,000 hours

Works Harder | Life tested to 85° C operating temperature for 10,000 cycles

Approved | US and Canada UL approved (C22.2NO.190)

Protected | 10,000 AFC pressure sensitive short circuit interrupting capability

Tested | Continuous life tested, oil leak tested and dielectric tested for insulation effectiveness

THE GUTS TO GET IT DONE.

Linebacker® capacitors are manufactured with thick polypropylene foil to handle increased operating temperatures, and PCB-free oil to prevent over-heating.

Voltage	Up to 440 VAC
Standard Tolerance	+/- 5%
Operating Temperature	-40° C to 85° C
Foil Thickness	6.0 µm +/- 5%

SLIM YOUR STOCK

(Trust us, it works.)

A common misconception is that you must have a 370V capacitor to replace a 370V capacitor. However, the voltage rating on a run capacitor displays the voltage that should not be exceeded. Stocking Linebacker® capacitors means with less parts you can handle applications up to 440V, so those 370V applications are good to go. Now you can start making plans for that extra shelf space you've just gained.

WE'VE GOT YOUR BACK.

Premium performance, not price.

SUPCO's long-standing reputation in manufacturing and sourcing allows us to offer a top-grade capacitor at extremely competitive market prices.

3 Year Warranty.

We stand behind the quality and performance of the Linebacker® with a 3-year warranty from the date of purchase.



SINGLE ROUND

Supco® P/N	MF Rating
LCR10X440R	10 MFD X 440V
LCR12.5X440R	12.5 MFD X 440V
LCR15X440R	15 MFD X 440V
LCR17.5X440R	17.5 MFD X 440V
LCR20X440R	20 MFD X 440V
LCR25X440R	25 MFD X 440V
LCR2X440R	2 MFD X 440V
LCR30X440R	30 MFD X 440V
LCR35X440R	35 MFD X 440V
LCR3X440R	3 MFD X 440V
LCR40X440R	40 MFD X 440V
LCR45X440R	45 MFD X 440V
LCR4X440R	4 MFD X 440V
LCR50X440R	50 MFD X 440V
LCR55X440R	55 MFD X 440V
LCR5X440R	5 MFD X 440V
LCR60X440R	60 MFD X 440V
LCR6X440R	6 MFD X 440V
LCR7.5X440R	7.5 MFD X 440V
LCR70X440R	70 MFD X 440V
LCR80X440R	80 MFD X 440V
LCR90X440R	90 MFD X 440V

Supco® P/N	MF Rating
LCR10X440	10 MFD X 440V
LCR12.5X440	12.5 MFD X 440V
LCR15X440	15 MFD X 440V
LCR17.5X440	17.5 MFD X 440V
LCR2.5X440	2.5 MFD X 440V
LCR20X440	20 MFD X 440V
LCR25X440	25 MFD X 440V
LCR2X440	2 MFD X 440V
LCR30X440	30 MFD X 440V
LCR35X440	35 MFD X 440V
LCR3X440	3 MFD X 440V
LCR40X440	40 MFD X 440V
LCR45X440	45 MFD X 440V
LCR4X440	4 MFD X 440V
LCR50X440	50 MFD X 440V
LCR55X440	55 MFD X 440V
LCR5X440	5 MFD X 440V
LCR60X440	60 MFD X 440V
LCR65X440	65 MFD X 440V
LCR6X440	6 MFD X 400V
LCR7.5X440	7.5 MFD X 440V
LCR70X440	70 MFD X 440V
LCR75X440	75 MFD X 440V
LCR80X440	80 MFD X 440V

DUAL ROUND

Supco® P/N	MF Rating
LCD10+5X440R	10+5 MFD X 440V
LCD15+5X440R	15+5 MFD X 440V
LCD20+15X440R	20+15 MFD X 440V
LCD20+5X440R	20+5 MFD X 440V
LCD25+10X440R	25+10 MFD X 440V
LCD25+15X440R	25+15 MFD X 440V
LCD25+3X440R	25+3 MFD X 440V
LCD25+5X440R	25+5 MFD X 440V
LCD25+7.5X440R	25+7.5 MFD X 440V
LCD30+3X440R	30+3 MFD X 440V
LCD30+4X440R	30+4 MFD X 440V
LCD30+5X440R	30+5 MFD X 440V
LCD30+7.5X440R	30+7.5 MFD X 440V
LCD35+10X440R	35+10 MFD X 440V
LCD35+3X440R	35+3 MFD X 440V
LCD35+4X440R	35+4 MFD X 440V
LCD35+5X440R	35+5 MFD X 440V
LCD35+6X440R	35+6 MFD X 440V
LCD35+7.5X440R	35+7.5 MFD X 440V
LCD40+10X440R	40+10 MFD X 440V
LCD40+3X440R	40+3 MFD X 440V
LCD40+4X440R	40+4 MFD X 440V
LCD40+5X440R	40+5 MFD X 440V
LCD40+6X440R	40+6 MFD X 440V
LCD40+7.5X440R	40+7.5 MFD X 440V
LCD45+10X440R	45+10 MFD X 440V
LCD45+3X440R	45+3 MFD X 440V
LCD45+4X440R	45+4 MFD X 440V
LCD45+5X440R	45+5 MFD X 440V

Supco® P/N	MF Rating
LCD10+5X440	10+5 MFD X 440V
LCD15+4X440	15+4 MFD X 440V
LCD15+5X440	15+5 MFD X 440V
LCD20+15X440	20+15 MFD X 440V
LCD20+5X440	20+5 MFD X 440V
LCD25+10X440	25+10 MFD X 440V
LCD25+5X440	25+5 MFD X 440V
LCD25+7.5X440	25+7.5 MFD X 440V
LCD30+10X440	30+10 MFD X 440V
LCD30+4X440	30+4 MFD X 440V
LCD30+5X440	30+5 MFD X 440V
LCD30+7.5X440	30+7.5 MFD X 440V
LCD35+10X440	35+10 MFD X 440V
LCD35+3X440	35+3 MFD X 440V
LCD35+4X440	35+4 MFD X 440V
LCD35+5X440	35+5 MFD X 440V
LCD35+7.5X440	35+7.5 MFD X 440V

Supco® P/N	MF Rating
LCD45+6X440R	45+6 MFD X 440V
LCD45+7.5X440R	45+7.5 MFD X 440V
LCD50+10X440R	50+10 MFD X 440V
LCD50+12.5X440R	50+12.5 MFD X 440V
LCD50+5X440R	50+5 MFD X 440V
LCD50+7.5X440R	50+7.5 MFD X 440V
LCD55+10X440R	55+10 MFD X 440V
LCD55+5X440R	55+5 MFD X 440V
LCD55+7.5X440R	55+7.5 MFD X 440V
LCD60+10X440R	60+10 MFD X 440V
LCD60+12.5X440R	60+12.5 MFD X 440V
LCD60+15X440R	60+15 MFD X 440V
LCD60+3X440R	60+3 MFD X 440V
LCD60+5X440R	60+5 MFD X 440V
LCD60+7.5X440R	60+7.5 MFD X 440V
LCD65+10X440R	65+10 MFD X 440V
LCD65+5X440R	65+5 MFD X 440V
LCD70+10X440R	70+10 MFD X 440V
LCD70+5X440R	70+5 MFD X 440V
LCD70+7.5X440R	70+7.5 MFD X 440V
LCD75+10X440R	75+10 MFD X 440V
LCD75+5X440R	75+5 MFD X 440V
LCD75+7.5X440R	75+7.5 MFD X 440V
LCD80+10X440R	80+10 MFD X 440V
LCD80+5X440R	80+5 MFD X 440V
LCD80+7.5X440R	80+7.5 MFD X 440V
LCD85+10X440R	85+10 MFD X 440V
LCD85+5X440R	85+5 MFD X 440V
LCD85+7.5X440R	85+7.5 MFD X 440V

Supco® P/N	MF Rating
LCD35+8.5X440	35+8.5 MFD X 440V
LCD40+3X440	40+3 MFD X 440V
LCD40+5X440	40+5 MFD X 440V
LCD40+7.5X440	40+7.5 MFD X 440V
LCD45+5X440	45+5 MFD X 440V
LCD45+7.5X440	45+7.5 MFD X 440V
LCD50+5X440	50+5 MFD X 440V
LCD50+7.5X440	50+7.5 MFD X 440V
LCD55+10X440	55+10 MFD X 440V
LCD55+5X440	55+5 MFD X 440V
LCD60+5X440	60+5 MFD X 440V
LCD60+7.5X440	60+7.5 MFD X 440V
LCD65+10X440	65+10 MFD X 440V
LCD65+7.5X440	65+7.5 MFD X 440V
LCD80+10X440	80+10 MFD X 440V
LCD80+5X440	80+5 MFD X 440V
LCD80+7.5X440	80+7.5 MFD X 440V

SINGLE OVAL

LINEBACKER®

A *Supco* BRAND



@sealedunitpartsco | @supco_hvac | supco.com

P: 800.333.9125 | E: orders@supco.com | F: 800.458.2818