



### FEATURES

Lens fixtures are the perfect choice for consistent lighting that spans a large area. These fixtures sit flush to the channel lip and comes with an opal lens to diffuse the light. Available in 3 sizes. Lens fixtures can be joined together seamlessly using the overlap lens found in the accessories section.

### SPECIFICATIONS

Light Source:	1 x 19 W Integrated LED
Beam Angle:	115°
Kelvin:	*3000K
*For 2700K, 3500K, 4000K please contact <a href="mailto:sales@eurofase.com">sales@eurofase.com</a>	
Initial Lumens:	1824 Lm
Delivered Lumens:	1197 Lm
CRI:	90+
Dimming:	TRIAC/0-10V
Color:	Black/White
Input:	24V DC (Remote Driver required)
Dimension:	23.74" L x 1.30" W x 2.17" H
Approval:	Indoor use
Electrical Approval:	  
Warranty:	

### ORDERING OPTIONS




Black  
36373-01




White  
36373-02

### DIAGRAM



### PHOTOMETRICS


H(m)	D(m)	E(lx)
<b>115°</b>		
1.0	3.16	209
2.0	6.32	52
3.0	9.48	23
4.0	12.64	13
5.0	15.80	8



1m=3.28ft  
1lx=0.09fc

### COMPATIBLE CHANNELS


#### SURFACE MOUNT



#### TRIM RECESSED



3FT: 35771-01/02  
6FT: 35772-01/02  
8FT: 35773-01/02



3FT: 35767-01/02  
6FT: 35768-01/02  
8FT: 35769-01/02



3FT: 35775-01/02  
6FT: 35776-01/02  
8FT: 35777-01/02

### COMPATIBLE DRIVERS



30264-014  
TRIAC dimming



44912-017  
0-10V dimming