


WIRE ENTRY POINT
WIRE RANGE: 500MCM - #4AWG
PRE-FILLED W/ OXIDE INHIBITOR

IPLD500-5C SHOWN

| PART NUMBER | NO. OF PORTS | LENGTH |
|-------------|--------------|--------|
| IPLD500-3C | 3 | 4.01 |
| IPLD500-4C | 4 | 5.16 |
| IPLD500-5C | 5 | 6.30 |
| IPLD500-6C | 6 | 7.45 |
| IPLD500-8C | 8 | 9.74 |
| IPLD500-10C | 10 | 12.03 |
| IPLD500-12C | 12 | 14.32 |
| IPLD500-14C | 14 | 16.61 |

- NOTES:
- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
 - UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
 - DUAL RATED FOR 90C COPPER AND/OR ALUMINUM CONDUCTOR.
 - COLD TEMPERATURE RATED TO -45C.
 - HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION AND CHEMICAL RESISTANT



POLARIS
SALES . CO . INC

| | | | |
|---|--|--|--|
| PROPRIETARY AND CONFIDENTIAL | | 11625 PROSPEROUS DRIVE ODESSA, FL 33556 | |
| THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED. | | <p>TITLE:</p> <p style="font-size: large;">CLEAR INSULATED DUAL ENTRY 500 CONNECTOR</p> | |
| DRAWN BY T.MITCHELL | | DATE 12/2021 | |
| MATERIAL: N/A | | SCALE: N/A | |
| | | <p>DWG. NO.</p> <p style="font-size: large;">IPLD500C</p> | |
| | | SHEET: 1 OF 1 | |