

TECHNICAL DATA SHEET



STRIPE CONCRETE RENEW

20-600 Concrete Coating Gray (Water Based)

Permanent marks that remain on streets and sidewalks after they're needed can be a nuisance. Stripe Concrete Renew will cover up those marks, helping you avoid the time and expense of using paint stripper. The concrete coating has a similar texture and color to most sidewalks. It is quick dry, highly durable, and is compatible with our Z-604 striping machine, Z-605 gun, and Z-606 wand.

Suggested Uses:

Sidewalks Driveways Warehouse floors Cinder block walls

Packaging:

UPC Number Cans per case Shipping weight per case Container Label weight Shipping Classification Hazard Class 043281008433 12 18 lbs. 20 fluid ounce can 17 oz. for gray limited quantity, UN1950 2.1

Properties:

Cleanup Flammability Flash point Specific Gravity Solids Content MIR value Storage Temperature Application Temperature Shelf life Freeze/Thaw

Paint or lacquer thinner Flammable -4F 0.83 ~26-30% Does not exceed 0.85 40-100F 40-100F Guaranteed for 2 years Up to 7 times without harm

Do not warehouse in subfreezing temperatures

Dry Time*:

To touch15 minutesTraffic ready1 hour

At 72F, 50% humidity, 1.5 mil thickness

Curing/Recoat time is extended with multiple coats and excessively thick coats

Gloss*: Flat

*as measured on a 60 degree gloss meter

Other Information:

Yields approximately 250 linear feet per can (4" wide stripe) or 50 square feet. The paint is traffic ready in 1 hour. Make stripes 2"-4" wide with our #Z-604 traffic machine. The universal sprayhead also works in competitive marking machines.

12-15-2021

Seymour of Sycamore | 917 Crosby Avenue | Sycamore |L 60178 Phone | 815.895.9101 • 800.435.4482 Fax | 815.895.8475 • 800.343.4258