

**ORA****ORA4****YU****YU4****YU6****REN****TUK**

Tweeter	▶ 3/4" Silk Dome Tweeter	3/4" Silk Dome Tweeter	3/4" Silk Dome Tweeter	1" Silk Dome	1" Silk Dome	1" Silk Dome	1" Silk Dome	28 mm x 35 mm Air Motion Transformer (AMT)
Woofer	▶ 3" Composite	3" Paper Cone (Magnetically Shielded)	4" Aluminum Concave Cone (Magnetically Shielded)	4" Kevlar®	4" Kevlar®	5.25" Kevlar®	5.25" Aluminum Concave Cone	5.25" Aluminum Concave Cone
Amplifier Type	▶ Class D	Class D Bi-Amplified	Class D Bi-Amplified	Class D	Class D	Class D	Class D	Class D
Power Output	▶ 100 W Peak (50 W RMS)	100 W Peak (50 W RMS) 9 W RMS per Tweeter 16 W RMS per Woofer	140 W Peak (70 W RMS) 12 W RMS per Tweeter 23 W RMS per Woofer	140 W Peak (70 W RMS)	140 W Peak (70 W RMS)	200 W Peak (100 W RMS)	200 W Peak (100 W RMS)	260 W Peak (130 W RMS)
Frequency Response	▶ 80 Hz - 20 kHz	70 Hz - 22 kHz	60 Hz - 22 kHz	60 Hz - 20 kHz	60 Hz - 20 kHz	50 Hz - 20 kHz	50 Hz - 22 kHz	50 Hz - 20 kHz
High/Low-Pass Filter	▶	100 Hz (Automatic)	80 Hz (Automatic)				80 Hz (Automatic)	80 Hz (Selectable)

Inputs

RCA	▶	✓	✓	✓	✓ Phono Switch	✓ Phono Switch	✓	✓ Dedicated Phono & Line Level
3.5mm AUX	▶	✓			✓	✓	✓	
Bluetooth	▶	✓	✓	✓	✓	✓	✓	✓
USB	▶	✓ USB-B	✓ USB-C	✓ USB-C			✓ USB-C	✓ USB-B
Optical	▶				✓ x2	✓ x2	✓	✓
HDMI ARC	▶						✓	

Outputs

Sub-Out	▶	✓	✓	✓	✓	✓	✓	✓
3.5mm Headphone Out	▶							✓
USB Charge	▶				✓	✓	✓	✓
1/4"-20 Mounting Point	▶	✓ Rear	✓ Rear & Bottom	✓ Bottom	✓ Bottom	✓ Bottom	✓ Bottom	✓ Bottom
Remote	▶			✓	✓	✓	✓	✓