



GOOD GRIP ANTI SLIP COATING

Good Grip is designed to improve traction on most surfaces. Contains plastic beads to improve traction on most any surface. More durable than tape, resistant to oil and gas, and traffic ready in 24 hours. Meets the OSHA recommended static coefficient of friction (0.5).

Suggested Uses:

- Ramps
- Marine docks
- Boats
- Steps
- Ladder Rungs
- Walkways
- Railings

Packaging:

Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	limited quantity, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 10 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.80
Solids Content	25%
MIR value	1.13, cannot exceed 2.10
HAPs content	9%
Storage Temperature	40-100F
Application Temperature	50-90F
Gasoline Resistance	Yes
Heat Resistance	350F
Resin System	Modified Epoxy
Shelf life	Guaranteed for 2 years

Dry Time*:

To touch	10 minutes
To recoat	30 minutes

Traffic Ready Minimum overnight dry

*At 72F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss*: Flat, <5

*as measured on a 60 degree gloss meter

Standard coefficient of friction (dry):	0.623
Standard coefficient of friction (wet):	0.40

Available Colors:

Part #	Description	UPC Code
16-81	Clear	043281002127
16-83	Black	043281000499
16-89	Yellow	043281000475

12-5-2021