



Li-On Battery

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)
Issue date: 3/21/2025 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Product form : Article
Trade name : Li-On Battery
Product code : 40089

1.2. Other means of identification

Other means of identification : 18650 3.7V 2.0Ah 7.4Wh

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Batteries and accumulators
Restrictions on use : No additional information available

1.4. Supplier's details

Supplier
ITW Global Tire Repair
125 Venture Drive, Suite 210, San Luis Obispo, CA 93401, USA
Tel: (888) 457-5463 (Toll Free)

1.5. Emergency phone number

Emergency number : Chemtel: +1(813)248-0585 (International)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR § 1910.1200)

Not classified

2.2. Label elements

GHS US labeling

No labeling applicable

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

Other hazards which do not result in classification : This product is not classified as hazardous but contains hazardous components. Risk of exposure only occurs if the battery cell is mechanically, thermally, or electrically abused and the enclosure is compromised. If this occurs, exposure to electrolyte solutions contained in the battery cell may occur by inhalation, eye contact, skin contact, or ingestion. The batteries described in this Safety Data Sheet are sealed units which are not hazardous when used according to the Manufacturer's recommendations.

2.5. Unknown acute toxicity

No additional information available

Li-On Battery

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR § 1910.1200)
Cobalt lithium dioxide	CAS-No.: 12190-79-3	30 – 60	Carc. 2, H351 Repr. 2, H361
Graphite	CAS-No.: 7782-42-5	15 – 40	Not classified
Ethylene carbonate	CAS-No.: 96-49-1	10 – 30	Acute Tox. 4 (Oral), H302 Eye Irrit. 2A, H319 STOT RE 2, H373
Copper	CAS-No.: 7440-50-8	5 – 10	Aquatic Chronic 2, H411
Lithium hexafluorophosphate(1-)	CAS-No.: 21324-40-3	5 – 10	Acute Tox. 3 (Oral), H301 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT RE 1, H372
Aluminium	CAS-No.: 7429-90-5	5 – 10	Water-react. 2, H261 Flam. Sol. 1, H228
Ethyl methyl carbonate	CAS-No.: 623-53-0	1 – 5	Flam. Liq. 2, H225

Comments : The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with paragraph (i) of § 1910.1200

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: If medical advice is needed, have product container or label at hand. Never give anything by mouth to an unconscious person.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician immediately. Give oxygen or artificial respiration if necessary.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects	: Risk of exposure only occurs if the battery cell is mechanically, thermally, or electrically abused and the enclosure is compromised. If this occurs, exposure to electrolyte solutions contained in the battery cell may occur by inhalation, eye contact, skin contact, or ingestion.
Symptoms/effects after inhalation	: Vapors or mists from a ruptured battery may cause respiratory irritation. Danger of serious damage to health by prolonged exposure through inhalation.

Li-On Battery

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Symptoms/effects after skin contact	: Skin contact with a ruptured battery can cause skin irritation. Causes severe skin burns. Redness. Itching. Pain. May produce skin irritation, blistering, ulcers, and deep scarring.
Symptoms/effects after eye contact	: Eye contact with the contents of a ruptured battery can cause severe irritation to the eye. Causes serious eye damage. Redness. Lacrimation. Itching. Blurred vision. Pain. Can cause blindness.
Symptoms/effects after ingestion	: Harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Abdominal pain. Swallowing this material will result in serious health hazard, potentially leading to collapse and death.
Chronic symptoms	: May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Carbon dioxide. Foam. Dry powder. Water spray. Use extinguishing agent suitable for surrounding fire.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Burning produces stinking and toxic fumes. In case of fire and/or explosion do not breathe fumes.
Explosion hazard	: Explosion risk in case of fire.
Reactivity in case of fire	: Damaged or opened cells or batteries can result in rapid heating and the release of flammable vapors. Reacts violently with water.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon dioxide. Carbon monoxide. Hydrogen fluoride. Lithium Oxide. Metal oxides.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Evacuate the danger area. Move containers from fire area if it can be done without personal risk. Exercise caution when fighting any chemical fire. Fight fire with normal precautions from a reasonable distance. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Evacuate unnecessary personnel. Ventilate spillage area. Avoid breathing vapors, fume. Do not get in eyes, on skin, or on clothing. Do not touch or walk on the spilled product. No action shall be taken without appropriate training or involving any personal risk.

For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel.

Li-On Battery

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Environmental precautions : Avoid release to the environment. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Notify authorities if product enters sewers or public waters.

6.2. Methods and materials for containment and cleaning up

For containment : Stop leak, if possible without risk.
Methods for cleaning up : Move containers from spill area. Mechanically recover the product. Clean up any spills as soon as possible, using an absorbent material to collect it. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Prevent entry to sewers and public waters.
Other information : Dispose of via an authorised person/ licensed waste disposal contractor or by other suitable waste treatment techniques.

For further information refer to section 13, For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Provide local exhaust or general room ventilation. Wear personal protective equipment. Avoid contact with skin and eyes. Take precautionary measures against static discharge. Do not short circuit, puncture, incinerate, crush, immerse in water, or expose to temperatures outside the temperature range stipulated by the manufacturer for the product. If this occurs, electrolyte leakage, or battery vent/explosion/fire may also occur depending on the circumstances.
Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Always wash hands after handling the product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions : Store in a dry place. Keep cool. Keep away from food, drink and animal feed. Proper grounding procedures to avoid static electricity should be followed. Protect from moisture. Protect from freezing. Store in accordance with local, regional, national or international regulation.
Storage area : Store in dry, cool, well-ventilated area.
Incompatible products : Strong acids. Strong bases. Strong oxidizing agents.
Incompatible materials : Direct sunlight. Keep away from any possible contact with water.
Heat and ignition sources : Do not expose the battery to high temperatures or fire.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Graphite (7782-42-5)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Graphite (all forms excepte graphite fibers)
ACGIH OEL TWA	2 mg/m ³ (R - Respirable particulate matter)
Remark (ACGIH)	TLV® Basis: Pneumoconiosis
Regulatory reference	ACGIH 2022

Li-On Battery

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Graphite (7782-42-5)	
USA - OSHA - Occupational Exposure Limits	
Local name	Graphite (Natural)
OSHA PEL TWA	15 mppcf
Remark (OSHA)	Table Z-3. CAS No. source: eCFR Table Z-1.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Graphite, natural
Cal/OSHA PEL (OEL TWA)	2.5 mg/m ³ (Respirable dust)
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
USA - NIOSH - Occupational Exposure Limits	
Local name	Graphite (Natural)
NIOSH REL 10h TWA	2.5 mg/m ³ (Respirable fraction)
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-3 Mineral Dusts (NIOSH Pocket Guide to Chemical Hazards (NPG))
Copper (7440-50-8)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Copper, as Cu
ACGIH OEL TWA	0.2 mg/m ³ (Fume) 1 mg/m ³ (Dusts and mists)
Remark (ACGIH)	TLV® Basis: Irr; GI; metal fume fever
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Copper
OSHA PEL TWA	0.1 mg/m ³ (Fume (as Cu)) 1 mg/m ³ (Dusts and mists (as Cu))
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Copper metal fume, as Cu
Cal/OSHA PEL (OEL TWA)	0.1 mg/m ³
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
USA - NIOSH - Occupational Exposure Limits	
Local name	Copper
NIOSH REL 10h TWA	0.1 mg/m ³ (Fume (as Cu)) 1 mg/m ³ (Dusts and mists (as Cu))
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))
Aluminium (7429-90-5)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Aluminum metal and insoluble compounds

Li-On Battery

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Aluminium (7429-90-5)	
ACGIH OEL TWA	1 mg/m ³ (R - Respirable particulate matter)
Remark (ACGIH)	TLV® Basis: Pneumoconiosis; LRT irr; neurotoxicity. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Aluminum Metal (as Al)
OSHA PEL TWA	15 mg/m ³ (Total dust) 5 mg/m ³ (Respirable fraction)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - NIOSH - Occupational Exposure Limits	
Local name	Aluminum Metal (as Al)
NIOSH REL 10h TWA	10 mg/m ³ (Total dust) 5 mg/m ³ (Respirable fraction)
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))
Monitoring methods	
Monitoring methods	Refer to all applicable national, international and local regulations or provisions.

8.2. Appropriate engineering controls

Appropriate engineering controls	: Provide local exhaust or general room ventilation. Handle in accordance with good industrial hygiene and safety procedures. Avoid all unnecessary exposure. Ensure exposure is below occupational exposure limits (where available).
Environmental exposure controls	: Avoid release to the environment. Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment. Personal protective equipment should be chosen according to the NIOSH standards and in discussion with the supplier of the protective equipment.

Hand protection:
Not required for normal conditions of use. In case of skin contact. Chemical resistant gloves (according to NIOSH standard)
Eye protection:
No special eye protection equipment recommended under normal conditions of use
Skin and body protection:
No special clothing/skin protection equipment is recommended under normal conditions of use
Respiratory protection:
No respiratory protection needed under normal use conditions

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Solid
Appearance	: batteries.

Li-On Battery

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Color	: Green Purple Gray
Odor	: odorless
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: Insoluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

Additional information	: Voltage: 3.7 V
	Capacity: 2.0Ah, 3.7Wh

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Damaged or opened cells or batteries can result in rapid heating and the release of flammable vapors.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

In contact with water releases flammable gas.

10.4. Conditions to avoid

Direct sunlight. High temperature. Heat and ignition sources. Moisture. Do not allow contact with water. Do not freeze.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Li-On Battery

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Lithium hexafluorophosphate(1-) (21324-40-3)	
LD50 oral rat	50 – 300 mg/kg
ATE US (oral)	100 mg/kg body weight
Ethylene carbonate (96-49-1)	
ATE US (oral)	500 mg/kg body weight
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Lithium hexafluorophosphate(1-) (21324-40-3)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Ethylene carbonate (96-49-1)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Li-On Battery	
Viscosity, kinematic	No data available
Symptoms/effects	: Risk of exposure only occurs if the battery cell is mechanically, thermally, or electrically abused and the enclosure is compromised. If this occurs, exposure to electrolyte solutions contained in the battery cell may occur by inhalation, eye contact, skin contact, or ingestion.
Symptoms/effects after inhalation	: Vapors or mists from a ruptured battery may cause respiratory irritation. Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/effects after skin contact	: Skin contact with a ruptured battery can cause skin irritation. Causes severe skin burns. Redness. Itching. Pain. May produce skin irritation, blistering, ulcers, and deep scarring.
Symptoms/effects after eye contact	: Eye contact with the contents of a ruptured battery can cause severe irritation to the eye. Causes serious eye damage. Redness. Lacrimation. Itching. Blurred vision. Pain. Can cause blindness.
Symptoms/effects after ingestion	: Harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Abdominal pain. Swallowing this material will result in serious health hazard, potentially leading to collapse and death.
Chronic symptoms	: May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.
Other information	: No experimental study on the product is available. The information given is based on our knowledge of the components and the classification of the product is determined by calculation.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general	: Do not allow product to spread into the environment. Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Li-On Battery

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

12.2. Persistence and degradability

Li-On Battery	
Persistence and degradability	Biodegradability in water: no data available.

12.3. Bioaccumulative potential

Li-On Battery	
Bioaccumulative potential	No data available concerning bioaccumulation.

12.4. Mobility in soil

Li-On Battery	
Ecology - soil	No additional information available.

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No other effects known.
Fluorinated greenhouse gases	: No

SECTION 13 Disposal considerations

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Do not dispose of waste into sewer.
Product/Packaging disposal recommendations	: Must not be disposed together with household garbage. Dispose in a safe manner in accordance with local/national regulations. To be disposed of as hazardous waste. Do not disassemble, short circuit, puncture, incinerate, crush, or puncture the battery. Do not mix new and used batteries.
Ecological waste information	: Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

UN-No. (DOT)	: UN3481
UN-No. (TDG)	: UN3481
UN-No. (IMDG)	: 3481
UN-No. (IATA)	: 3481

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT)	: Lithium ion batteries packed with equipment
Proper Shipping Name (TDG)	: LITHIUM ION BATTERIES PACKED WITH EQUIPMENT
Proper Shipping Name (IMDG)	: LITHIUM ION BATTERIES PACKED WITH EQUIPMENT
Proper Shipping Name (IATA)	: Lithium ion batteries packed with equipment

14.3. Transport hazard class(es)

DOT	
Transport hazard class(es) (DOT)	: 9
Hazard labels (DOT)	: 9

Li-On Battery

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)



TDG

Transport hazard class(es) (TDG) : 9
Hazard labels (TDG) : 9



IMDG

Transport hazard class(es) (IMDG) : 9
Hazard labels (IMDG) : 9A



IATA

Transport hazard class(es) (IATA) : 9
Hazard labels (IATA) : 9A



14.4. Packing group

Packing group (DOT) : Not applicable
Packing group (TDG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

UN-No. (DOT) : UN3481

Li-On Battery

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

DOT Special Provisions (49 CFR 172.102)	: 181 - When a package contains a combination of lithium batteries contained in equipment and lithium batteries packed with equipment, the following requirements apply: a. The shipper must ensure that all applicable requirements of §173.185 of this subchapter are met. The total mass of lithium batteries contained in any package must not exceed the quantity limits in columns (9A) and (9B) for passenger aircraft or cargo aircraft, as applicable; b. Except as provided in §173.185(c)(3) of this subchapter, the package must be marked "UN 3091 Lithium metal batteries packed with equipment", or "UN 3481 Lithium ion batteries packed with equipment," as appropriate. If a package contains both lithium metal batteries and lithium ion batteries packed with and contained in equipment, the package must be marked as required for both battery types. However, button cell batteries installed in equipment (including circuit boards) need not be considered; and c. The shipping paper must indicate "UN 3091 Lithium metal batteries packed with equipment" or "UN 3481 Lithium ion batteries packed with equipment," as appropriate. If a package contains both lithium metal batteries and lithium ion batteries packed with and contained in equipment, then the shipping paper must indicate both "UN 3091 Lithium metal batteries packed with equipment" and "UN 3481 Lithium ion batteries packed with equipment." 388 - a. Lithium batteries containing both primary lithium metal cells and rechargeable lithium ion cells that are not designed to be externally charged, must meet the following conditions: i. The rechargeable lithium ion cells can only be charged from the primary lithium metal cells; ii. Overcharge of the rechargeable lithium ion cells is precluded by design; iii. The battery has been tested as a primary lithium battery; and iv. Component cells of the battery must be of a type proved to meet the respective testing requirements of the Manual of Tests and Criteria, part III, subsection 38.3 (IBR, see 171.7 of this subchapter). b. Lithium batteries conforming to paragraph a. of this special provision must be assigned to UN Nos. 3090 or 3091, as appropriate. When such batteries are transported in accordance with 173.185(c), the total lithium content of all lithium metal cells contained in the battery must not exceed 1.5 g and the total capacity of all lithium ion cells contained in the battery must not exceed 10 Wh. 422 - When labelling is required, the label to be used must be the label shown in §172.447. Labels conforming to requirements in place on December 31, 2016 may continue to be used until December 31, 2018. When a placard is displayed, the placard must be the placard shown in §172.560. A54 - Lithium batteries or lithium batteries contained or packed with equipment that exceed the maximum gross weight allowed by Column (9B) of the 172.101 Table may only be transported on cargo aircraft if approved by the Associate Administrator.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 185
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 185
DOT Packaging Bulk (49 CFR 173.xxx)	: 185
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 35 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
TDG	
UN-No. (TDG)	: UN3481

Li-On Battery

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

TDG Special Provisions

- : 34 - (1) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of lithium cells and batteries on a road vehicle, a railway vehicle or a vessel on a domestic voyage if
- (a) for a lithium metal or lithium alloy cell, the lithium content is not more than 1 g, and, for a lithium-ion cell, the watt-hour rating is not more than 20 Wh;
 - (b) for a lithium metal or lithium alloy battery, the aggregate lithium content is not more than 2 g, and for a lithium-ion battery, the watt-hour rating is not more than 100 Wh;
 - (c) lithium ion batteries are marked with the watt-hour rating on the outside case, except for those manufactured before January 1, 2009;
 - (d) each cell and battery type passes each of the tests set out in paragraph 2.43.1(2)(a) of Part 2 (Classification);
 - (e) the cells and batteries are afforded protection against short circuit, including protection against contact with conductive materials within the same packaging that could lead to a short circuit;
 - (f) the cells and batteries are packed in a means of containment that completely encloses the cells and batteries;
 - (g) the gross mass of the cells and batteries does not exceed 30 kg, except when the cells and batteries are installed in or packed with equipment; and
 - (h) the cells and batteries are packed in a means of containment capable of withstanding a 1.2 m drop test in any orientation without damage to the cells or batteries contained inside the means of containment, without the contents shifting so as to allow battery-to-battery or cell-to-cell, contact, and without release of contents.
- (2) Cells and batteries referred to in subsection (1) that are installed in equipment must, unless they are afforded equivalent protection by the equipment in which they are contained,
- (a) be afforded protection against damage and short circuit, including protection against contact with conductive materials within the same packaging that could lead to a short circuit;
 - (b) subject to subsection (3), be fitted to prevent accidental activation; and
 - (c) be packed in a means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no release of the dangerous goods that could endanger public safety.
- (3) Paragraph (2)(b) does not apply to cells and batteries installed in devices that are intentionally active during transport such as radio frequency identification transmitters, watches and sensors, and that are not capable of generating a dangerous evolution of heat.
- (4) Except for means of containment containing button cell batteries installed in equipment, including circuit boards, or no more than four cells installed in equipment or no more than two batteries installed in equipment, each means of containment must be marked with the appropriate lithium battery mark in accordance with section 4.24.
- (5) Despite subsection (4), except for means of containment containing button cell batteries installed in equipment, including circuit boards, or no more than four cells installed in equipment or no more than two batteries installed in equipment, each means of containment may, until December 31, 2018, be marked with the following:
- (a) "lithium metal", "lithium métal", "lithium ion" or "lithium ionique", as appropriate;
 - (b) an indication that the means of containment must be handled with care and that a flammability hazard exists if the means of containment is damaged;
 - (c) an indication that special procedures must be followed in the event the means of containment is damaged, including inspection and repacking, if necessary; and
 - (d) a telephone number to call for additional information.
- 123 - (1) The testing requirements in subsection 38.3 of Part III of the Manual of Tests and Criteria do not apply to production runs consisting of not more than 100 cells and batteries or to pre-production prototypes of cells and batteries that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage if
- (a) the cells or batteries are imported, offered for transport, handled or transported in accordance with Packing Instruction P910 of the UN Recommendations; and
 - (b) the pre-production prototypes of cells and batteries are in transport for the purpose of testing.
- (2) Despite paragraph (1)(b), batteries that have a total mass of 12 kg or more and that have a strong, impact-resistant outer casing, or assemblies of them, may be packed in an outer means of containment or protective enclosure designed, constructed, filled, closed, secured and

Li-On Battery

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

maintained so that under normal conditions of transport, including handling, there will be no release of the dangerous goods that could endanger public safety. The batteries or battery assemblies must be protected from short-circuit, 137 - (1) This shipping name applies to lithium ion cells or batteries, and lithium metal cells or batteries, that are damaged or defective and do not conform to subsection 2.43.1(2) of Part 2 (Classification).

(2) Lithium ion cells or batteries and lithium metal cells or batteries that are damaged or defective, include, but are not limited to, cells or batteries that have leaked or vented, or have sustained physical or mechanical damage, and cannot be diagnosed prior to transport, or that have been identified as being defective for safety reasons.

(3) Lithium ion cells or batteries and lithium metal cells or batteries that are damaged or defective must be packed in accordance with Packing Instructions P908 or LP904 of the UN Recommendations, as applicable.

(4) As applicable, the outer means of containment or the overpack must be marked legibly and visibly on a contrasting background, with the words "Damaged/Defective Lithium Ion Batteries", "piles au lithium ionique endommagées/défectueuses", "Damaged/Defective Lithium Metal Batteries" or "piles au lithium métal endommagées/défectueuses".

(5) It is forbidden to transport lithium ion cells or batteries and lithium metal cells or batteries that are damaged or defective and that, under normal conditions of transport, are liable to disassemble rapidly, react dangerously, produce a flame or a dangerous evolution of heat, or produce a dangerous emission of toxic, corrosive or flammable gases or vapors.

(6) It is forbidden to transport by aircraft lithium ion cells or batteries and lithium metal cells or batteries that are damaged or defective, 138 - (1) When transported for disposal or recycling, lithium ion cells or batteries and lithium metal cells or batteries, or equipment containing those cells or batteries,

(a) are not subject to subsection 2.43.1(2) of Part 2 (Classification);

(b) must be packed in accordance with Packing Instructions P909 or LP904 of the UN Recommendations, as applicable, whether packed with or without non-lithium cells or batteries or equipment containing those cells or batteries;

(c) must be in a means of containment or an overpack that is marked legibly and visibly on a contrasting background with the words "Lithium batteries for disposal", "Piles au lithium destinées à l'élimination", "Lithium batteries for recycling" or "Piles au lithium destinées au recyclage", as appropriate; and

(d) are forbidden for transport by aircraft.

(2) Damaged or defective cells and batteries must be offered for transport or transported under special provision 137, 159 - (1) Subject to subsection (2), the label to be used for these dangerous goods is the one illustrated under the heading for lithium batteries "Class 9, Lithium Batteries" in the appendix to Part 4 (Dangerous Goods Safety Marks).

(2) The generic Class 9 label may be used until December 31, 2018.

Explosive Limit and Limited Quantity Index : 0
Excepted quantities (TDG) : E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 5 kg
Emergency Response Guide (ERG) Number : 147

IMDG
Special provision (IMDG) : 188, 230, 310, 348, 376, 377, 384, 387
Limited quantities (IMDG) : 0
Excepted quantities (IMDG) : E0
Packing instructions (IMDG) : P903, P908, P909, P910, P911, LP903, LP904, LP905, LP906
EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage) : S-I - SPILLAGE SCHEDULE India - FLAMMABLE SOLIDS (REPACKING POSSIBLE)
Stowage category (IMDG) : A
Stowage and handling (IMDG) : SW19
Properties and observations (IMDG) : Electrical batteries containing lithium ion may react (e.g. flame, heat, emission of toxic, corrosive or flammable gases or vapours) or disassemble due to damage, defects or short circuit.

IATA
Special provision (IATA) : A88, A99, A154, A181, A185, A213, A802

Li-On Battery

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Forbidden
PCA limited quantity max net quantity (IATA)	: Forbidden
PCA packing instructions (IATA)	: 966
PCA max net quantity (IATA)	: 5kg
CAO packing instructions (IATA)	: 966
CAO max net quantity (IATA)	: 35kg
ERG code (IATA)	: 12FZ

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Copper	CAS-No. 7440-50-8	5 – 10 %
Aluminium	CAS-No. 7429-90-5	5 – 10 %

Copper (7440-50-8)

CERCLA RQ	5000 lb
-----------	---------

15.2. International regulations

CANADA

Graphite (7782-42-5)

Listed on the Canadian DSL (Domestic Substances List)

Lithium hexafluorophosphate(1-) (21324-40-3)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Copper (7440-50-8)

Listed on the Canadian DSL (Domestic Substances List)

Aluminium (7429-90-5)

Listed on the Canadian DSL (Domestic Substances List)

Ethylene carbonate (96-49-1)

Listed on the Canadian DSL (Domestic Substances List)

Ethyl methyl carbonate (623-53-0)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Li-On Battery

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Cobalt lithium dioxide (12190-79-3)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Graphite (7782-42-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Copper (7440-50-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Aluminium (7429-90-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Issue date : 3/21/2025
Data sources : Supplier's safety documents.
Training advice : Training staff on good practice.

Full text of hazard classes and H-statements

H225	Highly flammable liquid and vapor
H228	Flammable solid
H261	In contact with water releases flammable gas
H301	Toxic if swallowed
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H319	Causes serious eye irritation
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.