

QUICK ACTION™

Carbide Tipped Hole Saws and Accessories

Easily cut thick or layered building materials including wood, wall tile, fiberglass, plastic, and fiber cement siding including James Hardie®

- Quick Change Pilot Drills with a tight, gripping hex shank are available in both **High Speed Steel** and **Carbide Tipped**.
- Unique Quick Connect Arbor easily attaches both pilot drill & hole saw quickly and securely.
- 19 separate Hole Saws work fast with Carbide Tipped Teeth featuring self-cleaning deep gullets.



Pilot Drill projects 1 in. (25 mm) past saw teeth for easy cutting in uneven surfaces like lap siding for easy saw plug ejection.



- Cleanly cut holes in walls clad with Fiber Cement Siding • Generous 2-1/4 in. (57 mm) Saw Depth is versatile for cutting through a variety of other wall cross-sections

19 Different Hole Saw Sizes!



QUICK CONNECT™ Arbor



QUICK CHANGE™ Pilot Drills



QUICK RELEASE SET™ Arbor and Pilot Drill



Quick Connect Arbor

Catalog Number	Hex Opening mm	Thread Size in.	Use for Carbide Tipped Hole Saws
HA3	10	5/8 - 18	1-3/8—6-5/16 (35-160)

Word Key: HSS - High Speed Steel CT - Carbide Tipped

Quick Change Pilot Drills

Catalog Number	Drill mm	Hex Shank in. (mm)	Overall Length in. (mm)	Drill Chuck in. (mm)	Use with Arbor
HH4	HSS 10	7-3/4 (196)	1-1/2 (12.7)	1/2 (12.7)	HA3
HH5	CT 10	7-3/4 (196)	1-1/2 (12.7)	1/2 (12.7)	HA3

Quick Release Set - Arbor with Pilot Drill

Catalog Number	Drill mm	Hex Shank in. (mm)	Overall Length in. (mm)	Drill Chuck in. (mm)	Use for Carbide Tipped Hole Saws
HHA4	HSS 10	7-3/4 (196)	1-1/2 (12.7)	1-3/8—6-5/16 (35-160)	
HHA5	CT 10	7-3/4 (196)	1-1/2 (12.7)	1-3/8—6-5/16 (35-160)	

Important Note: New Catalog Numbers for Arbor, Pilot Drills and Quick Release Sets are not compatible or interchangeable with any of these discontinued catalog numbers: HA1, HH1, HH2, HHA1, HHA2



WARNING:

Fiber cement contains crystalline silica. Respirable silica contained in cutting dust is known to cause cancer.

Malco®

Work. Perform. Outlast.
Limited Lifetime Warranty

www.malcotools.com

SL17784A

Quick-Action Carbide Tipped Hole Saws

Catalog Number	Hole Diameter in. (mm)	Cutting Depth in. (mm)	Thread Size
HF1	1-3/8 (35)	2-1/4 (57)	5/8—18
HF2	1-7/8 (48)	2-1/4 (57)	5/8—18
HF3	2 (51)	2-1/4 (57)	5/8—18
HF4	2-3/8 (60)	2-1/4 (57)	5/8—18
HF5	2-1/2 (64)	2-1/4 (57)	5/8—18
HF17	2-9/16 (65)	2-1/4 (57)	5/8—18
HF6	2-3/4 (70)	2-1/4 (57)	5/8—18
HF7	3 (76)	2-1/4 (57)	5/8—18
HF8	3-1/2 (89)	2-1/4 (57)	5/8—18
HF18	3-5/8 (92)	2-1/4 (57)	5/8—18
HF9	4 (102)	2-1/4 (57)	5/8—18
HF10	4-1/8 (105)	2-1/4 (57)	5/8—18
HF11	4-1/2 (114)	2-1/4 (57)	5/8—18
HF19	4-5/8 (117)	2-1/4 (57)	5/8—18
HF12	5 (127)	2-1/4 (57)	5/8—18
HF13	5-1/4 (133)	2-1/4 (57)	5/8—18
HF14	5-1/2 (140)	2-1/4 (57)	5/8—18
HF15	6 (152)	2-1/4 (57)	5/8—18
HF16	6-5/16 (160)	2-1/4 (57)	5/8—18