

## EXTREME FX CHROME



A distinctive, brilliant metallic chrome coating that will not burnish or rub off. This formulation dries fast, does not smudge, has good flexibility, and resists heat. The use of a clear topcoat is recommended to ensure maximum performance. For enhanced depth of image, use #16-121 clear as a topcoat. For improved solvent resistance, use EN-70 clear as a topcoat.

### Suggested Uses:

Mag wheels  
 Alternators  
 Bumpers  
 Trim accessories  
 Calipers  
 Blocks

### Packaging:

UPC Code	043281000169
Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	11 ounces (312 grams)
Shipping Classification	limited quantity, UN 1950
Hazard Class	2.1

### Properties:

Coverage	Up to 15 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.80
Solids Content	1%
MIR value	0.56, cannot exceed 1.25
HAPs content	0%
Storage Temperature	40-100F
Application Temperature	50-90F
Durability	Good when clearcoated
Abrasion Resistance	Good when clearcoated
Gasoline Resistance	No (if needed, use EN-70 clear)
Heat Resistance	250F
Shelf life	Guaranteed for 1 year

### Dry Time\*:

To touch	10 minutes
To topcoat	30 minutes

\*At 72° F, 50% humidity,  
 0.1 to 0.2 mil thickness

**Appearance:** "mirror-like"

### Additional Information:

For the best appearance, apply a light coat over a very smooth surface. If the surface is not smooth, defects will show through. When applying over a previously painted surface, that surface must be completely cured in order to avoid solvent 'strike-in', which will detract from the brightness and chrome-like appearance of the coating.

12-1-2021