

User Manual TL-FO-HD 4K Optical Fiber Extender



All Rights Reserved

Version: TL-FO-HD_160628



Preface

Read this user manual carefully before using this product. Pictures shown in this manual is for reference only, different model and specifications are subject to real product.

This manual is only for operation instruction only, not for any maintenance usage.

Trademarks

Product model and its logo are trademarks. Any other trademarks mentioned in this manual are acknowledged as the properties of the trademark owner. No part of this publication may be copied or reproduced without our prior written consent.

FCC Statement

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. It has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a commercial installation.

Operation of this equipment in a residential area is likely to cause interference, in which case the user at their own expense will be required to take whatever measures may be necessary to correct the interference.

Any changes or modifications not expressly approved by the manufacture would void the user's authority to operate the equipment.









SAFETY PRECAUTIONS

To insure the best from the product, please read all instructions carefully before using the device. Save this manual for further reference.

- Unpack the equipment carefully and save the original box and packing material for possible future shipment
- Follow basic safety precautions to reduce the risk of fire, electrical shock and injury to persons.
- Do not dismantle the housing or modify the module. It may result in electrical shock or burn.
- Using supplies or parts not meeting the products' specifications may cause damage, deterioration or malfunction.
- Refer all servicing to qualified service personnel.
- To prevent fire or shock hazard, do not expose the unit to rain, moisture or install this
 product near water.
- Do not put any heavy items on the extension cable in case of extrusion.
- Do not remove the housing of the device as opening or removing housing may expose you to dangerous voltage or other hazards.
- Install the device in a place with fine ventilation to avoid damage caused by overheat.
- Keep the module away from liquids.
- Spillage into the housing may result in fire, electrical shock, or equipment damage. If an
 object or liquid falls or spills on to the housing, unplug the module immediately.
- Do not twist or pull by force ends of the optical cable. It can cause malfunction.
- Do not use liquid or aerosol cleaners to clean this unit. Always unplug the power to the device before cleaning.
- Unplug the power cord when left unused for a long period of time.
- Information on disposal for scrapped devices: do not burn or mix with general household waste, please treat them as normal electrical wastes.





Introduction

TL-FO-HD is a mini optical fiber extender for 4K resolution. It contains a SOURCE module and a DISPLAY module. Compatible with multi-mode and single-mode fiber, it extends HDMI signals up to 400m/300m via single-mode cable/ multi-mode cable. With its HDMI1.4& HDCP compliance design, the TL-FO-HD supports high definition (up to 4096x2160@30Hz, 1080p 3D) signal.

Package List

- 1* TL-FO-HD (SOURCE and DISPLAY are included)
- 2* Power Adapter
- 1*Optical Fiber Cable (single-mode)
- 1*User Manual

Notes: Check whether all the items listed above are included in your package. If not, contact your dealer to make up.

Appearances

SOURCE Module:



- 1 PWR LED: Illuminated when powered
- 2 LINK LED: Illuminated when SOURCE & DISPLAY module are connected.
- ③ **(4) USB**: Insert a DC 5V 1A power adapter here
- (4) **OUT**: Connect to the **IN** of the DISPLAY module.






DISPLAY Module:



- 1 PWR LED: Illuminated when powered
- 2 LINK LED: Illuminated when SOURCE & DISPLAY moduleare connected.
- (3) **USB**: Insert a DC 5V 1A power adapter here
- 4 IN: Connected to the OUT of the SOURCE module

Connection:

The figure below illustrates a typical connection that can be utilized with TL-FO-HD:



- Step1. Insert the SOURCE module into the HDMI port of a HDMI source device (e.g. a PC).
- **Step2.** Connect the **OUT** port of the **SOURCE module** to the **IN** port of **DISPLAY module** with an optical fiber cable.
- **Step3.** Insert the **DISPLAY** into the HDMI port of a HDMI display device (e.g. a monitor).
- **Step4.** Plug DC 5V power adapters to the **USB** ports of both the **SOURCE** and the **DISPLAY** module.

Note: Connect the **SOURCE/DISPLAY module** with HDMI source/ sink directly or through a HDMI cable.





Specification

Model	SOURCE module	DISPLAY module	
Spec	SOORCE IIIodule	DISPLAT IIIodule	
Input			
Input Signal	1 HDMI	1 Optical Fiber	
Input Connector	19-pin Type A male HDMI	LC connector	
Signal	HDMI1.4	Optical Fiber	
Output			
Output	1 Optical Fiber	1 HDMI	
Output Connector	LC connector	19-pin Type A male HDMI	
Signal	Optical Fiber	HDMI1.4	
General			
Resolution	4k (max)		
Audio Format	PCM, Dolby Digital, DTS, DTS-HD		
HDMI Standard	Support HDMI1.4 and HDCP1.4		
Transmission Distance	≤400m via single-mode fiber		
	≤300m via multi-mode fiber		
Temperature	0 ~ 50°C		
Reference Humidity	10% ~ 90%		
Power Supply	Input: AC 100~240V, 50/60Hz; Output: DC 5V 1A		
Power Consumption	≤2.5w	≤2.3w	
Dimension (W*H*D)	60*10*22 mm	60*10*22 mm	
Weight	26g	26g	





Troubleshooting & Maintenance

Problems	Causes	Solutions
Color loss or vague/ double	Poor quality of the HDMI	Change to a high quality
image in HDMI display	cable (if used)	cable.
Power led is off, no video	Not powered	Power up the unit
	Poor contact of USB port	Make sure power adapter is
		in good contact
No output on the display	Source/ Display is off	Turn on the source/ display
	Poor contact of HDMI ports	Check the HDMI ports one
		by one to make sure they're
		in good contact.

If your problem persists after following the above troubleshooting steps, seek further help from authorized dealer or our technical support.





After-sales Service

If there appear some problems when running the device, please check and deal with the problems referring to this user manual.

- Product Limited Warranty: We warrant that our products will be free from defects in materials and workmanship for three years. Please see warranty page posted on www.tlnetworx.com for more info.
 - Proof of purchase in the form of a bill of sale or receipted invoice must be presented to obtain warranty service.
- 2) What the warranty does not cover (servicing available for a fee):
 - Warranty expiration.
 - Factory applied serial number has been altered or removed from the product.
 - Damage, deterioration or malfunction caused by:
 - Normal wear and tear
 - Use of supplies or parts not meeting our specifications
 - No certificate or invoice as the proof of warranty.
 - The product model showed on the warranty card does not match with the model of the product for repairing or had been altered.
 - Damage caused by force majeure.
 - Servicing not authorized
 - Any other causes which does not relate to a product defect
 - Delivery, installation or labor charges for installation or setup of the product
- Technical Support: Email to our after-sales department or make a call, please inform us the following information about your cases.
 - Product version and name.
 - Detailed failure situations.
 - The formation of the cases.

Remarks: For any questions or problems, please try to get help from your local distributor.

