



STRIPE 3 SERIES MARKING PAINT

A fast drying marking paint designed to be sprayed in an inverted position. Produces vivid marks, does not clog, and is safe for grass. Meets APWA color standards and can be sprayed by hand or with the Z-605 marking gun or Z-606 marking wand.

Suggested Uses:

Utility marking;
 Golf courses
 Landscaping
 Construction sites
 Surveying
 Mining

Packaging:

Cans per case	12
Shipping Weight	20 ounce cans: 20 lbs.
Container	20 fluid ounce can
Label weight	15 ounces (425 grams)
Hazard Class	2.1
Shipping Classification	limited quantity, UN 1950

Properties:

Coverage	Up to 500 linear feet
Cleanup	Paint or lacquer thinner
Flammability	Flammable
Flash point	-4F
Specific Gravity	0.73
Solids Content	16%
MIR value	0.48, cannot exceed 0.85
HAPs content	<1%
Storage Temperature	40-100F
Application Temperature	50-90F
Resin System	Lacquer
Shelf life	Guaranteed for 2 years
Freeze/Thaw	Up to 7 times without harm

****Do not warehouse in subfreezing temperatures****

Dry Time*:

To touch 1 hour

*At 72F, 50% humidity,
 1.5 mil thickness

**Curing/Recoat time is extended with
 multiple coats and excessively thick coats**

Gloss*: Flat, <15

*as measured on a 60 degree gloss meter

Available Colors:

Part #	Description	UPC Code	Part #	Description	UPC Code
20-352	White	043281008273	20-368	Fluorescent Green	043281008341
20-353	Precaution Blue	043281008280	20-369	Fluorescent Blue	043281008358
20-354	Fluorescent Red	043281008297	20-370	Alert Orange	043281008365
20-355	Safety Green	043281008303	20-371	Safety Red	043281008372
20-357	Fluorescent Orange	043281008310	20-376	Hi Visibility Yellow	043281008389
20-358	Fluorescent Red/Orange	043281008327	20-378	Caution Yellow	043281008396
20-363	Black	043281008334	20-379	Fluorescent Hot Pink	043281008402
			20-380	Purple	043281008563

12-9-2021