



SET SCREW
PLUG SP2/0

CABLE ENTRY
PLUG CP2/0

IPLD2/0-5 SHOWN

PART NUMBER	NO. OF PORTS	LENGTH
IPLD2/0-3	3	2.45
IPLD2/0-4	4	3.20
IPLD2/0-5	5	3.94
IPLD2/0-6	6	4.70
IPLD2/0-8	8	6.20
IPLD2/0-10	10	7.70
IPLD2/0-12	12	9.20
IPLD2/0-14	14	10.70



WIRE ENTRY POINT
WIRE RANGE: 2/0 - #14AWG
PRE-FILLED W/ OXIDE INHIBITOR

3/16" INTERNAL HEX PRESSURE SCREW



CONTACT NSI FOR SALES @ 800.321.5847



POLARIS
SALES . CO . INC

PROPRIETARY AND CONFIDENTIAL

11625 PROSPEROUS DRIVE ODESSA, FL 33556

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.

TITLE:

INSULATED DUAL ENTRY
2/0 CONNECTOR

NAME	DATE
T.MITCHELL	1/2021

DWG. NO.

IPLD2/0 SERIES

MATERIAL: N/A

SCALE: N/A

SHEET: 1 OF 1

NOTES:

- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
- UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
- DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.
- COLD TEMPERATURE RATED TO -45°C.
- HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION, CHEMICAL AND UV RESISTANT.