

Brake Parts Lubricants









Permatex® Brake Parts Lubricants **extend the life of braking system parts** by minimizing metal-metal contact of caliper pins, bushings, abutment clips protecting them from heat, pressure and wear.

BENEFITS:

- Non-melting formulas
- Prevents metal-to-metal contact
- Provides smoother and quieter braking

SUGGESTED APPLICATIONS:

-  Automotive
-  Farm & Tractor
-  Heavy Duty
-  Powersport
-  RV
-  EV

Item #	Description	Case	Case Dimensions (LxWxH)	Item UPC
85188	Synthetic Brake Lube .5oz	6	7.25" x 5.38" x 3.5"	6 86226 85188 8
20353	Synthetic Brake Lube 2oz	6	6.75" x 4.75" x 3.75"	6 86226 20353 3
24110	Synthetic Brake Lube 8oz	6	8" x 5.5" x 5.5"	6 86226 24110 8
24113*	Ceramic Brake Lube .5oz	6	7.25" x 5.38" x 3.5"	6 86226 24113 9
20351*	Ceramic Brake Lube 2oz	6	6.75" x 4.75" x 3.75"	6 86226 20351 9
24125	Ceramic Brake Lube 8oz	6	8" x 5.5" x 5.5"	6 86226 24125 2
24114*	Silicone Brake Lube .5oz	6	7.25" x 5.38" x 3.5"	6 86226 24114 6
20352*	Silicone Brake Lube 2oz	6	6.75" x 4.75" x 3.75"	6 86226 20352 6
24112	Silicone Brake Lube 8oz	6	8" x 5.5" x 5.5"	6 86226 24112 2

*MOQ of 10,000 required



SYNTHETIC BRAKE PARTS LUBRICANT

Our Synthetic Brake Parts Lubricant, formerly Ultra Disc Brake Caliper Lubricant, prevents seizing and sticking of disc brake components.

- Resists temperatures between **-40°F to 500°F (-40°C to 260°C)**
- Ideal for passenger vehicles



CERAMIC BRAKE PARTS LUBRICANT

Our Ceramic Brake Parts Lubricant, formerly Ceramic Extreme Brake Parts Lubricant is enhanced by ceramic solids for long-lasting, superior performance across a wider temperature range.

- Resists temperatures between **-40°F to 3000°F (-40°C to 1649°C)**
- Ideal for SUV's and vans



SILICONE BRAKE PARTS LUBRICANT

Our Silicone Brake Parts Lubricant, replacing the Silicone Ceramic Extreme Brake Parts Lubricant, fortified with ceramic solids, ensuring compatibility with rubber, plastic, and metal components.

- Resists temperatures between: **-50°F to 3000°F (-46°C to 1649°C)**
- Ideal for heavy duty vehicles (SUV's, Trucks, Trailers, EV, Hybrid)



permatex.com

www.permatex.com

Toll-free: 1-877-PERMATEX (877-376-2839)

Permatex and Design are TMs of Illinois Tool Works Inc. Copyright © 2024.
Permatex, an Illinois Tool Works company. All rights reserved



permatextraining.com