

Safety Data Sheet

Printing date 01/03/2024

Revised On 01/03/2024

1 Identification of the substance and manufacturer

Trade name: MRO ANSI 49 DARK GRAY (GALLONS)
Product code: 0000011417
Recommended use: Paint and coatings application.
Uses advised against: Any that differs from the recommended use.
Manufacturer/Supplier: Seymour of Sycamore
 917 Crosby Avenue
 Sycamore, IL 60178 USA
 phone: 815-895-9101
 www.seymourpaint.com
Emergency telephone number: 1-800-255-3924

Seymour of Sycamore
 3041 Dougall Avenue, Suite 503
 Windsor, ONT N9E 1S3 CANADA
 phone: 800-435-4482
 www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flammable Liquids 3 H226 Flammable liquid and vapor.
 Eye Irritation 2A H319 Causes serious eye irritation.
 Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.
 Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information:
GHS Hazard pictograms


GHS02 GHS07 GHS08

Signal word
Hazard statements

Warning
 Flammable liquid and vapor.
 Causes serious eye irritation.
 Suspected of causing cancer. Route of exposure: Inhalation.
 May cause damage to organs through prolonged or repeated exposure.
 Obtain special instructions before use.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash thoroughly after handling.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists: Get medical advice/attention.
 In case of fire: Use CO2, powder or water spray to extinguish.
 Store in a well-ventilated place.
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

64742-47-8	Mineral Spirits	15-25%
7727-43-7	barium sulfate	15-25%
13463-67-7	titanium dioxide	5-10%
64742-48-9	Naphtha, hydrotreated heavy	1-5%
1330-20-7	xylene (mix)	1-5%
111-76-2	Glycol Ether EB	0.2-1%

4 First-aid measures

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water.
After swallowing: Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects: No further relevant information available.
Indication of any immediate medical attention needed: No further relevant information available.

5 Fire-fighting measures

Special hazards: No further relevant information available.
Protective equipment for firefighters: No special measures required.

(Contd. on page 2)

Safety Data Sheet

Printing date 01/03/2024

Revised On 01/03/2024

Trade name: MRO ANSI 49 DARK GRAY (GALLONS)

(Contd. of page 1)

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Not required.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

7727-43-7 barium sulfate

PEL (USA) Long-term value: 15* 5** mg/m³
*total dust **respirable fraction

REL (USA) Long-term value: 10* 5** mg/m³
*total dust **respirable fraction

TLV (USA) Long-term value: 5* mg/m³
*inhalable fraction; E

1330-20-7 xylene (mix)

PEL (USA) Long-term value: 435 mg/m³, 100 ppm

REL (USA) Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV (USA) Long-term value: 20 ppm
BEI, A4

111-76-2 Glycol Ether EB

PEL (USA) Long-term value: 240 mg/m³, 50 ppm
Skin

REL (USA) Long-term value: 24 mg/m³, 5 ppm
Skin

TLV (USA) Long-term value: 20 ppm
BEI, A3

Ingredients with biological limit values:

1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

111-76-2 Glycol Ether EB

BEI (USA) 200 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

Hygienic protection:

Wash hands after use.
Do not eat or drink while working.

Breathing equipment:

Not required.

Hand protection:

Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Eye protection:

Tightly sealed goggles

9 Physical and chemical properties

Appearance: Liquid.

Odor threshold: Not determined.

pH-value: Not determined.

Melting point/Melting range: Undetermined.

Boiling point: 157 °C (314.6 °F)

Flash point: 39 °C (102.2 °F)

Flammability (solid, gas): Flammable.

Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 0.5 Vol %

(Contd. on page 3)

Safety Data Sheet

Printing date 01/03/2024

Revised On 01/03/2024

Trade name: MRO ANSI 49 DARK GRAY (GALLONS)

(Contd. of page 2)

Upper Explosion Limit: 6.5 Vol %
 Vapor pressure: Not determined.
 Vapor density: Not determined.
 Evaporation rate: Not determined.
 Partition coefficient: n-octonal/water: Not determined.
 Solubility: Not determined.
 Viscosity: Not determined.
 Water: 0.0 %

10 Stability and reactivity

Conditions to avoid: No decomposition if used according to specifications.
 Possibility of hazardous reactions: No dangerous reactions known.
 Incompatible materials: No further relevant information available.
 Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information**LD/LC50 values that are relevant for classification:****13463-67-7 titanium dioxide**

Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rbt)
Inhalative	LC50/4 h	>6.82 mg/l (rat)

64742-48-9 Naphtha, hydrotreated heavy

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>3,000 mg/kg (rab)

1330-20-7 xylene (mix)

Oral	LD50	8,700 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rbt)
Inhalative	LC50/4 h	6,350 mg/l (rat)

111-76-2 Glycol Ether EB

Oral	LD50	1,200 mg/kg (ATE) 1,480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)
Inhalative	LC50/4 h	3 mg/l (ATE)

Information on toxicological effects: No data available.
 Skin effects: No irritant effect.
 Eye effects: No irritating effect.
 Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.
 Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.
 Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.
 Bioaccumulative potential: No further relevant information available.
 Mobility in soil: No further relevant information available.
 Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
 Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number: UN1263
 DOT: Paint
 DOT: Paint
 ADR: 1263 Paint
 Transport hazard class(es): 3 Flammable liquids
 Class: Warning: Flammable liquids
 Special precautions for user: F-E, S-E
 EMS Number: A
 Stowage Category: III
 Packaging Group: III

(Contd. on page 4)

Safety Data Sheet

Printing date 01/03/2024

Revised On 01/03/2024

Trade name: MRO ANSI 49 DARK GRAY (GALLONS)

UN "Model Regulation":

UN 1263 PAINT, 3, III

(Contd. of page 3)

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulfate

1330-20-7 xylene (mix)

Toxic Substances Control Act

(TSCA):

All hazardous ingredients are found on the inventory list of substances.

Canadian Domestic Substances List

(DSL):

All ingredients are listed or exempted.

Consumer Product Safety

Commission (CPSC):

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide

1333-86-4 Carbon black

100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients is listed.

EPA:

7727-43-7 barium sulfate

D, CBD(inh), NL(oral)

1330-20-7 xylene (mix)

I

16 Other information

Contact:

Regulatory Affairs