





NOTES:

- 1. FLASH TO BE HELD TO A MINIMUM AND MAY NOT WEB ACROSS HOLES.
- 2. I.D. AND O.D. CONCENTRICITY .020.
- 3. ALL OTHER DIMENSIONS ±.015.
- 4. MATERIAL: BLACK NEOPRENE 50-60 DUROMETER
- 5. REPLACES SRB-35833B

REV.	DATE	CHANGE			UNLESS OTHERWISE SPECIFIED:		NAME	DATE			
Α	11/30/00	DRAWING RELI	EASED		DIMENSIONS ARE IN INCHES TOLERANCES:	DRAWN	JCN	7/15	REMKE INDUST		
		REDRAWN		FRACTIONAL± 1/64 ANGULAR: MACH±1° BEND ±1° ONE PLACE DECIMAL ±.015	CHECKED			310 CHADDI	NG, IL. 60090		
В	7/16/15				ENG APPR.			TITLE:			
					TWO PLACE DECIMAL ±.010 THREE PLACE DECIMAL ±.005	MFG APPR.				BUSHING	
					INTERPRET GEOMETRIC	Q.A.					
				TOLERANCING PER:	PROPRIETARY AND CONFIDENTIAL						
				SEE NOTE	THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF REMKE INDUSTRIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF REMKE INDUSTIRES IS PROHIBITED.		SIZE DWG. NO.				
				FINISH			DUCTION DUT THE	A	SBF-5002		
				DO NOT SCALE DRAWING			SCALE: 1:1		SHEET 1 OF 1		
,		5	†	4	3			2			1

