


FEATURES:

1. Material: TiN Plated CU
2. UL listed for U.S. & Canada.
3. Wire connector rated for 35Kv max.
4. Class B/C compressed, concentric, and compact copper conductor.
5. Expanded wire range when installed with dieless NSi compression tool (N121D).
6. Dimensions are for reference only.


SC-B : SC-300B



PROGRAM:	SOLIDWORKS
UPDATED:	9/2022
SALES REV:	A
SIZE:	B (11x17)



SCALE 5:2



COPPER COMPRESSION CONNECTOR TOOL AND DIE CHART (# OF CRIMPS PER SIDE)

WIRE SIZE	STRIP LENGTH	DIE COLOR	EXPANDED WIRE RANGE W/N121D	NSI		GREENLEE & ILSCO		BURNDY	T&B	HUSKIE	
				N1240 SERIES	NSI-12	NSI-12	GREENLEE 1240 SERIES ILSCO ILC-12, ILC-15	Y-35, Y750, PAT 750	TBM-15, TBM-14M	EP510C	
300kcmil	1-3/16"	WHITE	300kcmil-2/0AWG	KC12-300 (1)	CD15 (2)	HT41BF (2)	KC12-300 (1) ILD-12 (2)	U30RT (2)	15534 (2)	HT41BF (2)	CD15 (2)

