SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Revision Date 09-Jun-2025 **Version** 2

1. Identification

Product identifier

Product Name 2BR FORM A GASKET #2 SEALANT 3OZ

Other means of identification

Product Code 80016

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Restrictions on use No information available

Details of the supplier of the safety data sheet

Manufacturer Address
ITW Permatex, Inc.
6875 Parkland Blvd.
Solon, Ohio 44139 USA
Telephone: 1-87-Permatex
(866) 732-9502

May Also Be Distributed by:
ITW Permatex Canada
101-2360 Bristol Circle
Oakville, ON Canada L6H 6M5
Telephone: (800) 924-6994

E-mail address mail@permatex.com

Emergency telephone number

Company Phone Number 866-732-9502

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003453

24-hour emergency phone number No information available

2. Hazard(s) identification

Classification

Carcinogenicity	Category 1A

Label elements

Contains CRYSTALLINE SILICA; TITANIUM DIOXIDE; CARBON BLACK; METHYL ISOBUTYL KETONE

Danger

Hazard statements
May cause cancer.

Precautionary Statements - Prevention
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves, protective clothing, eye protection and face protection.
Precautionary Statements - Response
IF exposed or concerned: Get medical advice/attention.

Precautionary Statements - Storage
Store locked up.
Precautionary Statements - Disposal
Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

2.098 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.
13.348 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.
30.154 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).
28.998 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).
18.904 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Other Information
Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
KAOLIN	1332-58-7	30-60%	-	-
ETHANOL	64-17-5	7-13%	-	-
2-PROPANOL	67-63-0	0.5-1.5%	-	-
CRYSTALLINE SILICA	14808-60-7	0.5-1.5%	-	-
TITANIUM DIOXIDE	13463-67-7	0.1-1%	-	-
METHANOL	67-56-1	0.1-1%	-	-
CARBON BLACK	1333-86-4	0.1-1%	-	-
METHYL ISOBUTYL KETONE	108-10-1	0.1-1%	-	-

4. First-aid measures

Description of first aid measures

General advice IF exposed or concerned: Get medical advice/attention.

Inhalation Remove to fresh air.

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.

Skin contact Wash skin with soap and water.

Ingestion Rinse mouth.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Effects of Exposure May cause cancer.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. Fire-fighting measures

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Small Fire In case of fire, use water spray, foam, dry chemical, or CO2.
Large Fire In case of fire, use water spray, foam, dry chemical, or CO2.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the chemical No information available.

Hazardous combustion products No information available.

Explosion data
Sensitivity to mechanical impact None.
Sensitivity to static discharge None.

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation.

Other information Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

8. Exposure controls/personal protection

Control Parameters
Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
KAOLIN 1332-58-7	TWA: 2 mg/m³ respirable particulate matter particulate matter containing no Asbestos and <1% Crystalline silica	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction (vacated) TWA: 10 mg/m³ total dust (vacated) TWA: 5 mg/m³ respirable fraction	TWA: 10 mg/m³; total dust TWA: 5 mg/m³; respirable dust
ETHANOL 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m³	TWA: 1000 ppm; TWA: 1900 mg/m³; IDLH: 3300 ppm
2-PROPANOL 67-63-0	TWA: 200 ppm STEL: 400 ppm	TWA: 400 ppm TWA: 980 mg/m³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m³	TWA: 400 ppm; TWA: 980 mg/m³; STEL: 500 ppm STEL: 1225 mg/m³ IDLH: 2000 ppm
CRYSTALLINE SILICA 14808-60-7	TWA: 0.025 mg/m³ respirable particulate matter	TWA: 50 µg/m³ TWA: 50 µg/m³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m³ respirable dust : (250)/(%SiO2 + 5) mppcf TWA respirable fraction : (10)/(%SiO2 + 2) mg/m³ TWA respirable fraction	TWA: 0.05 mg/m³; respirable dust IDLH: 50 mg/m³ respirable dust
TITANIUM DIOXIDE 13463-67-7	TWA: 0.2 mg/m³ nanoscale respirable particulate matter TWA: 2.5 mg/m³ finescale respirable particulate matter	TWA: 15 mg/m³ total dust (vacated) TWA: 10 mg/m³ total dust	TWA: 2.4 mg/m³; CIB 63 fine TWA: 0.3 mg/m³; CIB 63 ultrafine, including engineered nanoscale IDLH: 5000 mg/m³
METHANOL 67-56-1	TWA: 200 ppm STEL: 250 ppm pSk	TWA: 200 ppm TWA: 260 mg/m³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m³ Sdv	TWA: 200 ppm; TWA: 260 mg/m³; STEL: 250 ppm STEL: 325 mg/m³ IDLH: 6000 ppm
CARBON BLACK 1333-86-4	TWA: 3 mg/m³ inhalable particulate matter	TWA: 3.5 mg/m³ (vacated) TWA: 3.5 mg/m³	TWA: 3.5 mg/m³; TWA: 0.1 mg/m³; Carbon black in presence of Polycyclic

			aromatic hydrocarbons PAH IDLH: 1750 mg/m³
METHYL ISOBUTYL KETONE 108-10-1	TWA: 20 ppm STEL: 75 ppm	TWA: 100 ppm TWA: 410 mg/m³ (vacated) TWA: 50 ppm (vacated) TWA: 205 mg/m³ (vacated) STEL: 75 ppm (vacated) STEL: 300 mg/m³	TWA: 50 ppm; TWA: 205 mg/m³; STEL: 75 ppm STEL: 300 mg/m³ IDLH: 500 ppm

Chemical name	Alberta	British Columbia	Ontario	Quebec
KAOLIN 1332-58-7	TWA: 2 mg/m³; respirable	TWA: 2 mg/m³; respirable particulate	TWA: 2 mg/m³; respirable particulate matter	TWAEV: 2 mg/m³; respirable dust
ETHANOL 64-17-5	TWA: 1000 ppm; TWA: 1880 mg/m³;	STEL: 1000 ppm;	STEL: 1000 ppm;	STEV: 1000 ppm;
2-PROPANOL 67-63-0	TWA: 200 ppm; TWA: 492 mg/m³; STEL: 400 ppm; STEL: 984 mg/m³;	TWA: 200 ppm; STEL: 400 ppm;	TWA: 200 ppm; STEL: 400 ppm;	TWAEV: 200 ppm; STEV: 400 ppm;
CRYSTALLINE SILICA 14808-60-7	TWA: 0.025 mg/m³; respirable particulate	TWA: 0.025 mg/m³; respirable	TWA: 0.10 mg/m³; respirable fraction	TWAEV: 0.05 mg/m³; respirable dust
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m³;	TWA: 10 mg/m³; total dust TWA: 3 mg/m³; respirable fraction	TWA: 10 mg/m³;	TWAEV: 10 mg/m³; total dust
METHANOL 67-56-1	TWA: 200 ppm; TWA: 262 mg/m³; STEL: 250 ppm; STEL: 328 mg/m³; pSk	TWA: 200 ppm; STEL: 250 ppm; Sk	TWA: 200 ppm; STEL: 250 ppm; dSk	TWAEV: 200 ppm; TWAEV: 262 mg/m³; STEV: 250 ppm; STEV: 328 mg/m³; Sd
CARBON BLACK 1333-86-4	TWA: 3.5 mg/m³;	TWA: 3 mg/m³; inhalable	TWA: 3 mg/m³; inhalable particulate matter	TWAEV: 3 mg/m³; inhalable dust
METHYL ISOBUTYL KETONE 108-10-1	TWA: 50 ppm; TWA: 205 mg/m³; STEL: 75 ppm; STEL: 307 mg/m³;	TWA: 20 ppm; STEL: 75 ppm;	TWA: 20 ppm; STEL: 75 ppm;	TWAEV: 20 ppm; STEV: 75 ppm;

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
KAOLIN	TWA: 2 mg/m³; particulate matter, respirable particulate matter	TWA: 2 mg/m³;	TWA: 2 mg/m³; particulate matter, respirable particulate matter	TWA: 2 mg/m³; particulate matter, respirable particulate matter
ETHANOL	STEL: 1000 ppm;	STEL: 1000 ppm;	STEL: 1000 ppm;	STEL: 1000 ppm;
2-PROPANOL	TWA: 200 ppm; STEL: 400 ppm;	TWA: 200 ppm; STEL: 400 ppm;	TWA: 200 ppm; STEL: 400 ppm;	TWA: 200 ppm; STEL: 400 ppm;
CRYSTALLINE SILICA	TWA: 0.025 mg/m³; respirable particulate matter	TWA: 0.025 mg/m³; respirable fraction	TWA: 0.025 mg/m³; respirable particulate matter	TWA: 0.025 mg/m³; respirable particulate matter
TITANIUM DIOXIDE	TWA: 0.2 mg/m³; nanoscale respirable particulate matter TWA: 2.5 mg/m³; finescale respirable particulate matter	TWA: 10 mg/m³;	TWA: 0.2 mg/m³; nanoscale respirable particulate matter TWA: 2.5 mg/m³; finescale respirable particulate matter	TWA: 0.2 mg/m³; nanoscale respirable particulate matter TWA: 2.5 mg/m³; finescale respirable particulate matter
METHANOL	TWA: 200 ppm; STEL: 250 ppm; pSk	TWA: 200 ppm; STEL: 250 ppm; pSk	TWA: 200 ppm; STEL: 250 ppm; pSk	TWA: 200 ppm; STEL: 250 ppm; pSk
CARBON BLACK	TWA: 3 mg/m³; inhalable particulate matter	TWA: 3 mg/m³; inhalable fraction	TWA: 3 mg/m³; inhalable particulate matter	TWA: 3 mg/m³; inhalable particulate matter
METHYL ISOBUTYL KETONE	TWA: 20 ppm;	TWA: 20 ppm;	TWA: 20 ppm;	TWA: 20 ppm;

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
	STEL: 75 ppm;	STEL: 75 ppm;	STEL: 75 ppm;	STEL: 75 ppm;

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
KAOLIN	TWA: 2 mg/m³; respirable fraction STEL: 4 mg/m³; respirable fraction	TWA: 2 mg/m³; particulate matter, respirable particulate matter	TWA: 2 mg/m³; respirable fraction STEL: 4 mg/m³; respirable fraction	TWA: 30 mppcf; TWA: 10 mg/m³; STEL: 20 mg/m³;
ETHANOL	TWA: 1000 ppm; STEL: 1250 ppm;	STEL: 1000 ppm;	TWA: 1000 ppm; STEL: 1250 ppm;	TWA: 1000 ppm; TWA: 1900 mg/m³; STEL: 1000 ppm; STEL: 1900 mg/m³;
2-PROPANOL	TWA: 200 ppm; STEL: 400 ppm;	TWA: 200 ppm; STEL: 400 ppm;	TWA: 200 ppm; STEL: 400 ppm;	TWA: 400 ppm; TWA: 980 mg/m³; STEL: 500 ppm; STEL: 1225 mg/m³; Sk
CRYSTALLINE SILICA	TWA: 0.05 mg/m³; respirable fraction	TWA: 0.025 mg/m³; respirable particulate matter	TWA: 0.05 mg/m³; respirable fraction	TWA: 300 particle/mL;
TITANIUM DIOXIDE	TWA: 10 mg/m³; STEL: 20 mg/m³;	TWA: 0.2 mg/m³; nanoscale respirable particulate matter TWA: 2.5 mg/m³; finescale respirable particulate matter	TWA: 10 mg/m³; STEL: 20 mg/m³;	TWA: 30 mppcf; TWA: 10 mg/m³; STEL: 20 mg/m³;
METHANOL	TWA: 200 ppm; STEL: 250 ppm; Sk	TWA: 200 ppm; STEL: 250 ppm;	TWA: 200 ppm; STEL: 250 ppm; pSd	TWA: 200 ppm; TWA: 260 mg/m³; STEL: 250 ppm; STEL: 310 mg/m³; Sk
CARBON BLACK	TWA: 3.5 mg/m³; STEL: 7 mg/m³;	TWA: 3 mg/m³; inhalable particulate matter	TWA: 3.5 mg/m³; STEL: 7 mg/m³;	TWA: 3.5 mg/m³; STEL: 7 mg/m³;
METHYL ISOBUTYL KETONE	TWA: 50 ppm; STEL: 75 ppm;	TWA: 20 ppm; STEL: 75 ppm;	TWA: 50 ppm; STEL: 75 ppm;	TWA: 100 ppm; TWA: 410 mg/m³; STEL: 125 ppm; STEL: 510 mg/m³; Sk

Biological occupational exposure limits

Chemical name	ACGIH
2-PROPANOL 67-63-0	40 mg/L - urine (Acetone) - end of shift at end of workweek
METHANOL 67-56-1	15 mg/L - urine (Methanol) - end of shift
METHYL ISOBUTYL KETONE 108-10-1	1 mg/L - urine (MIBK) - end of shift

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear suitable gloves.

Skin and body protection Wear suitable protective clothing.

Respiratory protection Use appropriate respiratory protection.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

Thermal hazards No information available.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state	Paste / Gel Liquid
Appearance	Black Paste
Color	Black
Odor	Alcohol
Odor threshold	No information available

Property	**Values**	**Remarks • Method**
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	82 °C / 179.6 °F	
Flash point	No data available	CC (closed cup)
Evaporation rate	7.7	Ether = 1
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability limit:	No data available	
Lower flammability limit:	No data available	
Vapor pressure	33 mm Hg @ 68°F	
Vapor density	2.0	Air = 1
Relative density	1.5	
Water solubility	Partially soluble	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	No data available	
Particle characteristics		
Particle Size	No data available	
Particle Size Distribution	No data available	

Other information

Explosive properties	No information available
Oxidizing properties	No information available
Softening point	No information available
Molecular weight	No information available
VOC content	13%
Density	No information available
Bulk density	No information available

10. Stability and reactivity

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions None under normal processing.

Hazardous polymerization No information available.

Conditions to avoid None known based on information supplied.

Incompatible materials None known based on information supplied.

Hazardous decomposition products None known based on information supplied.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available.

Eye contact Specific test data for the substance or mixture is not available.

Skin contact Specific test data for the substance or mixture is not available.

Ingestion Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity .

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral)	6,874.10 mg/kg
ATEmix (dermal)	9,074.80 mg/kg
ATEmix (inhalation-gas)	99,999.00 ppm
ATEmix (inhalation-vapor)	1,848.7668 mg/l
ATEmix (inhalation-dust/mist)	75.50 mg/l

2.098 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
13.348 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
30.154 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
28.998 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
18.904 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
KAOLIN 1332-58-7	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rat)	-
ETHANOL 64-17-5	= 7060 mg/kg (Rat)	-	= 116.9 mg/L (Rat) 4 h = 133.8 mg/L (Rat) 4 h
2-PROPANOL 67-63-0	5050 mg/kg	12800 mg/kg	> 10000 ppm (Rat) 6 h
TITANIUM DIOXIDE 13463-67-7	> 2000 mg/kg (Rat)	-	> 5.09 mg/L (Rat) 4 h
METHANOL 67-56-1	= 6200 mg/kg (Rat)	= 15840 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h
CARBON BLACK 1333-86-4	> 10000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 4.6 mg/m^3 (Rat) 4 h
METHYL ISOBUTYL KETONE 108-10-1	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	2000 - 4000 ppm (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation No information available.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
KAOLIN 1332-58-7	A4 - Not Classifiable as a Human Carcinogen	-	-	-
ETHANOL 64-17-5	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	Group 1 - Carcinogenic to humans	Known Human Carcinogen	Present
2-PROPANOL 67-63-0	A4 - Not Classifiable as a Human Carcinogen	-	-	-
CRYSTALLINE SILICA 14808-60-7	A2 - Suspected Human Carcinogen	Group 1 - Carcinogenic to humans	Known Human Carcinogen	Present
TITANIUM DIOXIDE 13463-67-7	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	Group 2B - Possibly carcinogenic to humans	-	Present
CARBON BLACK 1333-86-4	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	Group 2B - Possibly carcinogenic to humans	-	Present
METHYL ISOBUTYL KETONE 108-10-1	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	Group 2B - Possibly carcinogenic to humans	-	Present

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)
A2 - Suspected human carcinogen
A3 - Animal Carcinogen
IARC (International Agency for Research on Cancer)
Group 1 - Carcinogenic to humans
Group 2B - Possibly carcinogenic to humans
NTP (National Toxicology Program)
Known - Known Carcinogen
Occupational Safety and Health Administration of the US Department of Labor
X - Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

12. Ecological information

Ecotoxicity Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
ETHANOL 64-17-5	-	LC50: 12.0 - 16.0mL/L (96h, Oncorhynchus mykiss) LC50: >100mg/L (96h, Pimephales promelas) LC50: 13400 - 15100mg/L (96h, Pimephales promelas)	-	LC50: 9268 - 14221mg/L (48h, Daphnia magna) EC50: =2mg/L (48h, Daphnia magna)
2-PROPANOL 67-63-0	EC50: >1000mg/L (96h, Desmodesmus subspicatus) EC50: >1000mg/L (72h, Desmodesmus subspicatus)	LC50: =9640mg/L (96h, Pimephales promelas) LC50: =11130mg/L (96h, Pimephales promelas) LC50: >1400000µg/L (96h, Lepomis macrochirus)	-	EC50: =13299mg/L (48h, Daphnia magna)
METHANOL 67-56-1	-	LC50: =28200mg/L (96h, Pimephales promelas) LC50: >100mg/L (96h, Pimephales promelas) LC50: 19500 - 20700mg/L (96h, Oncorhynchus mykiss) LC50: 18 - 20mL/L (96h, Oncorhynchus mykiss) LC50: 13500 - 17600mg/L (96h, Lepomis macrochirus)	-	-
METHYL ISOBUTYL KETONE 108-10-1	EC50: =400mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 496 - 514mg/L (96h, Pimephales promelas)	-	EC50: =170mg/L (48h, Daphnia magna)

Persistence and degradability No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
ETHANOL 64-17-5	-0.35
2-PROPANOL 67-63-0	0.05
METHANOL 67-56-1	-0.77
METHYL ISOBUTYL KETONE 108-10-1	1.9

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products	Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Do not reuse empty containers.
US EPA Waste Number	Waste designations and classifications should be determined by the end user based on the application for which the product was used.

14. Transport information

DOT	Not regulated
TDG	Not regulated
MEX	Not regulated
ICAO (air)	Not regulated
IATA	Not regulated
IMDG	Not regulated

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Does not comply
IECSC	Complies
KECI	Complies
PICCS	Complies
AICS	Complies
NZIoC	Complies

Legend:
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing Chemicals Inventory
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances
NZIoC - New Zealand Inventory of Chemicals

US Federal Regulations

SARA 313
Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
2-PROPANOL - 67-63-0	1.0
METHYL ISOBUTYL KETONE - 108-10-1	0.1

SARA 311/312 Hazard Categories
Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)
This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA
This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
METHANOL 67-56-1	5000 lb / kg (final RQ)	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
METHYL ISOBUTYL KETONE 108-10-1	5000 lb / kg (final RQ)	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65
This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
ETHANOL - 64-17-5	*Developmental (in alcoholic beverages)
CRYSTALLINE SILICA - 14808-60-7	*Carcinogen
TITANIUM DIOXIDE - 13463-67-7	*Carcinogen (airborne, unbound particles of respirable size)
METHANOL - 67-56-1	Developmental
CARBON BLACK - 1333-86-4	*Carcinogen (airborne, unbound particles of respirable size)
METHYL ISOBUTYL KETONE - 108-10-1	Carcinogen Developmental

*The asterisked chemical(s) listed are not subject to Proposition 65 because they are not airborne in the finished product Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage Ethanol has been shown to be a reproductive toxin only when consumed as an alcoholic beverage

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
KAOLIN 1332-58-7	X	X	X
ETHANOL 64-17-5	X	X	X
2-PROPANOL 67-63-0	X	X	X
WATER 7732-18-5	-	-	X
CRYSTALLINE SILICA 14808-60-7	X	X	X

TITANIUM DIOXIDE 13463-67-7	X	X	X
METHANOL 67-56-1	X	X	X
CARBON BLACK 1333-86-4	X	X	X
METHYL ISOBUTYL KETONE 108-10-1	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA	**Health hazards** 1	**Flammability** 0	**Instability** 0	**Special hazards** -
HMIS	**Health hazards** *	**Flammability** 0	**Physical hazards** 0	**Personal protection** X

Chronic Hazard Star Legend ** = Chronic Health Hazard*

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend
SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances
STOT: Specific Target Organ Toxicity
ATE: Acute Toxicity Estimate
LC50: 50% Lethal Concentration
LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
+	Sensitizers		

Key literature references and sources for data used to compile the SDS
U.S. Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
U.S. Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGL(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
Japan National Institute of Technology and Evaluation (NITE)
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine’s PubMed database (NLM PUBMED)
U.S. National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
International Organization for Economic Co-operation and Development (OECD) Environment, Health, and Safety Publications
International Organization for Economic Co-operation and Development (OECD) High Production Volume Chemicals Program
International Organization for Economic Co-operation and Development (OECD) Screening Information Data Set
United Nations World Health Organization (WHO)

Revision Date 09-Jun-2025

Revision Note No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.