

**FEATURES:**

1. Terminal lugs are dual rated for use with both copper and aluminum cables.

**SPECIFICATIONS:**

1. UL486B listed Wire Connector.
2. Temperature Rating: 90 °C.
3. Voltage: 600V.
4. AL9CU.



PROGRAM:	SOLIDWORKS
UPDATED:	10/2024
SALES REV:	B
SIZE:	C

## LK Series:Transformer Lug Kits Mechanical Set-Screw Types



CAT. NO.	TRANSFORMER KVA SIZE	TERMINAL LUGS INCLUDED			HARDWARE INCLUDED		STD. CTN. QTY
		QTY.	LUG TYPE	WIRE RANGE	QTY.	BOLT SIZE	
LK-1	15-37-1/2 1ø	8	8	2-14	8	1/4-20X3/4	1
	15-45-3Ø	4	4	250 MCM-6	8	1/4-20X3/4	1
LK-2	50-75 1ø	12	12	250 MCM-6	8	1/4-20 x 3/4	1
	75-112-1/2 3ø	12	12	250 MCM-6	8	1/4-20 x 1 3/4	1
LK-3	100-167 1ø	3	3	250 MCM-6	3	1/4-20 x 3/4	1
	150-300 3ø	22	22	600 MCM-2	16	3/8-16 x 2	1
LK-4	500 3ø	29	29	600 MCM-2	18	3/8-16 x 2	1
LK-5	15-25 1ø	7	7	1/0-14	7	1/4-20 x 1 1/2	1
	15-37 1/2 3ø	7	7	1/0-14	7	1/4-20 x 1 1/2	1
LK-6	37 1/2-50 1ø	7	7	250 MCM-6	7	5/16-16 x 1 1/2	1
	45-75 3ø	6	6	350 MCM-6	7	5/16-16 x 1 1/2	1
		3	3	1/0-14	3	1/4-20 x 1	1
LK-7	225 3ø	6	6	350 MCM-6	6	1/2-13 x 2	1
		6	6	350 MCM-6	13	3/8-16 x 1 1/2	1
LK-8	225 3ø	3	3	500 MCM-4	7	3/8-16 x 2	1
		4	4	600 MCM-2	7	3/8-16 x 2	1
LK-9	300 3ø	3	3	350 MCM-6	7	1/2-13 x 2	1
		12	12	500 MCM-4	4	1/2-13 x 2 1/2	1
LK-10	400-500 3ø	16	16	800-300 MCM	11	1/2-13 x 2 1/2	1
		3	3	600 MCM-2	11	1/2-13 x 2 1/2	1

