



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS  
which includes the amended Hazardous Products Act (HPA) and the Hazardous Products  
Regulation (HPR)

Revision Date 12-Jun-2025

Version 3

## 1. Identification

### Product identifier

**Product Name** 133MA ANTI-SEIZE LUBRICANT 8.5 OZ

### Other means of identification

**Product Code** 81464

**UN number or ID number** 1950

**Synonyms** CAN Item Number 76765

### Recommended use of the chemical and restrictions on use

**Recommended Use** Aerosol Lubricant

**Restrictions on use** No information available

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

ITW Permatex, Inc.  
6875 Parkland Blvd.  
Solon, Ohio 44139 USA  
Telephone: 1-87-Permatex  
(866) 732-9502

#### **May Also Be Distributed by:**

ITW Permatex Canada  
101-2360 Bristol Circle  
Oakville, ON Canada L6H 6M5  
Telephone: (800) 924-6994

**E-mail address** mail@permatec.com

### Emergency telephone number

**24 Hour Emergency Phone Number** Chem-Tel: 800-255-3924  
International Emergency:  
00+1+ 813-248-0585  
Contract Number: MIS0003453

**24-hour emergency phone number** No information available

## 2. Hazard(s) identification

### Classification

Aerosols	Category 1
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Aspiration hazard	Category 1

**Label elements**

Contains HEPTANE; ACETONE; DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC [<3% DMSO]; PARAFFIN OILS (PETROLEUM), CATALYTIC DEWAXED LIGHT

**Danger****Hazard statements**

Extremely flammable aerosol. Pressurized container: May burst if heated.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause cancer.  
May cause drowsiness or dizziness.  
May be fatal if swallowed and enters airways.

**Precautionary Statements - Prevention**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Wear protective gloves, protective clothing, eye protection and face protection.  
Wash face, hands and any exposed skin thoroughly after handling.  
Avoid breathing dust, fume, gas, mist, vapors and spray.  
Use only outdoors or in a well-ventilated area.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Do not pierce or burn, even after use.  
Do not spray on an open flame or other ignition source.

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention.  
Specific treatment (see supplemental first aid instructions on this label).

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice and attention.

**Skin**

IF ON SKIN: Wash with plenty of water and soap.  
If skin irritation occurs: Get medical advice and attention.  
Take off contaminated clothing and wash it before reuse.

**Inhalation**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
Call a POISON CENTER or doctor if you feel unwell.

**Ingestion**

IF SWALLOWED: Immediately call a POISON CENTER or doctor.  
Do NOT induce vomiting.

**Precautionary Statements - Storage**

Store locked up.  
Store in a well-ventilated place. Keep container tightly closed.  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

**Precautionary Statements - Disposal**

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

66.11805 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.  
44.61805 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.  
71.37805 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).  
89.37805 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).  
50.60305 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

**Other Information**

Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

### 3. Composition/information on ingredients

#### Substance

Not applicable.

#### Mixture

**Synonyms** CAN Item Number 76765.

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
HEPTANE	142-82-5	10-30%	-	-
PROPANE	74-98-6	10-30%	-	-
ACETONE	67-64-1	10-30%	-	-
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC [<3% DMSO]	64742-52-5	7-13%	-	-
SILICA, MICA	12001-26-2	5-10%	-	-
ALUMINIUM POWDER	7429-90-5	1-5%	-	-
GRAPHITE	7782-42-5	1-5%	-	-
PARAFFIN OILS (PETROLEUM), CATALYTIC DEWAXED LIGHT	64742-71-8	0.5-1.5%	-	-

### 4. First-aid measures

#### Description of first aid measures

##### **General advice**

Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. Immediate medical attention is required.

##### **Inhalation**

Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.

##### **Eye contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.

##### **Skin contact**

Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.

##### **Ingestion**

Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical attention.

##### **Self-protection of the first aider**

Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

**Most important symptoms and effects, both acute and delayed**

**Symptoms** Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

**Effects of Exposure** May cause cancer.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.

**5. Fire-fighting measures**

**Suitable Extinguishing Media** Dry chemical. Carbon dioxide (CO2). Water spray.

**Large Fire** CAUTION: Use of water spray when fighting fire may be inefficient.

**Unsuitable extinguishing media** DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

**Specific hazards arising from the chemical** Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated.

**Explosion data**

**Sensitivity to mechanical impact** None.

**Sensitivity to static discharge** Yes.

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

**6. Accidental release measures****Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapors/spray.

**Other information** Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

**Methods and material for containment and cleaning up**

**Methods for containment** Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.

**Methods for cleaning up** Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

**7. Handling and storage**

**Precautions for safe handling****Advice on safe handling**

Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapors or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

**Conditions for safe storage, including any incompatibilities****Storage Conditions**

Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Store locked up. Keep out of the reach of children. Store away from other materials.

**8. Exposure controls/personal protection****Control Parameters****Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
HEPTANE 142-82-5	TWA: 200 ppm TWA: 400 ppm STEL: 400 ppm STEL: 500 ppm pOt	TWA: 500 ppm TWA: 2000 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m <sup>3</sup>	TWA: 85 ppm; TWA: 350 mg/m <sup>3</sup> ; Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m <sup>3</sup> 15 min IDLH: 750 ppm
PROPANE 74-98-6	: See Appendix F: Minimal Oxygen Content, explosion hazard Sa	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup>	TWA: 1000 ppm; TWA: 1800 mg/m <sup>3</sup> ; IDLH: 2100 ppm
ACETONE 67-64-1	TWA: 250 ppm STEL: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) STEL: 2400 mg/m <sup>3</sup> The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	TWA: 250 ppm; TWA: 590 mg/m <sup>3</sup> ; IDLH: 2500 ppm
SILICA, MICA 12001-26-2	TWA: 0.1 mg/m <sup>3</sup> respirable particulate matter	TWA: 20 mppcf respirable dust <1% Crystalline silica (vacated) TWA: 3 mg/m <sup>3</sup> respirable dust <1% Crystalline silica TWA: 20 mppcf <1% Crystalline silica	TWA: 3 mg/m <sup>3</sup> ; containing <1% Quartz respirable dust IDLH: 1500 mg/m <sup>3</sup>
ALUMINIUM POWDER 7429-90-5	TWA: 1 mg/m <sup>3</sup> respirable particulate matter	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> ; total dust TWA: 5 mg/m <sup>3</sup> ; respirable dust TWA: 5 mg/m <sup>3</sup> ; Al

		respirable fraction (vacated) TWA: 5 mg/m <sup>3</sup> Al Aluminum	
GRAPHITE 7782-42-5	TWA: 2 mg/m <sup>3</sup> respirable particulate matter all forms except graphite fibers	TWA: 15 mg/m <sup>3</sup> total dust synthetic TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf respirable dust natural (vacated) TWA: 2.5 mg/m <sup>3</sup> respirable dust natural (vacated) TWA: 10 mg/m <sup>3</sup> total dust synthetic (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf natural	TWA: 2.5 mg/m <sup>3</sup> ; natural respirable dust IDLH: 1250 mg/m <sup>3</sup>

Chemical name	Alberta	British Columbia	Ontario	Quebec
HEPTANE 142-82-5	TWA: 400 ppm; TWA: 1640 mg/m <sup>3</sup> ; STEL: 500 ppm; STEL: 2050 mg/m <sup>3</sup> ;	TWA: 400 ppm; STEL: 500 ppm;	TWA: 400 ppm; STEL: 500 ppm;	TWAEV: 400 ppm; STEV: 500 ppm;
PROPANE 74-98-6	TWA: 1000 ppm;	Sa	: ; Sa (See Appendix F: Minimal Oxygen Content;explosion hazard)	Sa
ACETONE 67-64-1	TWA: 500 ppm; TWA: 1200 mg/m <sup>3</sup> ; STEL: 750 ppm; STEL: 1800 mg/m <sup>3</sup> ;	TWA: 250 ppm; STEL: 500 ppm;	TWA: 250 ppm; STEL: 500 ppm;	TWAEV: 250 ppm; STEV: 500 ppm;
SILICA, MICA 12001-26-2	TWA: 3 mg/m <sup>3</sup> ; respirable	TWA: 3 mg/m <sup>3</sup> ; respirable	TWA: 3 mg/m <sup>3</sup> ; respirable particulate matter	TWAEV: 0.1 mg/m <sup>3</sup> ; respirable aerosol fraction
ALUMINIUM POWDER 7429-90-5	TWA: 10 mg/m <sup>3</sup> ; dust TWA: 5 mg/m <sup>3</sup> ;	TWA: 1.0 mg/m <sup>3</sup> ; respirable	TWA: 1 mg/m <sup>3</sup> ; respirable particulate matter	TWAEV: 5 mg/m <sup>3</sup> ;
GRAPHITE 7782-42-5	TWA: 2 mg/m <sup>3</sup> ; respirable	TWA: 2 mg/m <sup>3</sup> ; respirable	TWA: 2 mg/m <sup>3</sup> ; respirable particulate matter	TWAEV: 2 mg/m <sup>3</sup> ; respirable dust

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
HEPTANE	TWA: 200 ppm; STEL: 400 ppm;	TWA: 400 ppm; STEL: 500 ppm;	TWA: 400 ppm; STEL: 400 ppm;	TWA: 200 ppm; STEL: 400 ppm;
PROPANE	: ; Sa (See Appendix F: Minimal Oxygen Content)	: ;	: ;	: ; Sa (See Appendix F: Minimal Oxygen Content)
ACETONE	TWA: 250 ppm; STEL: 500 ppm;	TWA: 250 ppm; STEL: 500 ppm;	TWA: 250 ppm; STEL: 500 ppm;	TWA: 250 ppm; STEL: 500 ppm;
SILICA, MICA	TWA: 0.1 mg/m <sup>3</sup> ; respirable particulate matter	TWA: 3 mg/m <sup>3</sup> ; respirable fraction	TWA: 0.1 mg/m <sup>3</sup> ; respirable particulate matter	TWA: 0.1 mg/m <sup>3</sup> ; respirable particulate matter
ALUMINIUM POWDER	TWA: 1 mg/m <sup>3</sup> ; respirable particulate matter	TWA: 1 mg/m <sup>3</sup> ; respirable fraction	TWA: 1 mg/m <sup>3</sup> ; respirable particulate matter	TWA: 1 mg/m <sup>3</sup> ; respirable particulate matter
GRAPHITE	TWA: 2 mg/m <sup>3</sup> ; respirable particulate matter	TWA: 2 mg/m <sup>3</sup> ; respirable fraction	TWA: 2 mg/m <sup>3</sup> ; respirable particulate matter	TWA: 2 mg/m <sup>3</sup> ; respirable particulate matter

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
HEPTANE	TWA: 400 ppm; STEL: 500 ppm;	TWA: 200 ppm; STEL: 400 ppm;	TWA: 400 ppm; STEL: 500 ppm;	TWA: 400 ppm; TWA: 1600 mg/m <sup>3</sup> ; STEL: 500 ppm; STEL: 2000 mg/m <sup>3</sup> ;
PROPANE	TWA: 1000 ppm; STEL: 1250 ppm;	: ;	TWA: 1000 ppm; STEL: 1250 ppm;	Sa
ACETONE	TWA: 500 ppm; STEL: 750 ppm;	TWA: 250 ppm; STEL: 500 ppm;	TWA: 500 ppm; STEL: 750 ppm;	TWA: 1000 ppm; TWA: 2400 mg/m <sup>3</sup> ; STEL: 1250 ppm; STEL: 3000 mg/m <sup>3</sup> ;
SILICA, MICA	TWA: 3 mg/m <sup>3</sup> ; respirable fraction STEL: 6 mg/m <sup>3</sup> ; respirable fraction	TWA: 0.1 mg/m <sup>3</sup> ; respirable particulate matter	TWA: 3 mg/m <sup>3</sup> ; respirable fraction STEL: 6 mg/m <sup>3</sup> ; respirable fraction	TWA: 20 mppcf;
ALUMINIUM POWDER	TWA: 10 mg/m <sup>3</sup> ; dust STEL: 20 mg/m <sup>3</sup> ; dust	TWA: 1 mg/m <sup>3</sup> ; respirable particulate matter	TWA: 10 mg/m <sup>3</sup> ; dust STEL: 20 mg/m <sup>3</sup> ; dust	
GRAPHITE	TWA: 2 mg/m <sup>3</sup> ; respirable fraction STEL: 4 mg/m <sup>3</sup> ; respirable fraction	TWA: 2 mg/m <sup>3</sup> ; respirable particulate matter	TWA: 2 mg/m <sup>3</sup> ; respirable fraction STEL: 4 mg/m <sup>3</sup> ; respirable fraction	TWA: 20 mppcf; TWA: 30 mppcf; TWA: 10 mg/m <sup>3</sup> ;

#### Biological occupational exposure limits

Chemical name	ACGIH
ACETONE 67-64-1	25 mg/L - urine (Acetone) - end of shift

#### Appropriate engineering controls

Engineering controls	Showers Eyewash stations Ventilation systems.
----------------------	---

#### Individual protection measures, such as personal protective equipment

<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles). Tight sealing safety goggles.
<b>Hand protection</b>	Wear suitable gloves.
<b>Skin and body protection</b>	Wear suitable protective clothing. Long sleeved clothing. Antistatic boots. Chemical resistant apron. Wear fire/flame resistant/retardant clothing.
<b>Respiratory protection</b>	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. Use appropriate respiratory protection.
<b>General hygiene considerations</b>	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

## 9. Physical and chemical properties

#### Information on basic physical and chemical properties

Physical state	Aerosol
----------------	---------

<b>Appearance</b>	No information available	
<b>Color</b>	Gray	
<b>Odor</b>	Solvent	
<b>Odor threshold</b>	No information available	
<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>
<b>pH</b>	No data available	
<b>Melting point / freezing point</b>	No data available	
<b>Boiling point / boiling range</b>	No data available	
<b>Flash point</b>	< -18 °C / -0.4 °F	Gives a flame projection at full valve opening or flashback at any degree of valve opening
<b>Evaporation rate</b>	Not applicable	
<b>Flammability (solid, gas)</b>	No data available	
<b>Flammability Limit in Air</b>		
<b>Upper flammability limit:</b>	No data available	
<b>Lower flammability limit:</b>	No data available	
<b>Vapor pressure</b>	No data available	
<b>Vapor density</b>	>1	Air = 1
<b>Relative density</b>	0.885-0.905	
<b>Water solubility</b>	Insoluble in water	
<b>Solubility(ies)</b>	No data available	
<b>Partition coefficient</b>	No data available	
<b>Autoignition temperature</b>	No data available	
<b>Decomposition temperature</b>	No data available	
<b>Kinematic viscosity</b>	No data available	
<b>Dynamic viscosity</b>	No data available	
<b>Particle characteristics</b>		
<b>Particle Size</b>	No data available	
<b>Particle Size Distribution</b>	No data available	
<b>Other information</b>		
<b>Explosive properties</b>	No information available	
<b>Oxidizing properties</b>	No information available	
<b>Softening point</b>	No information available	
<b>Molecular weight</b>	No information available	
<b>VOC content</b>	39.5%	
<b>Density</b>	No information available	
<b>Bulk density</b>	No information available	

## 10. Stability and reactivity

<b>Reactivity</b>	No information available.
<b>Chemical stability</b>	Stable under normal conditions.
<b>Possibility of hazardous reactions</b>	None under normal processing.
<b>Conditions to avoid</b>	Heat, flames and sparks.
<b>Incompatible materials</b>	Strong acids. Strong bases. Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Carbon oxides. Copper compounds.

## 11. Toxicological information

### Information on likely routes of exposure

#### Product Information

<b>Inhalation</b>	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.
-------------------	--

<b>Eye contact</b>	Specific test data for the substance or mixture is not available. May cause irritation. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
<b>Skin contact</b>	Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

#### Symptoms related to the physical, chemical and toxicological characteristics

<b>Symptoms</b>	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
-----------------	---

#### Acute toxicity

#### Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral)	7,891.70 mg/kg
ATEmix (dermal)	5,512.50 mg/kg
ATEmix (inhalation-gas)	318,021.70 ppm
ATEmix (inhalation-vapor)	99,999.00 mg/l
ATEmix (inhalation-dust/mist)	8.70 mg/l

66.11805 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

44.61805 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

71.37805 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

89.37805 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

50.60305 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
HEPTANE 142-82-5	-	= 3000 mg/kg ( Rabbit )	> 29.29 mg/L ( Rat ) 4 h
PROPANE 74-98-6	-	-	> 800000 ppm ( Rat ) 15 min
ACETONE 67-64-1	= 5800 mg/kg ( Rat )	> 15700 mg/kg ( Rabbit )	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC [<3% DMSO] 64742-52-5	> 5000 mg/kg ( Rat )	> 5000 mg/kg ( Rabbit )	-
ALUMINIUM POWDER 7429-90-5	-	-	> 0.888 mg/L ( Rat ) 4 h
GRAPHITE 7782-42-5	-	-	> 2000 mg/m <sup>3</sup> ( Rat ) 4 h

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Classification based on data available for ingredients. Causes skin irritation.

**Serious eye damage/eye irritation** Classification based on data available for ingredients. Causes serious eye irritation.

**Respiratory or skin sensitization** No information available.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
ACETONE 67-64-1	A4 - Not Classifiable as a Human Carcinogen	-	-	-
ALUMINIUM POWDER 7429-90-5	A4 - Not Classifiable as a Human Carcinogen	-	-	-
PARAFFIN OILS (PETROLEUM), CATALYTIC DEWAXED LIGHT 64742-71-8	A2 - Suspected Human Carcinogen	Group 1 - Carcinogenic to humans	Known Human Carcinogen	Present

**Legend**

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A2 - Suspected human carcinogen

**IARC (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to humans

**NTP (National Toxicology Program)**

Known - Known Carcinogen

**Occupational Safety and Health Administration of the US Department of Labor**

X - Present

**Reproductive toxicity** No information available.

**STOT - single exposure** May cause drowsiness or dizziness.

**STOT - repeated exposure** No information available.

**Aspiration hazard** May be fatal if swallowed and enters airways.

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
HEPTANE 142-82-5	-	LC50: =375.0mg/L (96h, Cichlid fish)	-	-
ACETONE 67-64-1	-	LC50: 4.74 - 6.33mL/L (96h, Oncorhynchus mykiss) LC50: 6210 - 8120mg/L (96h, Pimephales promelas) LC50: =8300mg/L (96h, Lepomis macrochirus)	-	EC50: 10294 - 17704mg/L (48h, Daphnia magna) EC50: 12600 - 12700mg/L (48h, Daphnia magna)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC [<3% DMSO] 64742-52-5	-	LC50: >5000mg/L (96h, Oncorhynchus mykiss)	-	EC50: >1000mg/L (48h, Daphnia magna)
GRAPHITE 7782-42-5	-	LC50: >100mg/L (96h, Danio rerio)	-	-

**Persistence and degradability** No information available.

**Bioaccumulation****Component Information**

Chemical name	Partition coefficient
HEPTANE 142-82-5	4.66
PROPANE 74-98-6	1.09
ACETONE 67-64-1	-0.24

**Other adverse effects** No information available.

## 13. Disposal considerations

**Waste treatment methods**

**Waste from residues/unused products** Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

**US EPA Waste Number** Waste designations and classifications should be determined by the end user based on the application for which the product was used.

## 14. Transport information

**DOT**

**UN number or ID number** 1950  
**Proper shipping name** Aerosols, Limited Quantity (LQ)  
**Transport hazard class(es)** 2.1  
**Emergency Response Guide Number** 126

**TDG**

**UN number or ID number** 1950  
**UN proper shipping name** Aerosols, Limited Quantity (LQ)  
**Transport hazard class(es)** 2.1

**MEX**

**UN number or ID number** 1950  
**UN proper shipping name** Aerosols, Limited Quantity (LQ)  
**Transport hazard class(es)** 2.1

**IATA**

**UN number or ID number** ID 8000  
**UN proper shipping name** Consumer Commodity  
**Transport hazard class(es)** 9  
**Special Provisions** 9L

**IMDG**

**UN number or ID number** 1950  
**UN proper shipping name** Aerosols Limited Quantity (LQ)  
**Transport hazard class(es)** 2.1

## 15. Regulatory information

### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Regulations

**The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable

**The Stockholm Convention on Persistent Organic Pollutants** Not applicable

**The Rotterdam Convention** Not applicable

#### International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Does not comply
IECSC	Complies
KECI	Complies
PICCS	Complies
AICS	Complies
NZIoC	Complies

#### **Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing Chemicals Inventory

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

#### US Federal Regulations

##### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
ALUMINIUM POWDER - 7429-90-5	1.0

##### **SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

##### **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

##### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
ACETONE 67-64-1	5000 lb / kg (final RQ)	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

#### US State Regulations

**California Proposition 65**

This product does not contain any Proposition 65 chemicals

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
HEPTANE 142-82-5	X	X	X
PROPANE 74-98-6	X	X	X
ACETONE 67-64-1	X	X	X
SILICA, MICA 12001-26-2	X	X	X
ALUMINIUM POWDER 7429-90-5	X	X	X
GRAPHITE 7782-42-5	X	X	X
PARAFFIN OILS (PETROLEUM), CATALYTIC DEWAXED LIGHT 64742-71-8	-	X	-

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**16. Other information**

<b>NFPA</b>	<b>Health hazards</b> 2	<b>Flammability</b> 4	<b>Instability</b> 0	<b>Special hazards</b> -
<b>HMIS</b>	<b>Health hazards</b> 3 *	<b>Flammability</b> 4	<b>Physical hazards</b> 0	<b>Personal protection</b> X

Chronic Hazard Star Legend

\* = Chronic Health Hazard

**Key or legend to abbreviations and acronyms used in the safety data sheet****Legend**

SVHC: Substances of Very High Concern for Authorization:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity

ATE: Acute Toxicity Estimate

LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

**Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
+	Sensitizers		

**Key literature references and sources for data used to compile the SDS**

U.S. Agency for Toxic Substances and Disease Registry (ATSDR)

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

U.S. Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan National Institute of Technology and Evaluation (NITE)

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

U.S. National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

International Organization for Economic Co-operation and Development (OECD) Environment, Health, and Safety Publications

International Organization for Economic Co-operation and Development (OECD) High Production Volume Chemicals Program

International Organization for Economic Co-operation and Development (OECD) Screening Information Data Set

United Nations World Health Organization (WHO)

**Revision Date** 12-Jun-2025

**Revision Note** No information available.

**Disclaimer**

**The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.**