

TurboShearCM



Work. Perform. Outlast.
Limited Lifetime Warranty



Cut corrugated mild steel with ease. Elongated blades with compact jaws create a steep 75-degree offset for a nearly vertical approach when starting a cut. This versatile and portable TurboShear fits a drill you already own to make easy cross cuts, fast lengthwise cuts, even circular and square outlets cuts in large or small pattern corrugated metal roofing and most trapezoidal (box) metal roofing panels.



TSCM
Pat. No. 9,649,702



360° Rotating Head

The 360-degree rotating head allows users to position and lock the drill so it doesn't interfere with material for quick, hassle-free cuts every time!



Drill Requirements:
1/4 in. (6.35 mm) Chuck,
Min. 14.4V - DC, Max 7A-AC

Capacities: Mild Steel 30-24 ga. - 0.012 - 0.024 in.
(0.31 - 0.61 mm)

Catalog Number	Description	Net Wt. oz. (g)	Net Wt. lbs. (kg)
TSCM	Corrugated Metal TurboShear	—	2.2 (1.00)
Replacement Parts			
TSDC	TurboShear Drill Clamp	8 (227)	—
TSCG	TurboShear Chuck Guard	.96 (27)	—
TSCMRB	Corrugated Metal TurboShear Replacement Blades	6.4 (181)	—