



PBE GUIDE COAT

#20-1676

Guide Coat allows you to achieve a perfect repair every time. It provides a visual guide when sanding over primer, body fillers, and glazing putties. Detect low spots, scratches or other minor imperfections in the repair. This ultra thin coating wets the surface evenly, dries fast, and will not clog sandpaper.

Suggested Uses:

Automotive body panels
 fiberglass
 wood

Packaging:

UPC Code	043281002240
Cans per case	6
Shipping weight per case	9 lbs.
Container	20 fluid ounce can
Label weight	15 ounces (425 grams)
Shipping Classification	limited quantity, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 15 square feet
Cleanup	Paint/lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.85
MIR Value:	0.82, does not exceed 0.95
Solids Content	7%
HAPs content	9%
Storage Temperature	40-100F
Application Temperature	50-90F
Abrasion Resistance	Fair
Heat Resistance	250F continuous
Resin System	Acrylic lacquer
Shelf life	Guaranteed for 2 years

Dry Time*:

To touch	5 minutes
To Topcoat	15 minutes

*At 72F, 50% humidity,
 0.3 mil thickness

Gloss*: Flat, <15

*as measured on a 60 degree gloss meter

12-1-2021