



Project Info:	Type:
Job Ref:	Catalog Number:
Approvals:	Date:
Item Number:	UPC Code:66238105526

SPECIFICATION SHEET

DS185

Duct Sealing Compound

DESCRIPTION

Sealant that is permanently soft and non-toxic. The product is designed to be molded by hand, allowing the user to seal around openings, including but not limited to - electrical boxes, flashings, service mast entries, conduit penetrations, etc. It provides an excellent moisture and vapor seal, while remaining permanently flexible and reusable if necessary.



FEATURES

- Excellent Chemical Resistance
- Printable with Latex and Enamels
- Non-Corrosive to Metals
- Excellent Adhesion to most substrates
- 100% Solids for Water-Tight Seals
- Excellent Dielectric Strength - 200 volts / mil or 10 KV

Properties	Value – Result	Test Method
Weight:	13 #'s / gal. +/- .5 #'s gal.	ASTM D71-72
Color:	Gray	
Odor:	Minimal	
Solids Content:	100%	
Dielectric Strength:	200 volts/mil or 10 KV	ASTM D149-64
Specific Gravity:	1.65 – 1.80	ASTM D792-66
Flame / Smoke:	5 /10	UL 723
Cone Penetration:	115 – 140mm /10 @ 25°F	ASTM D217-52T
Sag:	None	AAMA 807.1
Water Absorption:	None	GSTM 21
Oil Migration:	None	C772-03
Shelf Life:	18 Months	
Service Temps:	-40°F/-40°C to 249°F/120°C	
Storage Temps:	10°F/-14°C to 100°F/38°C *Store in clean, dry area	
Sizes:	1lb or 5lb	

APPLICATION INFORMATION

DS185 should be applied to surfaces that are dry, clean and free of contaminants in normal working conditions. After applying product to surface of material, apply ample pressure to secure product in place.

MEETS SPECIFICATIONS

- FDA - for packaging and transporting food as listed in CFR Title 21
- USDA - for use in meat and poultry processing areas
- Made in US
- UL 723 Classified

