

UL-LISTED pressure-type wire connector to UL486C.

TEMPERATURE 105°C (221°F) max.

VOLTAGE 600V max in building wiring; 1000V max in fixtures and signs.



WWC-G | Grey Winged Connectors

FOR UL LISTED AND CQC CERTIFIED

3 #10	3 #14 w/1 or 2 #16
4 #12	3 #14 w/1 or 2 #18
3 #12 w/1 #14	4 #14 w/1 #16
3 #12 w/1 #16	4 #14 w/1 #18

FOR CSA AND CQC CERTIFIED

2 or 3 #10	3 #10 w/1 or 2 #14 or #16	4 #14 w/1 #16 or #18
3 or 4 #12	3 #12 w/1 or 2 #14, #16 or #18	1 #8 w/1 or 2 #10
1 #10 w/3 #18	3 #12 w/1 #14 or #16	1 #8 w/1 to 4 #16 or #18
1 #10 w/2 to 4 #12 or #14	3 #14 w/1 or 2 #16 or #18	



WWC-B | Blue Winged Connectors

FOR UL LISTED AND CQC CERTIFIED

1 or 2 #6	1 #8 w/3 #10	2 #10 w/3 #12
2 #8	1 #10 w/3 #12	3 #10 w/1 #12
2 to 4 #10	2 #10 w/1 #12	3 #10 w/2 #12
3 #12	2 #10 w/2 #12	

FOR CSA AND CQC CERTIFIED

2 or 3 #8	1 or 2 #8 w/1 to 4 #14	3 #10 w/1 #12
2 to 4 #10	3 #8 w/1 #12 or #14	3 #10 Sol w/2 #12 Sol
1 #8 w/1 to 3 #10	1 #10 w/2 or 3 #12	3 #10 Sol w/2 #12 Str
1 or 2 #8 w/1 to 3 #12	2 #10 w/1 to 3 #14	3 #10 Str w/2 #12 Str



WWC-GR | Green Grounding Connectors

USE FOR GROUNDING TERMINAL ONLY

FOR UL LISTED, CSA AND CQC CERTIFIED

2 to 5 #12	1 #12 w/1 to 3 #14
2 to 4 #14	2 #12 w/1 to 3 #14
1 #10 w/1 or 2 #12	3 #12 w/1 #14
1 #10 w/1 to 3 #14	



WWC-R | Red Winged Connectors

FOR UL LISTED AND CSA CERTIFIED

1 #6	2 #10 w/2 #12 w/1 or 2 #16 or #18	2 #14 w/1 #16 w/1 to 3 #18
1 or 2 #8	2 #10 w/2 #12 w/1 #14	3 #14 w/1 to 3 #16, #18, #20 or #22
1 to 4 #10	2 #10 w/1 to 3 #12 or #14	3 #14 w/1 #16 w/1 or 2 #18
1 to 5 #12	2 #10 w/1 to 4 #16 or #18	4 #14 w/1 or 2 #16, #18, #20 or #22
1 to 6 #14 or #16	2 #10 w/2 #14 w/1 or 2 #16	4 #14 w/1 #16 w/1 #18
2 to 6 #18	2 #10 w/1 #16 w/1 to 3 #18	5 #14 w/1 #16 or #18
3 to 6 #20	3 #10 w/1 to 3 #16 or #18	1 #16 w/1 to 5 #18, #20 or #22
4 to 6 #22	3 #10 w/1 #12	1 #16 w/1 #18 w/1 to 3 #20 or #22
1 #6 w/1 #10	3 #10 w/1 or 2 #14	1 or 2 #16 w/1 #20 w/1 or 2 #22
1 #6 w/1 #10 w/1 #14	3 #10 w/1 #12 w/1 #16 or #18	1 #16 w/2 #20 w/1 or 2 #22
1 #6 w/1 or 2 #12	3 #10 w/1 #14 w/1 #16	2 #16 w/1 #18 w/1 to 3 #20 or #22
1 #6 w/1 #12 w/1 or 2 #14	3 #10 w/1 #14 w/1 or 2 #18	2 #16 w/1 to 4 #18, #20 or #22
1 #6 w/2 #12 w/1 #18	3 #10 w/1 #16 w/1 or 2 #18	2 #16 w/2 #20 w/1 or 2 #22
1 #6 w/2 #14 w/1 or 2 #16	1 #12 w/1 #14 w/1 to 3 #18	3 #16 w/1 to 3 #18, #20 or #22
1 #8 w/1 or 2 #10	1 #12 w/1 #16 w/1 to 3 #18	3 #16 w/1 #18 w/1 or 2 #20 or #22
1 #8 w/1 #10 w/1 or 2 #12 or #14	1 #12 w/1 to 5 #14, #16 or #18	3 #16 w/1 #20 w/1 or 2 #22
1 #8 w/2 #10 w/1 #14	1 or 2 #12 w/1 #14 w/1 to 3 #16	4 #16 w/1 or 2 #18, #20 or #22
1 #8 w/1 to 3 #12	1 or 2 #12 w/2 #14 w/1 or 2 #16	4 #16 w/1 #18 w/1 #20 or #22
1 #8 w/2 #12 w/1 or 2 #14	2 #12 w/1 to 4 #14, #16 or #18	4 #16 w/1 #20 w/1 #22
1 #8 w/1 to 4 #14	2 #12 w/1 #14 or #16 w/1 to 3 #18	5 #16 w/1 #18, #20 or #22
1 #8 w/1 to 5 #16	3 #12 w/1 to 3 #14, #16 or #18	1 #18 w/1 to 5 #20 or #22
1 #10 w/1 to 4 #12	3 #12 w/1 #14 w/1 or 2 #16 or #18	1 to 3 #18 w/1 #20 w/1 or 2 #22
1 #10 w/1 #12 w/1 to 4 #14, #16 or #18	3 #12 w/2 #14 w/1 #16	1 to 3 #18 w/2 #20 w/1 #22
1 #10 w/2 #12 w/1 or 2 #14	3 #12 w/1 #16 w/1 or 2 #18	2 #18 w/1 to 4 #20 or #22
1 #10 w/2 #12 w/1 to 3 #16 or #18	4 #12 w/1 #14	3 #18 w/1 to 3 #20 or #22
1 #10 w/3 #12 w/1 #14	4 #12 w/1 #14 w/1 #16 or #18	4 #18 w/1 or 2 #20 or #22
1 #10 w/1 to 5 #14, #16 or #18	4 #12 w/1 or 2 #16	5 #18 w/1 #20 or #22
1 #10 w/1 #14 w/1 to 4 #16 or #18	4 #12 w/1 #16 w/1 #18	1 #20 w/2 to 5 #22
1 #10 w/2 #14 w/1 to 3 #16	1 #14 w/1 to 5 #16 or #18	2 #20 w/1 to 4 #22
1 #10 w/1 #16 w/1 to 4 #18	1 #14 w/1 #16 w/1 to 3 #18	3 #20 w/1 to 3 #22
2 #10 w/1 #12 w/1 or 2 #14	1 #14 w/1 to 5 #20 or #22	4 #20 w/1 or 2 #22
2 #10 w/1 #12 w/1 to 3 #16	2 #14 w/1 to 4 #16, #18, #20 or #22	5 #20 w/1 #22

WWC-T | Tan Winged Connectors

FOR UL LISTED TO US AND CANADIAN SAFETY STANDARDS

1 to 3 #10	1 #16 w/1 or 2 #14 w/1 #12	1 #18 w/1 to 4 #16, #14 or #12
1 to 4 #12	1 #16 w/1 or 2 #14 w/1 #10	1 #18 w/1 or 2 #10
1 to 5 #14	1 #16 w/1 to 4 #14 or #12	2 #18 w/1 to 4 #16 or #14
2 to 6 #20, #18 or #16	1 #16 w/1 or 2 #10	2 #18 w/1 or 2 #10
3 to 6 #22	1 #16 w/1 #12 w/1 #10	3 #18 w/1 to 3 #16, #14 or #12
1 #10 w/1 #8	2 #16 w/1 #14 w/1 or 2 #12	3 #18 w/1 or 2 #10
1 #12 w/1 or 2 #10	2 #16 w/2 #14 w/1 #12	4 #18 w/1 or 2 #16, #14 or #12
1 #12 w/1 #8	2 #16 w/1 #12 w/1 #10	4 #18 w/1 #10
2 #12 w/1 #10	3 #16 w/1 #14 w/1 #12 or #10	5 #18 w/1 #16 or #14
1 #14 w/1 or 2 #12 w/1 #10	4 #16 w/1 #12 w/1 #10	1 #20 w/1 to 4 #18, #16 or #14
1 #14 w/1 to 3 #12	2 #16 w/1 to 4 #14	2 #20 w/1 to 3 #18, #16 or #14
1 #14 w/1 or 2 #10	2 #16 w/1 to 3 #12	3 #20 w/1 or 2 #18, #16 or #14
2 #14 w/1 #12 w/1 #10	2 #16 w/1 or 2 #10	4 #20 w/1 or 2 #18, #16 or #14
2 #14 w/1 or 2 #12	3 #16 w/1 to 3 #14	1 #22 w/1 to 5 #20, #18 or #16
2 #14 w/1 or 2 #10	3 #16 w/1 or 2 #12 or #10	2 #22 w/1 to 4 #20, #18 or #16
2 #14 w/1 #8	4 #16 w/1 or 2 #14 or #12	3 #22 w/1 to 3 #20, #18 or #16
3 #14 w/1 #12 or #10	4 #16 w/1 #10	4 #22 w/1 or 2 #20, #18 or #16
3 #14 w/2 #12	5 #16 w/1 #14	1 #22 w/1 #20 w/1 or 2 #16
4 #14 w/1 #12 or #10	5 #16 w/1 #10	1 #22 w/1 #18 w/1 #16



WWC-N1 | Yellow Compact Winged Connectors

FOR UL LISTED TO U.S. & CANADIAN SAFETY STANDARDS AND CQC CERTIFIED

1 #10, #12 or #14	1 #10 w/1 or 2 #14 or #16	3 #14 w/1 #16, #18, #20 or #22
2 or 3 #12	1 #10w/1 to 3 #18	1 #16 w/1 to 5 #18 or #20
2to 4 #14	1 #12 w/1 or 2 #14 or #16	
2 to 6 #16 or #18	1 #12 w/1 or 2 #18, #20 or #22	
3 to 6 #20	2 #12 w/1 #14, #16, #18, #20 or #22	
4 to 6 #22	1 #14 w/1 to 3 #16, #18, #20 or #22	
1 #10 w/1 #12	2 #14 w/1 or 2 #16, #18, #20 or #22	



WWC-N2 | Red Compact Winged Connectors

FOR UL LISTED TO U.S. & CANADIAN SAFETY STANDARDS AND CQC CERTIFIED

1 #6, #8, #10, #12 or #14	1 #8 w/1 #10 Str w/1 #12 Str	1 #12 w/1 to 4 #14, #16 or #18
2 or 3 #10	1 #8 w/1 to 3 #12 Str	1 #12 w/1 #14 w/1 to 4 #16
2 to 5 #12	1 #8 w/1 #14 Str	1 #12 w/2 to 5 #14, #16 or #18
2 to 6 #14, #16 or #18	1 #10 w/1 to 3 #12	2 #12 w/1 #14, #16 or #18
3 to 6 #20	1 #10 w/1 to 4 #14, #16 or #18	1 #14 w/1 to 6 #16 or #18
5 or 6 #22	2 #10 w/1 or 2 #12 or #14	2 #14 w/1 #16 or #18
1 #8 w/1 #10 Str	2 #10 w/1 to 3 #16 or #18	1 #16 w/2 to 6 #18