



STAINLESS STEEL BLACK #16-56

A special formulation containing 316L stainless steel pigment to provide maximum corrosion resistance and protection against weather, sunlight, oil, and water. Dries to a flat finish. Recommended as a topcoat, not a primer. Use of a primer is always beneficial to enhance adhesion and overall durability. Dries quickly and heat resistant up to 300°F.

Suggested Uses:

Protect metal
Paint metal structures
Touch up welds

Packaging:

UPC Code	043281011099
Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	limited quantity, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 15 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.83
Solids Content	~29%
MIR value	0.67, cannot exceed 0.80
HAPs content	3%
Storage Temperature	40-100F
Application Temperature	50-90F
Gasoline Resistance	Yes
Heat Resistance	300F
Resin System	Alkyd
Shelf life	Guaranteed for 2 years

Dry Time*:

To touch	10 minutes
To topcoat	15 minutes
To recoat	before 1 hour or After 24 hours

*At 72F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss*: <5*, flat
*as measured on a 60 degree gloss meter

Additional Information:

Not for use on internal engine parts.

Related Products:

Alumi Blast #CA16-55



or Cast Blast #CA16-48



12-4-2024