Safety Data Sheet

Date of issue: 01/19/2026 Revised On 01/19/2026

1 Identification of the substance and manufacturer

Trade name: **RED INSULATING VARNISH**
Other means of identification

Product code: 0006201525
Article category
Recommended use: Paint and coatings application.
Uses advised against: Any that differs from the recommended use.
Manufacturer/Supplier: Seymour of Sycamore
917 Crosby Avenue
Sycamore, IL 60178 USA
phone: 815-895-9101
www.seymourpaint.com

Seymour of Sycamore
3041 Dougall Avenue, Suite 503
Windsor, ONT N9E 1S3 CANADA
phone: 800-435-4482
www.seymourpaint.com

Emergency telephone number: 1-800-255-3924

2 Hazard(s) identification

Classification of the substance or mixture

Aerosols 1	H222-H229	Extremely flammable aerosol. Pressurized container: may burst if heated.
Skin irritation 2	H315	Causes skin irritation.
Reproductive toxicity 2	H361	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure) 3	H336	May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure) 2	H373	May cause damage to organs through prolonged or repeated exposure.

Additional information:
GHS Hazard pictograms



GHS02 GHS07 GHS08

Signal word Danger
Hazard statements
Extremely flammable aerosol. Pressurized container: may burst if heated.
Causes skin irritation.
Suspected of damaging fertility or the unborn child.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.

Precautionary statements
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Do not breathe dust/fume/gas/mist/vapors/spray.
Avoid breathing fume/mist/vapors/spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of water.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
Store in a well-ventilated place.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).
Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures
Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone	25-50%
74-98-6	propane	15-25%
106-97-8	n-butane	5-10%
108-88-3	Toluene	≥5-<10%
2807-30-9	Glycol Ether EP	1-5%
67-63-0	Isopropyl Alcohol	1-5%
1330-20-7	xylene (mix)	1-5%
107-87-9	Methyl Propyl Ketone	1-5%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 2)

Safety Data Sheet

Date of issue: 01/19/2026 Revised On 01/19/2026

Trade name: RED INSULATING VARNISH

(Contd. of page 1)

After swallowing: Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects: Dizziness
Indication of any immediate medical attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO_2, extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards: Can form explosive gas-air mixtures.
Protective equipment for firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures: Use respiratory protective device against the effects of fumes/dust/aerosol.
Methods and material for containment and cleaning up: Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling Use only in well ventilated areas.
Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone	
PEL (USA)	Long-term value: 2400 mg/m³, 1000 ppm
REL (USA)	Long-term value: 590 mg/m³, 250 ppm
TLV (USA)	Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm A4, BEI
74-98-6 propane	
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm
TLV (USA)	see Appendix F Minimal oxygen content (D, EX)
106-97-8 n-butane	
REL (USA)	Long-term value: 1900 mg/m³, 800 ppm
TLV (USA)	Short-term value: 2370 mg/m³, 1000 ppm (EX)
108-88-3 Toluene	
PEL (USA)	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm
TLV (USA)	Long-term value: 20 ppm BEI, OTO, A4
67-63-0 Isopropyl Alcohol	
PEL (USA)	Long-term value: 980 mg/m³, 400 ppm
REL (USA)	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm
TLV (USA)	Short-term value: 984 mg/m³, 400 ppm Long-term value: 491 mg/m³, 200 ppm BEI, A4
1330-20-7 xylene (mix)	
PEL (USA)	Long-term value: 435 mg/m³, 100 ppm
REL (USA)	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm
TLV (USA)	Long-term value: 20 ppm BEI, A4
107-87-9 Methyl Propyl Ketone	
PEL (USA)	Long-term value: 700 mg/m³, 200 ppm
REL (USA)	Long-term value: 530 mg/m³, 150 ppm
TLV (USA)	Short-term value: 529 mg/m³, 150 ppm

(Contd. on page 3)

Safety Data Sheet

Date of issue: 01/19/2026 Revised On 01/19/2026

Trade name: RED INSULATING VARNISH

(Contd. of page 2)

Ingredients with biological limit values:	
67-64-1 Acetone	
BEI (USA)	25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
108-88-3 Toluene	
BEI (USA)	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene 0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)
67-63-0 Isopropyl Alcohol	
BEI (USA)	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
1330-20-7 xylene (mix)	
BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids

Hygienic protection: Immediately remove all soiled and contaminated clothing.
Wash hands after use.
Store protective clothing separately.
Avoid contact with the eyes and skin.
Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection: Nitrile gloves.
The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Physical state	Aerosol
Odor:	Aromatic
Odor threshold:	Not determined.
Melting point/Melting range	Undetermined.
Boiling point:	-44 °C (-47.2 °F)
Flammability:	Extremely flammable.
Lower Explosion Limit:	1.7 Vol %
Upper Explosion Limit:	10.9 Vol %
Flash point:	-19 °C (-2.2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
pH-value:	Not determined.
Viscosity:	Not determined.
Solubility:	Not determined.
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapor density	Not determined.
Particle characteristics	Not applicable.
Appearance:	Aerosol.
Ignition temperature:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Evaporation rate	Not applicable.
Partition coefficient: n-octonal/water:	Not determined.

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.

Chemical stability: Not fully evaluated.

(Contd. on page 4)

Safety Data Sheet

Date of issue: 01/19/2026 Revised On 01/19/2026

Trade name: RED INSULATING VARNISH

(Contd. of page 3)

Possibility of hazardous reactions: No dangerous reactions known.
Incompatible materials: No further relevant information available.
Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

67-63-0 Isopropyl Alcohol		
Oral	LD50	4,570 mg/kg (rat)
Dermal	LD50	13,400 mg/kg (rab)
Inhalative	LC50/4 h	30 mg/l (rat)
1330-20-7 xylene (mix)		
Oral	LD50	8,700 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	6,350 mg/l (rat)

Information on toxicological effects: No data available.
Skin effects: No irritant effect.
Eye effects: Irritating effect.
Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.
Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.
Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents.
Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.
Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number UN1950
DOT UN1950
DOT Aerosols, flammable
ADR 1950 Aerosols
Transport hazard class(es):
Class 2.1 Gases
Special marking (IATA):
Packaging Group: --
Special precautions for user: Warning: Gases
EMS Number: F-D,S-U
UN "Model Regulation": UN 1950 AEROSOLS, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3	Toluene
67-63-0	Isopropyl Alcohol
1330-20-7	xylene (mix)

Toxic Substances Control Act (TSCA): All ingredients are found on the inventory list of substances.
Canadian Domestic Substances List (DSL): All ingredients are listed or exempted.
Consumer Product Safety Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

100-41-4	ethyl benzene
108-10-1	methyl isobutyl ketone

(Contd. on page 5)

Safety Data Sheet

Date of issue: 01/19/2026 Revised On 01/19/2026

Trade name: RED INSULATING VARNISH

(Contd. of page 4)

Prop 65 chemicals known to cause birth defects or reproductive harm:	
108-88-3	Toluene
108-10-1	methyl isobutyl ketone

EPA:		
67-64-1	Acetone	I
1330-20-7	xylene (mix)	I

16 Other information

Contact: Regulatory Affairs