



PBE PROFESSIONAL PRIMERS

A professional grade primer specifically formulated to meet the performance needs of body shop personnel. Sandable in 5 minutes, this primer adheres extremely well to bare metal surfaces. Very good protection against rust and corrosion. The large fan sprayhead eliminates the need for a spray gun on small repair jobs, and reduces your cleanup time.

Suggested Uses:

body panels
 engine parts
 metal structures
 aviation parts
 heavy machinery

Packaging:

Cans per case	6
Shipping weight per case	9 lbs.
Container	20 fluid ounce can
Label weight	15 ounces (425 grams)
Shipping Classification	limited quantity, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 18 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.78
Solids Content	17%
MIR value	0.60, cannot exceed 0.70
HAPs content	3%
Storage Temperature	40-100F
Application Temperature	50-90F
Topcoat	10 minutes
Gasoline Resistance	No
Heat Resistance	250F
Resin System	Nitrocellulose lacquer
Shelf life	Guaranteed for 2 years

Dry Time*:

To touch	5 minutes
Sandable	5 minutes

*At 72F, 50% humidity,
 1.5 mil thickness

**Curing/Recoat time is extended with
 multiple coats and excessively thick coats**

Gloss*: Flat, <15

*as measured on a 60 degree gloss meter

Available Colors:

Part #	Description	UPC Code
20-1671	Light Gray	043281002196
20-1672	Black	043281002202
20-1673	Red Iron Oxide	043281002219

12-9-2021