								+		Ø 1.4	2				
O-RING OPTIONAL ADD: R							4.8 approx.								
LOCK NUT OPTIONAL ADD: L 1/2 NPSM THREAD													EAVE		
ITEM NO.	PART NUMBER		DESCRIPTION	N MATERIAL		QTY.									
	RSPV-100-B		BODY VALOX			1									
2	SRB-105 - SRB-106		BUSHING NEOPRENE			1							RoHS		
3	SOR-1-VNT		O-RING	D-RING BUNA-N		1							COMPLIANT		
4	RSP-100-ND		NUT	VALOX		1			CATA	LOG N	UMBER	SEALING RANGE	BODY BORE		
5	LN-50		LOCK NUT	ADD: L, C.R.S. ZINC PL		TED 1			R	RSPV-105-E		.250312	.570		
6	R-106-D		MESH	STAINLESS WIRE		1			R	RSPV-106-E		.312375	.570		
REV.	DATE CHAN		NGE	IGE					NAME	DATE	_	REMK			
Α	7/29/13	DRAV	VING RELEAS	SED	TOLER.	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64		DRAWN CHECKED	JCN	7/13	] 310 CH	REMKE INDU Addick dr, whee	STRIES LING. IL 60090		
						ANGULAR: MACH ±1° BEND ±1° ONE PLACE DECIMAL ±.015		ENG APPR.			TITLE:		00000		
						TWO PLACE DECIMAL ±.010 THREE PLACE DECIMAL ±.005		MFG APPR.				RSPV-105-106-E SERIES			
						INTERPRET GEOMETRIC TOLERANCING PER:		Q.A.			-				
							ASTIC	PROPRIETARY AND CONFIDENTIAL			SIZE DWG. NO.				
					FINISH			DRAWING IS THE SOLE PROPERTY OF REMKE INDUSTRIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE			RSPV-105-106-E ASSEMBLY				
						) NOT SCA	LE DRAWING	WRITTEN PERMISSION OF REMKE INDUSTIRES IS PROHIBITED.			SCALE	: 1:1	SHEET 1 OF 1		
		5	Ť	4			3			2			1		