

Safety Data Sheet

Date of issue: 01/19/2026

Revised On 01/19/2026

1 Identification of the substance and manufacturer

| | |
|-------------------------------|---|
| Trade name: | TOOLMAKER'S BLUE LAYOUT INK |
| Other means of identification | |
| Product code: | 0006201558 |
| Article category | |
| Recommended use: | Paint and coatings application. |
| Uses advised against: | Any that differs from the recommended use. |
| Manufacturer/Supplier: | Seymour of Sycamore 917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com |
| Emergency telephone number: | Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482 www.seymourpaint.com |
| 1-800-255-3924 | |

2 Hazard(s) identification**Classification of the substance or mixture**

| | | |
|--|-----------|--|
| Aerosols 1 | H222-H229 | Extremely flammable aerosol. Pressurized container: may burst if heated. |
| Eye irritation 2A | H319 | Causes serious eye irritation. |
| Reproductive toxicity 2 | H361 | Suspected of damaging fertility or the unborn child. |
| Specific target organ toxicity (single exposure) 3 | H336 | May cause drowsiness or dizziness. |
| Specific target organ toxicity (repeated exposure) 2 | H373 | May cause damage to organs through prolonged or repeated exposure. |

Additional information:
GHS Hazard pictograms

GHS02 GHS07 GHS08

Signal word**Hazard statements**

Danger

Extremely flammable aerosol. Pressurized container: may burst if heated.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Avoid breathing fume/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Wear protective gloves/protective clothing/eye protection/face protection.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients**Chemical characterization: Mixtures**

This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

| | | |
|----------|---------------------|--------|
| 67-64-1 | Acetone | 25-50% |
| 74-98-6 | propane | 10-15% |
| 108-21-4 | isopropyl acetate | 10-15% |
| 106-97-8 | n-butane | 5-10% |
| 64-17-5 | ethyl alcohol | 5-10% |
| 108-88-3 | Toluene | 1-5% |
| 111-76-2 | Glycol Ether EB | 1-5% |
| 78-93-3 | methyl ethyl ketone | 1-5% |
| 67-63-0 | Isopropyl Alcohol | 1-5% |
| 67-56-1 | methanol | 0.2-1% |

4 First-aid measures**After inhalation:**

Supply fresh air; consult doctor in case of complaints.

(Contd. on page 2)

Safety Data Sheet

Date of issue: 01/19/2026

Revised On 01/19/2026

Trade name: TOOLMAKER'S BLUE LAYOUT INK

(Contd. of page 1)

| | |
|--|--|
| After skin contact: | Remove contaminated clothing. Wash exposed area with soap and water. |
| After eye contact: | Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. |
| After swallowing: | Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting. |
| Most important symptoms and effects: | Dizziness |
| Indication of any immediate medical attention needed: | No further relevant information available. |

5 Fire-fighting measures

| | |
|---|--|
| Extinguishing agents: | CO2, extinguishing powder or water spray. Fight larger fires with water spray. |
| Special hazards: | Can form explosive gas-air mixtures. |
| Protective equipment for firefighters: | A respiratory protective device may be necessary. |

6 Accidental release measures

| | |
|---|---|
| Personal precautions, protective equipment and emergency procedures: | Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol. |
| Methods and material for containment and cleaning up: | Ensure adequate ventilation. Dispose contaminated material as waste according to section 13. |

7 Handling and storage

| | |
|--------------------------------------|---|
| Precautions for safe handling | Use only in well ventilated areas. |
| Storage requirements: | Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up. |

8 Exposure controls/personal protection**Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**

| | |
|-----------|--|
| PEL (USA) | Long-term value: 2400 mg/m ³ , 1000 ppm |
| REL (USA) | Long-term value: 590 mg/m ³ , 250 ppm |
| TLV (USA) | Short-term value: 1187 mg/m ³ , 500 ppm |
| | Long-term value: 594 mg/m ³ , 250 ppm |

A4, BEI**74-98-6 propane**

| | |
|-----------|--|
| PEL (USA) | Long-term value: 1800 mg/m ³ , 1000 ppm |
| REL (USA) | Long-term value: 1800 mg/m ³ , 1000 ppm |
| TLV (USA) | see Appendix F Minimal oxygen content (D, EX) |

108-21-4 isopropyl acetate

| | |
|-----------|---|
| PEL (USA) | Long-term value: 950 mg/m ³ , 250 ppm |
| TLV (USA) | Short-term value: 626 mg/m ³ , 150 ppm |
| | Long-term value: 417 mg/m ³ , 100 ppm |

106-97-8 n-butane

| | |
|-----------|--|
| REL (USA) | Long-term value: 1900 mg/m ³ , 800 ppm |
| TLV (USA) | Short-term value: 2370 mg/m ³ , 1000 ppm (EX) |

64-17-5 ethyl alcohol

| | |
|-----------|--|
| PEL (USA) | Long-term value: 1900 mg/m ³ , 1000 ppm |
| REL (USA) | Long-term value: 1900 mg/m ³ , 1000 ppm |
| TLV (USA) | Short-term value: 1880 mg/m ³ , 1000 ppm A3 |

108-88-3 Toluene

| | |
|-----------|---|
| PEL (USA) | Long-term value: 200 ppm |
| | Ceiling limit value: 300; 500* ppm |
| | *10-min peak per 8-hr shift |
| REL (USA) | Short-term value: 560 mg/m ³ , 150 ppm |
| TLV (USA) | Long-term value: 375 mg/m ³ , 100 ppm |
| | Long-term value: 20 ppm |
| | BEI, OTO, A4 |

111-76-2 Glycol Ether EB

| | |
|-----------|---|
| PEL (USA) | Long-term value: 240 mg/m ³ , 50 ppm |
| | Skin |

(Contd. on page 3)

Safety Data Sheet

Date of issue: 01/19/2026

Revised On 01/19/2026

Trade name: TOOLMAKER'S BLUE LAYOUT INK

(Contd. of page 2)

| | |
|--|--|
| REL (USA) | Long-term value: 24 mg/m ³ , 5 ppm Skin |
| TLV (USA) | Long-term value: 97 mg/m ³ , 20 ppm BEI, A3 |
| 78-93-3 methyl ethyl ketone | |
| PEL (USA) | Long-term value: 590 mg/m ³ , 200 ppm |
| REL (USA) | Short-term value: 885 mg/m ³ , 300 ppm |
| | Long-term value: 590 mg/m ³ , 200 ppm |
| TLV (USA) | Short-term value: 150 ppm Long-term value: 75 ppm BEI, Skin |
| 67-63-0 Isopropyl Alcohol | |
| PEL (USA) | Long-term value: 980 mg/m ³ , 400 ppm |
| REL (USA) | Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm |
| TLV (USA) | Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 491 mg/m ³ , 200 ppm BEI, A4 |
| 67-56-1 methanol | |
| PEL (USA) | Long-term value: 260 mg/m ³ , 200 ppm |
| REL (USA) | Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin |
| TLV (USA) | Short-term value: 328 mg/m ³ , 250 ppm Long-term value: 262 mg/m ³ , 200 ppm Skin; BEI |
| Ingredients with biological limit values: | |
| 67-64-1 Acetone | |
| BEI (USA) | 25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific) |
| 108-88-3 Toluene | |
| BEI (USA) | 0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene |
| | 0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene |
| | 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background) |
| 111-76-2 Glycol Ether EB | |
| BEI (USA) | 200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis) |
| 78-93-3 methyl ethyl ketone | |
| BEI (USA) | 2 mg/L Medium: urine Time: end of shift Parameter: Methyl ethyl ketone (nonspecific) |
| 67-63-0 Isopropyl Alcohol | |
| BEI (USA) | 40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific) |
| 67-56-1 methanol | |
| BEI (USA) | 15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific) |

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use. Store protective clothing separately. Avoid contact with the eyes and skin. Do not eat or drink while working.

(Contd. on page 4)

Safety Data Sheet

Date of issue: 01/19/2026

Revised On 01/19/2026

Trade name: TOOLMAKER'S BLUE LAYOUT INK

(Contd. of page 3)

| | |
|-----------------------------|--|
| Breathing equipment: | A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene. |
| Hand protection: | Nitrile gloves. |
| Eye protection: | The glove material must be impermeable and resistant to the substance. Tightly sealed goggles |

9 Physical and chemical properties

| | |
|--|--|
| Physical state | Aerosol |
| Odor: | Aromatic |
| Odor threshold: | Not determined. |
| Melting point/Melting range | Undetermined. |
| Boiling point: | -44 °C (-47.2 °F) |
| Flammability: | Extremely flammable. |
| Lower Explosion Limit: | 1.7 Vol % |
| Upper Explosion Limit: | 10.9 Vol % |
| Flash point: | -19 °C (-2.2 °F) |
| Flammability (solid, gas): | Extremely flammable. |
| Decomposition temperature: | Not determined. |
| pH-value: | Not determined. |
| Viscosity: | Not determined. |
| Solubility: | Not determined. |
| Vapor pressure: | Not determined. |
| Relative Density: | Between 0.77 and 0.85 (Water equals 1.00) |
| Vapor density | Not determined. |
| Particle characteristics | Not applicable. |
| Appearance: | Aerosol. |
| Ignition temperature: | Product is not self-igniting. |
| Danger of explosion: | In use, may form flammable/explosive vapour-air mixture. |
| Evaporation rate | Not applicable. |
| Partition coefficient: n-octanol/water: | Not determined. |

10 Stability and reactivity

| | |
|--|--|
| Reactivity: | Stable at normal temperatures. |
| Conditions to avoid: | Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures. |
| Chemical stability: | Not fully evaluated. |
| Possibility of hazardous reactions: | No dangerous reactions known. |
| Incompatible materials: | No further relevant information available. |
| Hazardous decomposition: | No dangerous decomposition products known. |

11 Toxicological information**LD/LC50 values that are relevant for classification:****108-21-4 isopropyl acetate**

| | | |
|------|------|-------------------|
| Oral | LD50 | 9,800 mg/kg (rat) |
|------|------|-------------------|

64-17-5 ethyl alcohol

| | | |
|------------|----------|-------------------|
| Oral | LD50 | 7,060 mg/kg (rat) |
| Inhalative | LC50/4 h | 20,000 mg/l (rat) |

111-76-2 Glycol Ether EB

| | | |
|------------|----------|--|
| Oral | LD50 | 1,200 mg/kg (ATE) 1,480 mg/kg (rat) |
| Dermal | LD50 | 400 mg/kg (rab) |
| Inhalative | LC50/4 h | 3 mg/l (ATE) |

78-93-3 methyl ethyl ketone

| | | |
|--------|------|----------------------|
| Oral | LD50 | 3,300 mg/kg (rat) |
| Dermal | LD50 | 5,000 mg/kg (rabbit) |

67-63-0 Isopropyl Alcohol

| | | |
|------------|----------|--------------------|
| Oral | LD50 | 4,570 mg/kg (rat) |
| Dermal | LD50 | 13,400 mg/kg (rab) |
| Inhalative | LC50/4 h | 30 mg/l (rat) |

67-56-1 methanol

| | | |
|--------|------|-----------------------|
| Oral | LD50 | 5,628 mg/kg (rat) |
| Dermal | LD50 | 15,800 mg/kg (rabbit) |

Information on toxicological effects: No data available.**Skin effects:** No irritant effect.**Eye effects:** Irritating effect.

(Contd. on page 5)

Safety Data Sheet

Date of issue: 01/19/2026

Revised On 01/19/2026

Trade name: TOOLMAKER'S BLUE LAYOUT INK

(Contd. of page 4)

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.
Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.
Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents.

Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.
Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

| | |
|-------------------------------|-----------------------|
| UN-Number | UN1950 |
| DOT | UN1950 |
| DOT | Aerosols, flammable |
| ADR | 1950 Aerosols |
| Transport hazard class(es): | |
| Class | 2.1 Gases |
| Marine pollutant: | No |
| Special marking (IATA): | |
| Packaging Group: | -- |
| Special precautions for user: | Warning: Gases |
| EMS Number: | F-D,S-U |
| UN "Model Regulation": | UN 1950 AEROSOLS, 2.1 |

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

| | |
|----------|-------------------|
| 108-88-3 | Toluene |
| 111-76-2 | Glycol Ether EB |
| 67-63-0 | Isopropyl Alcohol |

Toxic Substances Control Act

(TSCA): All ingredients are found on the inventory list of substances.

Canadian Domestic Substances List

(DSL): All ingredients are listed or exempted.

Consumer Product Safety Commission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

| | |
|----------|------------------------|
| 100-41-4 | ethyl benzene |
| 108-10-1 | methyl isobutyl ketone |

Prop 65 chemicals known to cause birth defects or reproductive harm:

| | |
|----------|------------------------|
| 108-88-3 | Toluene |
| 67-56-1 | methanol |
| 108-10-1 | methyl isobutyl ketone |

EPA:

| | | |
|----------|---------------------|----|
| 67-64-1 | Acetone | I |
| 111-76-2 | Glycol Ether EB | NL |
| 78-93-3 | methyl ethyl ketone | I |

16 Other information

Contact: Regulatory Affairs