



PRESSURE CLEANERS



Made in Australia
SINCE 1982

HP3523AE

Cold Water Cleaner



Specifications

- ⇒ 350 bar (5076 psi) pump pressure
- ⇒ 435 bar (6309 psi) EWP pressure (optional)
- ⇒ 23 Litres Per Minute pump volume
- ⇒ GX690 Honda petrol engine
- ⇒ 1450 rpm low speed pump
- ⇒ Electric start
- ⇒ Heavy duty machine

Standard Equipment

- ⇒ Interpump brass head pump
- ⇒ 10 Metre high pressure hose
- ⇒ RL56 Gun with S3 Lance, fixed nozzle & protector
- ⇒ VB350 Unloader valve & VS350 Safety Valve
- ⇒ Water cooling tank
- ⇒ Operating and Maintenance manual

Features	Benefits
Interpump with ceramic pistons and brass head	Non-corrosive pump head to extend pump life and reduce maintenance costs
Oz-tuff belt drive	15% more power available than a gearbox and no more gearbox oil leaks (maintenance free)
Water cooling tank	Protects the pump in bypass, when pistol trigger is closed
Inlet water filter	Stops debris from scoring pistons and seals
Pressure gauge	Easily monitor pump performance
3 Stage powder coated zinc annealed chassis and frame with lifting hook and 4 pneumatic wheels	Resistant to corrosion and greater manoeuvrability over tough terrain

For more information,
please visit our website

spitwater.com.au

TOUGH + READY

CREATED BY **OTTICO**