



REMOVABLE CAP
TO TIGHTEN SCREW
(REPLACE WHEN COMPLETE)



5/16 INTERNAL HEX
PRESSURE SCREW



WIRE ENTRY POINT
WIRE RANGE: 350MCM - #10AWG
PRE-FILLED W/ OXIDE INHIBITOR

IPL350-3 SHOWN

PART NUMBER	NO. OF PORTS	LENGTH
IPL350-3	3	3.52
IPL350-4	4	4.57
IPL350-5	5	5.62
IPL350-6	6	6.67
IPL350-8	8	8.77
IPL350-10	10	10.87
IPL350-11	11	11.92
IPL350-12	12	12.97
IPL350-14	14	15.07
IPL350-16	16	17.17
IPL350-18	18	19.27

CONTACT NSi FOR SALES @ 800.321.5847



POLARIS
SALES . CO . INC

PROPRIETARY AND CONFIDENTIAL

11625 PROSPEROUS DRIVE ODESSA, FL 33556

THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
POLARIS SALES CO. INC. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
POLARIS SALES CO. INC. IS PROHIBITED.

TITLE:

INSULATED
350 CONNECTOR

NAME	REVISED
L. HILL	4/17/2024

DWG. NO.

IPL350-SERIES

MATERIAL: N/A

SCALE: 1:2

SHEET: 1 OF 1

NOTES:

- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
- UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
- DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.
- COLD TEMPERATURE RATED TO -45°C.
- HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION, CHEMICAL AND UV RESISTANT.