


Removable Polyethylene Film Tape



Backing:	LDPE Film
Adhesive:	Acrylic (A200)
Liner:	N/A
Colors:	Clear
Specifications:	N/A
Size Options:	Incremental widths 1/4" - 46" x 108ft

Applications

- Protective masking on plastics and metals during shipping and assembly - saves money by reducing damage to delicate surfaces!
- Surface protection
- Label overlaminates

Features

- LDPE Film
- Acrylic Adhesive

Benefits

- Highly conformable
- Abrasion and moisture resistant
- Solvent resistant
- Good all temperature performance
- Removes cleanly from most surfaces
- Easy to apply

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	4.5 mils	0.114 mm	PSTC-133
Substrate Thickness	3.5 mils	0.089 mm	PSTC-133
Adhesion to Steel	12 oz/in	1.31 N/cm	ASTM D-3330
Tensile Strength	10 lb/in	17.51 N/cm	ASTM D-3759
Elongation	400%		
Application Temperature	50 to 120 °F	10 to 49 °C	
Operating Temperature	-40 to 190 °F	-40 to 88 °C	

Recommended Storage Conditions: 40-60% Humidity, 60 - 80 °F
Standard Shelf Life (at 25 °C): 12 months from shipment date

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY GLOBAL'S knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.