



Limited Lifetime Warranty

Commercial Grade Chainlink Hog Ring Pliers & Staples



Commercial grade Hog Ring Pliers with Magazine installs 9-Ga. (3.8 mm) collated aluminum rings or exclusive 9-Ga. (3.8 mm) collated steel rings.
Easily secures 7-Ga. (4.5 mm) wire to 9-Ga. (3.8 mm) chain link fence.

Designed to address the most stringent regulatory codes, this commercial grade hog ring pliers ensures uninterrupted operation to quickly install extra secure Malco 9 Ga. (3.8 mm) collated aluminum rings or exclusive 9 Ga. (3.8 mm) collated steel rings anywhere along a chainlink fence. Long handles save time and effort with plenty of leverage and reach. The 25-count strips of collated rings can be loaded into the pliers' symmetrical magazine from either direction. A plunger feed automatically sets up each ring. There is no need to manually rotate the magazine out of the way as the pliers' clinching mechanism brings the ring forward of the nose for easy access to tension wire and fence. The magazine easily folds down for safe and easy storage of tool.



- Easy loading, auto-feed magazine.
- Long handles for extra leverage and reach.
- Easy access to tension wire and fence.
- Use with HRA5 Aluminum Rings or HRS5 Steel Rings.



HRA5 EV

Aluminum Hog Rings, 9-ga. (3.8 mm)
Lightweight for Fast Installation

- Unique overlap clinch is twice as strong as closest alternative.
- 6061-T94 or 5052-H38 Alloy.
- 25-piece loading strips with no sharp points are safe and easy to load.
- One 500 pack secures 1000 feet (305 m) of tension wire spaced at 24 in. (61 cm) intervals.



Collapsible Magazine for Easy Storage!



Easy to Load and Lock!



HRS5 EV

Galvanized Steel Hog Rings, 9-ga. (3.8 mm)
Strong and Weather Resistant!

- Unique overlap clinch is twice as strong as closest alternative.
- Class 3 Coating Per ASTM A641.
- 25-piece loading strips with no sharp points are safe and easy to load.
- The only collated 9-Ga. steel hog rings on the market.
- One 500 pack secures 1000 feet (305 m) of tension wire spaced at 24 in. (61 cm) intervals.

Catalog Number	Description	Hog Ring Usage	Length in. (mm)	Weight lbs. (oz.)	For Tools	Material	Qty.	Crown in. (mm)	Opening in. (mm)	Inside Dia. in (mm)	Thickness Gauge (mm)
HRP5	Hog Ring Pliers w / Mag.	HRA5 / HRS5	20 (508)	2.9 (1.32)	—	—	—	—	—	—	—
HRS5 EV	Hog Ring Staples				HRP5	Galvanized Steel	500	1-7/16 (37)	5/8 (16)	7/16 (11)	9 (3.8)
HRA5 EV	Hog Ring Staples				HRP5	Aluminum Alloy	500	1-7/16 (37)	5/8 (16)	7/16 (11)	9 (3.8)
HRP5RP	Replacement Plunger / Spring Assembly				HRP5	—	—	—	—	—	—