

INSTALLATION INSTRUCTIONS FOR PPA15 POWER PLUG ADAPTER

WARNING - Always turn off power before attaching the PPA15 power plug adapter to the disconnect box. Only use this device on disconnect boxes equipped with both neutral and ground wires.

Setup instructions

1. Turn off breaker that supplies power to the disconnect box.
2. Open lid and remove the disconnect.
3. Insert the banana jack from black wire into the PPA15.

Note: You can use either the Blade or the Alligator clamp black wire assembly.

Insert Blade into the line side of the disconnect slot. The left or right side will work.

You can also use the alligator clip if the blade doesn't fit. Attach the Alligator Clip to the line side power lug / screw-down terminal.

4. Attach the magnetic side of PPA15 to the side of the disconnect box to keep the PPA15 connected during use.
5. Insert the blade or attach the alligator clip.
6. Connect the ground wire (Green) alligator clip to ground.
7. Connect the (White) alligator clip to neutral.
8. Turn breaker on and you are ready to use the PPA15 power plug adapter.

Note: The overload will pop if the amperage exceeds 15A. If the overload pops, turn off the tool in use before resetting the overload. Then turn the tool back on.

IF THE AMPERAGE EXCEEDS 15A AND THE OVERLOAD KEEPS POPPING, STOP USING THIS DEVICE. IT IS NOT RECOMMENDED TO FOR USE IF AMPERAGE IS EXCEEDED.

PPA15 should not be used as a permanent power plug. Always disconnect power before removing PPA15.



Disconnect power before servicing equipment.



800.333.9125 - techsupport@supco.com - www.supco.com