

FEATURES:**FQC Series**

- Nickel plated.
- 0.250 x 0.30 tab size.
- 22-14AWG wire size.

DR Series

- Made from 35mm unplated 6061-T6 Aluminum alloy providing for a strong, lightweight rail for mounting sockets, terminal blocks or other electro-mechanical devices.
- Comes supplied with oval holes 1.1 cm, approximately x 0.4 cm apart.
- Standard 10mm height allows for ease of installation vs. traditional 7.5mm height.

POLARIS®

PROGRAM:	SOLIDWORKS
UPDATED:	09/2024
SALES REV:	A
SIZE:	B (11x17)

HARDWARE OPTIONS: FQC, DR SERIES

CAT. NO.	FIG. NO.	DESCRIPTION	HEIGHT	LENGTH	STD. CTN. QTY.
FQC-00	1	Quick Disconnect – 0° Flat	–	–	10
FQC-45	2	Quick Disconnect – 45° Bend	–	–	10
FQC-90	3	Quick Disconnect – 90° Bend	–	–	10
J-30	4	30 AMP Jumper	–	–	10
DR3910	5	For Mounting Sockets, Terminal Blocks, Or Other Electro-Mechanical Devices	10 mm	39.3"	10

SPECIFICATIONS:**FQC Series**

- Voltage: 30AMP., 600V Max.

DR Series

- CSA.
- UL Recognize.