



WC-G | Grey Wire Connectors

Temperature Rating: 105° C (221° F) Max.

Voltage Rating: 300V Max.

FOR UL LISTED, CSA AND CQC CERTIFIED

1 #14	1 #16 w/1 or 2 #20	2 #18 w/1 #20 w/1 #22
1 or 2 #16	1 #16 w/1 to 3 #22	2 #18 w/1 #20
1 to 3 #18	1 #16 w/1 #18 w/1 #20	2 #18 w/1 or 2 #22
2 to 4 #20	1 #16 w/1 #18 w/1 #22	1 #20 w/1 to 4 #22
2 to 4 #22	1 #18 w/1 to 3 #20	2 #20 w/1 to 3 #22
1 #14 w/1 #20 or #22	1 #18 w/1 to 4 #22	3 #20 w/1 or 2 #22
1 #16 w/1 #18	1 #18 w/1 #20 w/1 #22	



WC-B | Blue Wire Connectors

Temperature Rating: 105° C (221° F) Max.

Voltage Rating: 300V Max.

FOR UL LISTED, CSA AND CQC CERTIFIED

1 #14	1 #16 w/1 to 3 #18	1 #18 w/1 to 4 #20 or #22
1 to 3 #16	1 #16 w/1 #18 w/1 #20	1 or 2 #18 w/1 #20 w/1 #22
1 to 4 #18	1 #16 w/1 to 4 #20 or #22	2 #18 w/1 to 3 #20 or #22
3 to 5 #20	1 #16 w/1 #22 w/1 #18 or #20	3 #18 w/1 or 2 #20 or #22
2 #22	2 #16 w/1 #18	4 #18 w/1 #22
1 #14 w/1 #16	2 #16 w/1 or 2 #20	3 #20 w/1 or 2 #22
1 #14 w/1 or 2 #18	2 #16 w/1 #20 w/1 #22	4 #20 w/1 #22
1 #14 w/1 to 3 #20 or #22	2 #16 w/1 to 3 #22	



WC-O | Orange Wire Connectors

Temperature Rating: 105° C (221° F) Max.

Voltage Rating: 600V Max. Building wiring; 1000V Max. Fixtures and Signs

FOR UL LISTED, CSA AND CQC CERTIFIED

Voltage Rating: 600V Max.

1 or 2 #14	1 #16 w/1 or 2 #18	1 #18 w/2 to 4 #20
2 or 3 #16	1 #16 w/1 #18 w/1 #22	1 #18 w/3 or 4 #22
2 to 4 #18	1 #16 w/1 to 3 #20 or #22	1 or 2 #18 w/1 #20 w/1 #22
1 #14 w/1 #16	1 or 2 #16 w/1 #20 w/1 #22	2 #18 w/1 or 2 #20 or #22
1 #14 w/1 #16 w/1 #18	2 #16 w/1 #18	3 #18 w/1 #20 or #22
1 #14 w/1 or 2 #18	2 #16 w/1 or 2 #20	
1 #14 w/1 to 3 #20 or #22	2 #16 w/1 to 3 #22	

Voltage Rating: 300V Max.

4 #16	1 #14 w/4 #20	1 #18 w/1 #20
5 #18	2 #14 w/1 #18	1 #18 w/5 #22
3 to 5 #20	2 #14 w/1 to 3 #20 or #22	2 #18 w/3 #22
5 #22 Sol	1 #16 w/4 #18	3 #18 w/2 #20 or #22
5 #22 Str	2 #16 w/2 or 3 #18	4 #18 w/1 #20 or #22
3 #22 Sol w/2 #22 Str	2 #16 w/3 #20	1 #20 w/4 #22
1 #14 w/1 #16 w/1 #18	3 #16 w/1 #18	2 #20 w/2 or 3 #22
1 #14 w/2 #16	3 #16 w/1 or 2 #20 or #22	3 #20 w/1 or 2 #22
1 #14 w/3 #18	4 #16 w/1 #20 or #22	4 #20 w/1 #22



WC-R | Red Wire Connectors

Temperature Rating: 105° C (221° F) Max.

Voltage Rating: 600V Max. Building wiring; 1000V Max. Fixtures and Signs

FOR UL LISTED AND CQC CERTIFIED

Voltage Rating: 600V Max.

- 2 #10 Sol
- 2 to 4 #12
- 2 to 6 #14
- 3 to 9 #18
- 1 #10 Sol w/1 #10 Str
- 1 #10 w/1 to 3 #12 or #14
- 2 #10 w/1 to 3 #16 or #18
- 2 #10 Sol w/2 #12 Sol
- 2 #10 Sol w/2 #12 Str
- 2 #10w/1 or 2 #14
- 1 #12 w/1 to 5 #14
- 1 #12 w/1 to 4 #16 or #18
- 1 #12 w/1 #20
- 2 #12 w/1 to 4 #14
- 2 #12 w/1 to 3 #16 or #18
- 3 #12 w/1 or 2 #16 or #18

- 3 #12 w/2 or 3 #14
- 4#12w/1 #14, #16 or #18
- 2 #14 w/1 to 4 #16 or #18
- 3 #14 w/1 to 3 #16 or #18
- 4# 14 w/1 or 2 #16
- 4 #14 w/1 to 3 #18
- 5 #14 w/1 #16 or #18

Voltage Rating: 300V Max.

- 1 #10
- 4 to 6 #16
- 1 #10 w/1 #12 w/3 or 4 #18
- 1 #10 w/1 #14 w/4 #18
- 1 #10 w/1 #14 w/1 to 4 #20
- 1 #10 w/1 #14 w/1 to 4 #22
- 1 #10 w/1 or 2 #20 w/1 to 4 #22
- 1 #12 w/2 #14 w/3 #16
- 1 #12 w/1 #16 w/1 to 4 #20
- 1 #12 w/1 #16 w/1 to 4 #22
- 1 #12 w/1 #16 w/1 to 4 #20
- 1 #12 w/1 #16 w/1 to 4 #22
- 1 #12 w/1 to 4 #20
- 2 #12 w/1 #14 w/2 or 3 #16
- 2 #12 w/2 #14 w/1 #16
- 2 #12 w/1 #16 w/4 #18
- 2 #12 w/6 #16
- 3 #12 w/1 #14
- 3 #12 w/1 #16 w/1 #20
- 1 #14 w/1 #18 w/4 #22

- 2 #14 w/1 #16 w/1 to 4 #20
- 2 #14 w/1 #16 w/1 to 4 #22
- 3 #14 w/1 #16 w/1 to 3 #18
- 1 #16 w/4 #18
- 2 #16 w/3 or 4 #18
- 3 #16 w/1 or 2 #20 w/1 to 3 #22
- 4 #16 w/1 #18 or #20
- 4, 5 or 6 #16 w/1 #22
- 4 or 5 #16 w/2 #22

FOR CSA CERTIFIED

Voltage Rating: 600V Max.

- 2 to 4 #12
- 2 to 6 #14
- 3 to 9 #18
- 1 #10 w/1 to 2 #12
- 1 #10 w/1 to 4 #14
- 1 #12 w/1 to 5 #14
- 1 #12 w/2 to 4 #16 or #18
- 2 #12 w/1 to 4 #14
- 2 #12 w/1 to 3 #16 or #18
- 3 #12 w/2 #14
- 3 #12 w/1 or 2 #16 or #18
- 4 #12 w/1 #16

- 2 #14 w/1 to 4 #16 or #18
- 3 #14 w/1 to 3 #16 or #18
- 4 #14 w/1 or 2 #16 or #18
- 5 #14 w/1 #16 or #18



WC-Y | Yellow Wire Connectors

Temperature Rating: 105° C (221° F) Max.

Voltage Rating: 600V Max. Building wiring; 1000V Max. Fixtures and Signs

FOR UL LISTED

- 1 #8
- 1 #10
- 1 to 3 #12
- 1 to 4 #14
- 2 to 5 #16
- 2 to 7 #18
- 3 to 6 #20
- 1 #10 w/1 or 2 #12, #14, #16 or #18
- 1 #10 w/3 or 4 #16 or #18
- 1 #10 w/1 #12 w/1 #14 or #16
- 1 #10 w/1 #12 w/1 or 2 #18
- 1 #10 w/1 #14 w/2 #16
- 1 #10 w/1 #14 w/1 to 3 #18
- 1 #10 w/2 #14w/1 #16
- 1 #10 w/1 #16 w/1 or 2 #18
- 1 #12 w/1 to 3 #14, #16 or #18
- 1 #12 w/1 to 4 #16 or #18
- 1 #12 w/1 #14 w/3 #16
- 1 #12 w/2 #14 w/2 #16
- 2 #12 w/1 or 2 #14, #16 or #18
- 2 #12 w/1 #14 w/1 #16 or #18
- 2 #12 w/1 #16 w/1 or 2 #18
- 1 #14 w/1 to 4 #16, #18 or #20
- 1 #14 w/1 #16 w/1 to 3 #20
- 1 #14 w/1 #18 w/1 to 3 #20
- 2 #14 w/1 to 3 #16, #18 or #20
- 2 #14 w/1 #16 w/1 or 2 #18 or #20
- 2 #14 w/1 #16 w/1 to 3 #22
- 3 #14 w/1 #16 w/1 #18, #20 or #22
- 3 #14 w/1 #18 w/1 #20 or #22

- 3 #14 w/1 or 2 #16, #18, #20 or #22
- 4 #14w/1 #16 or #18
- 1 #16 w/1 to 4 #18, #20 or #22
- 1 #16 w/1 #18 w/2 to 4 #20 or #22
- 1 #16 w/2 #20 w/2 #22
- 2 #16 w/1 to 3 #18, #20 or #22
- 2 #16 w/1 #18 w/1 or 2 #20 or #22
- 3 #16 w/1 or 2 #18, #20 or #22
- 3 #16 w/1 #18 w/1 #20 or #22
- 4 #16 w/1 or 2 #18, #20 or #22
- 1 #18 w/3 or 4 #20 or #22
- 1 #18 w/2 #20 w/3 #22
- 2 #18 w/3 #20 or #22
- 2 #18 w/1 #20 w/3 #22





WC-HB1 | Black Wire Connectors

Temperature Rating: 150° C (302° F) Max.

Voltage Rating: 300V Max.

FOR UL LISTED, CSA AND CQC CERTIFIED

- 2 #18 Str
- 1 #18 Str w/1 #20 Str
- 1 #18 Str w/1 #22 Str



WC-HB3 | Black Wire Connectors

Temperature Rating: 150° C (302° F) Max.

Voltage Rating: 600V Max. Building wiring; 1000V Max. Fixtures and Signs

FOR UL LISTED, CSA AND CQC CERTIFIED

- | | | |
|--|----------------------------|----------------------------|
| 1 or 2#14 | 1 #16 w/1 or 2 #18 | 1 #18 w/2 or 4 #20 |
| 2 #16 | 1 #16 w/1 #18 w/1 #22 | 1 or 2 #18 w/1 #20 w/1 #22 |
| 2 to 4 #18 | 1 #16 w/1 to 3 #20 or #22 | 1 #18 w/3 or 4 #22 |
| 1 #14 w/1 #16 | 1 or 2 #16 w/1 #20 w/1 #22 | 2 #18 w/1 or 2 #20 or #22 |
| 1 #14 w/1 #16 w/1 #18 1 #14 w/1 or 2 #18 | 2 #16 w/1 #18 | 3 #18 w/1 #20 or #22 |
| 1 #14 w/1 to 3 #20 | 2 #16 w/1 or 2 #20 | |
| 1 #14 w/1 to 3 #22 | 2 #16 w/1 to 3 #22 | |