


- FEATURES:**
- 1. Material: Tin Plated CU
 - 2. UL listed for U.S. & Canada.
 - 3. Wire connector rated for 35Kv max.
 - 4. Class B/C compressed, concentric, and compact copper conductor only.
 - 5. Expanded wire range when installed with dieless NSi compression tool (N12ID).
 - 6. Dimensions are for reference only, tolerance is +/- .06".


L Series: L4014

POLARIS®

PROGRAM:	SOLIDWORKS
UPDATED:	4/2022
SALES REV:	A
SIZE:	B (11x17)



SCALE 2:1



<div><div></div><div>+</div></div>			COPPER COMPRESSION CONNECTOR TOOL AND DIE CHART (# OF CRIMPS)										
			NSI				GREENLEE		ILSCO	BURNDY	T&B	HUSKIE	
WIRE SIZE	STRIP LENGTH	DIE COLOR	EXPANDED WIRE RANGE W/N12ID	N1240 SERIES	NSI-12	NSI-12	1240 SERIES		ILC-12/ILC-15 SERIES	Y-35. Y750, PAT 750	TBM-15, TBM-14M	EP510C	
4/0AWG	1-1/2"	PURPLE	4/0AWG-#1AWG	KC12-4/0 (2)	CD12 (4)	HT41BC (4)	KC12-4/0 (2)	ILD-10 (4)	KC12-4/0 (2)	U28RT (4)	15511 (4)	HT41BC (4)	CD12 (4)

