



Toll Free: 87 PERMATEX
(877-376-2839)

10 Columbus Blvd., Hartford,
Connecticut 06106

6875 Parkland Boulevard, Solon
Ohio 44139

Technical Data Sheet

Permatex® All-Purpose Spray Adhesive

AAM Revised 11/15

PRODUCT DESCRIPTION

Permatex® Spray Adhesive is an all-purpose, pressure sensitive, spray adhesive that allows both permanent and repositionable bonding.

PRODUCT BENEFITS

- Fast tack
- Resists water and humidity
- Repositionable or permanent bond
- Adheres to both porous and non-porous materials
- Won't bleed through - surfaces remain unstained
- Safe on all surfaces - non-aggressive solvents
- VOC compliant
- Will not shrink


TYPICAL APPLICATIONS

Bonds the following substrates:

- Paper
- Fabric
- Leather
- Cardboard
- Polystyrene foam
- Foam rubber
- Foil
- Metal
- Most plastics
- Rubber
- Felt
- Cork
- Glass
- Wood

DIRECTIONS FOR USE

1. Provide adequate ventilation.
2. Surfaces should be free of oil, dirt and grease.
3. Mask areas that should not be coated.
4. Shake can well. Note: The product does not require a ball agitator. For best results, the aerosol can should be at room temperature before spraying.
5. **For a repositionable bond**, apply a uniform coat to one surface. After a few seconds, press sprayed item to surface. To reposition sprayed item, start at a corner and peel back. Allow one minute to dry.
6. **For a permanent bond**, apply a medium coat to both surfaces. Allow to dry one minute before bonding together. For more porous surfaces, bond them while they are slightly wet. Allow one minute to dry.



Note: For headliners use **Heavy Duty Spray Adhesive**. Aerosol product will cover (2 coats) ~ 16 square feet.

For Cleanup

1. Turn can upside-down and spray to clear nozzle.
2. Clean hands with Permatex® brand hand cleaners.

PROPERTIES OF MATERIAL

	Typical Value
Chemical Type	Rubber
Appearance	Clear liquid
Odor	Solvent
Flash Point	Aerosol, contents under pressure, consult MSDS
NFPA 704 Flammability Rating	4 (Highly flammable)

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as an adhesive for chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

ORDERING INFORMATION

Part Number	Container Size
82019 (118DA)	16 oz. aerosol can

STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8° to 28°C (46° to 82°F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range.

NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.
THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.
PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.
PERMATEX, INC., HARTFORD SQUARE NORTH, 10 COLUMBUS BOULEVARD, HARTFORD, CT 06106 PHONE - (1-87PERMATEX)