		1.45		2.04 AF	PROX.				Ø 1				COMPLIANT
	3/4 N.P.	.T. THREAD-			LOCK NUT OPTIONAL ADD: L				R	PART NUMBE SP-920	ER D3	SEALING RANGE .125188 .188250	BODY BORE .765 .765
ITEM	PAR	RT NUMBER	DESCRIPTION	Г	DESCRIPTION	QTY				SP-920		.188230	.765
NO.								R	RSP-9206		.312375	.765	
1	RSP-9200-B		BODY		NYLON 6/6	1			R	SP-920	)7	.375437	.765
2	SRB-203	THRU SRB-213	BUSHING		NEOPRENE	1			R	SP-920	28	.438500	.765
3	RSP-200	-WB	WASHER		NYLON 6/6	1				SP-92		.500562	.765
4	RSP-200	-N	NUT		NYLON 6/6	1			RSP-9210			.500625	.765
5	SOR-2		O-RING		BUNA-N	1				SP-92 SP-92		.562688	.765
	LN-75		LOCK NUT	ADD: L,	_	D 1	_			SP-92		.688812	.765
EV.	V. DATE CHANGE				UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES			NAME	DATE			REMK	E
A 5	5/30/13	DRAWING RE	LEASED		TOLERANCES: FRACTIONAL±1/64 ANGULAR: MACH±1° BEND±1° ONE PLACE DECIMAL ±.015 TWO PLACE DECIMAL ±.010	DRAWN CHECKED ENG APPR.		JCN 5/13		310 CHADDICK DR, WHEELING, IL. 60090 TITLE:			
					THREE PLACE DECIMAL ±.005	MFG APPR. Q.A.				-	RSI	<b>-9200</b>	SERIES
										SIZE	DWG. NO.		
						THE INFORMAT DRAWING IS TH REMKE INDUST	HE SOL RIES. A	LE PROPERTY ANY REPROE	OF OUCTION	A			ASSEMBLY
					DO NOT SCALE DRAWING		PART OR AS A WHOLE WITHOUT TH ITTEN PERMISSION OF REMKE INDU ROHIBITED.			SCAL	E: 1:1		SHEET 1 OF 1
		5	4		3				2				1